CONDITIONS OF APPROVAL, IF ANY:


UNITED STATES DEPARTMENT OF THE INTERIOR



Form approved, Budget Bureau No. 42-R1425.

	DEPARTMEN	5. LEARE DESIGNATION AND SERIAL NO.		
	GEOLG			
APPLICATION	1 FOR PERMIT	BACK 6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
Ia. TYPE OF WORK	LL 🛛	DEEDEN []	DI UC DA	7. UNIT AGREEMENT NAME
b. TYPE OF WELL	LL [A	DEEPEN [PLUG BA	
OIL X GA	S X OTHER		INGLE MULTIP	Allen Federal 8. FARM OR LEASE NAME.
2. NAME OF OPERATOR	The state of the s	***************************************		
DIAMOND SHAM	TROCK		***	9. WELL NO.
3. Address of operator				/ #32-6
Drawer E, Ve	ernal, Utah 84	078 801-789-52 d in accordance with any s	70	10. FIELD AND POOL, OR WILDCAT
At surface				Fiold Monument
		on 6, T9S, R17E,	S.L.B.& M.	11. SEC., T., R., M., OR BLK. BUHE
At proposed prod. zone Same	SWN	と		Sec. 6, T9S, R17E, S.L.B.&
	ND DIRECTION PROM NE	REST TOWN OR POST OFFIC	E.	12. COUNTY OR PARISH 13. STATE
13 miles Sou	thwest of Myto	on, Utah		Duchesne. Utah
 DISTANCE FROM PROPO LOCATION TO NEAREST 	SED*		O. OF ACRES IN LEASE	17. NO. OF ACRES ASSIGNED TO THIS WELL
PROPERTY OR LEASE L. (Also to nearest drig	. unit line, if any)	1949	640 . 2 .	40
18. DISTANCE FROM PROPO TO NEAREST WELL, DR	HLLING, COMPLETED,		ROPOSED DELTH	20. ROTARY OR CABLE TOOLS
OR APPLIED FOR, ON THIS	•	N/A	5300' MUN; W	Rotary
1. ELEVATIONS (Show whe	324		PM	22. APPROX. DATE WORK WILL START*
3. V		· · · · · · · · · · · · · · · · · · ·		A.S.A.P.
		PROPOSED CASING ANI	D CEMENTING PROGRA	AM The state of th
SIZE OF HOLE	SIZE OF CASING	WEIGHT PER POOT	SETTING DEPTH	QUANTITY OF CEMENT
12½"	8 5/8"	24#_K-55	250'	Circulate to surface
7 7/8"	5 ¹ ⁄2 '	_15.5# K-55	T.D. 5300'	300 sacks
			"	
Dr	ill 12½" hole	to approximatel	v 250° set 8 5/	8" casing, set up BOP
as	required and	pressure test.	Drill 7 7/8" h	ole to approximately
53	00' if product	ion is found fe	asable set 5½"	production casing.
•	API	PROVED BY TH	E DIVISION	그는 그렇다 있는 사람들이 뭐 됐다.
		OIL, GAS, AND		
		1/2/5		
·	DA*	E:		그 그 그 한 지수는 없는 사람이 하셨다면요?
	BY:	Bylly	NUT	그는 그는 그 있는 사람 사람 중 중심을 다 되었다.
N ABOVE SPACE DESCRIBE	PROPOSED PROGRAM: If	proposal is to deepen or p	olug back, give data on pr	resent productive zone and proposed new productive
reventer program, if any		any, give pertinent data o	on subsurface locations an	d measured and true vertical depths. Give blowout
1.				
SIGNED DILL EL	Patt-	mini e D	istrict Superin	tendant 12/20/80
(IV) I a series of the series	F11. A	TEVIE	- WALLEY HOLDER III	LEHUGHL PATE 12/27/01
(This space for Feder	at or State office use)			
PERMIT NO.	4		APPROVAL DATE	
. Titanas un nur				그는 그는 사람들은 사람들은 사람들이 가지 않는데 그 것이 없다.

T 9 S, R 17 E, S.L.B. & M.



X = Section Corners Located

PROJECT

DIAMOND SHAMROCK

Well location, ALLEN FEDERAL 32-6, located as shown in the SW 1/4 NE1/4 Section 6
T9S, R17E, SLB&M
Duchesne County, Utah




THIS IS TO CERTIFY THAT THE ABOVE PLAT WAS PREPARED FROM FIELD NOTES OF ACTUAL SURVEYS MADE BY ME OR UNDER MY SUPERVISION AND THAT THE SAME ARE TRUE AND COMPRET TO THE BEST OF MY KNOWLEDGE AND BELIEF

REGISTERED LAND SURVEYOR REGISTRATION NO. 3154

PO BOX Q - 85 SOUTH - 200 EAST VERNAL, UTAH - 84078

LINONO SHAMROCK



1. GEOLOGICAL NAME OF SURFACE FORMATION

(A) Uinta Formation of Eocene Age

2. TOPS OF IMPORTANT GEOLOGICAL MARKERS

- (A) Mahogany Formation 3060'
- (B) Garden Gulch Formation 3630'
- (C) Douglas Creek Formation 4610'

3. ESTIMATED DEPTHS OF ANTICIPTAED WATER, OIL OR GAS

- (A) Gas anticipated at 2600' in Evacuation Creek Member (Water or Oil no anticipated)
- (B) Oil & Gas anticipated in Basal Green River Formation (Douglas Creek at 5300'

4. PROPOSED CASING PROGRAM

(A) 250' of 8 5/8" surface casing 32# per foot. 3150' of $5\frac{1}{2}$ " 15.5# per foot. (K-55)

5. SPECIFICATION FOR PRESSURE CONTROL EQUIPMENT

- (A) 12 inch 3000# Double Hydraulic B.O.P. with Pipe Rams and Blind Rams and Spherical BOP.
- (B) B.O.P. to be pressure tested before spudding and daily testing of closing units and rams while drilling.

6. PROPOSED CIRCULATING MEDIUM

(A) Brine water is proposed to be used unless additional weight is needed to control pressures or heaving shale. In this event a chemical-gel fresh water mud will be used and Barite as needed to control pressure.

7. AUXILIARY EQUIPMENT TO BE USED

- (A) Upper Kelly Cock
- (B) Float At Bit
- (C) Floor T.I.W. Valve (stabbing valve) for drill pipe
- (D) Gas Detector Logging Unit

8. TESTING LOGGING AND CORING PROGRAM


- (A) Drill stem test of Evacuation Creek and Douglas Creek
- (B) Will run dual lateralog, BHC, and CNL-FDC .

9. ANTICIPATED ABNORMAL PRESSURES, TEMPERATURES OF HAZARDS

- (A) No abnormal pressures expected
- (B) No Hydrogen Sulfide Gas expected

10. STARTING DATE AND DURATION OF OPERATIONS

- (A) Anticipated starting date as soon as approvals are made.
- (B) This well is anticipated to be drilled in approximately 30 days.



DIONOVE TREVENUTE VAN CLUBES RAMS; ONS ELIND AND ONS ELIN RAM;

Ding. A

DIAMOND SHAMROCK

13 Point Surface Use Plan

For

Well Location

Allen Federal #32-6

Located In

Section 6, T9S, R17E, S.L.B.& M.

Duchesne County, Utah

1. EXISTING ROADS

To reach DIAMOND SHAMROCK well location, Allen Federal #32-6 located in the SW4 NE4 Section 6, T9S, R17E, S.L.B.& M., Duchesne County, Utah; proceed Southwesterly out of Myton, Utah along U.S. Highway 40-1.5 miles to the junction of this Highway and Utah State Highway 53, to the South; proceed Southerly along this Highway 1.5 miles more or less, to the intersection of Utah State Highway 53 and Utah State Highway 216, thence proceed Southeasterly along Utah State Highway 216 9.9 miles to the junction of this road and an existing road to the Southwest; proceed Southwesterly along this service road 1.4 miles to the point at which the planned access road (to be discussed in Item #2) leaves the existing road and proceeds in a Northwesterly direction.

The Highway mentioned in the foregoing paragraph are bituminous surfaced roads up to the intersection of Utah State Highway 53 and 216, at which point Utah State Highway 216 is constructed out of existing native materials that are prevalent to the existing area it is located in and ranges from clay to sandy-clay shale materials, as are the aforementioned dirt oil field service roads and other roads in the vicinity.

There is no anticipated construction on any portion of the above described roads. They will meet the necessary standards required to facilitate an orderly flow of traffic during the drilling phase, completion phase, and production phase of the well. These roads will be maintained at the standards required by the B.L.M. or other controlling agencies.

2. PLANNED ACCESS ROAD

See Topographic Map "B".

The proposed access road leaves the existing service road in the SE4 NW4 Section 6, T9S, R17E, S.L.B.& M., and proceeds in a Southeasterly direction for a distance of 800' more or less to the proposed location site.

In order to facilitate the anticipated traffic flow necessary to drill and produce this well, the following standards will be met:

This proposed access road will be an 18' crown road (9' either side of the centerline) with drain ditches along either side of the proposed road where it is determined necessary in order to handle any run-off from normal meterological conditions that are prevalent to this area.

Back slopes along the cut area of the road will be 12 to 1 slopes and terraced.

The road will be centerline flagged prior to the commencement of construction.

The grade of this road will vary from flat to 8% but will not exceed this amount. This road will be constructed from native borrow accumulated during construction.

2. PLANNED ACCESS ROAD - cont...

There will be no culverts required along this access road.

If deemed necessary by the local governmental agencies or their representatives, turnouts will be installed for safety purposed every 0.25 miles or on the top of ridges or at interval and location that will proved the greatest sight distance. These turnouts will be 200' in length and 10' in width and will be tapered from the shoulder of the road for a distance of 50' in length at both the access and outlet ends.

Since there are no fences along this road, there will be no cattleguards required.

The vegetation along this route consists of sparse amounts of sagebrush, rabbitbrush, some grasses and cacti with large areas that are devoid of vegetation.

3. LOCATION OF EXISTING WELLS

See Topographic Map "B".

There are no known producing wells, abandoned wells, temporarily abandoned wells, water wells, disposal wells, drilling wells, shut in wells, injection wells, monitoring or observation wells for other resources within a one mile radius of this location site.

4. LOCATION OF EXISTING AND PROPOSED FACILITIES

There are no DIAMOND SHAMROCK tank batteries, production facilities, oil gathering lines, gas gathering lines, injection lines, or disposal lines within a one miles radius of this location site.

In the event that production is established, plans for a flowline from this location to existing lines in the area will be submitted to the proper authorities and the existing area of the location will be utilized for the establishment of the necessary production facilities.

The total area that is needed for the production of this well will be fenced and cattleguards will be utilized for access to these facilities.

The area will be built if possible, with native materials and if these materials are not available, then the necessary arrangements will be made to get them from private sources.

These facilities will be constructed using bulldozers, graders, and workman crews to construct and place the proposed facilities.

If there is any deviation from the above, all appropriate agencies will be notified.

Rehabilitation of disturbed areas no longer needed for operation after construction is completed will meet the requirements of Item #10.

5. LOCATION OF AND TYPE OF WATER SUPPLY

Water to be used for the drilling and production of this well will be hauled by truck from the Duchesne River, at a point where Highway 40 crosses it North of Myton, Utah, approximately 14.4 miles to the Northeast of the proposed location site.

In the event that the above sources is not used, other arrangements will be made with the proper authorities for an alternate source.

All regulation and guidelines will be followed and no deviations will be made unless all concerned agencies are notified.

There will be no water well drilled at this location site.

6. SOURCES OF CONSTRUCTION MATERIALS

All construction material for this location site and access road shall be borrow materials accumulated during the construction of the location site and access road. No additional road gravels or pit lining materials from other sources are anticipated at this time, but if they are required, the appropriate actions will be taken to acquire them from private sources.

The native materials that will be used in the construction of this location site and access road will consist of a sandy-clay soil and sandstone and shale material gathered in actual construction of the road and location.

7. METHODS FOR HANDLING WASTE DISPOSAL

A reserve pit shall be constructed, and at least half of the depth of the reserve pit shall be below the existing ground surface. Non-flammable materials such as cuttings, salts, chemicals, etc., will be buried in the reserve pit and covered with a minimum of four feet of earth material. Prior to the onset of drilling, the reserve pit will be fenced on three sides. Upon completion of drilling, the fourth side of the reserve pit will be fenced and allowed to dry completely before backfilling and reclamation are attempted. A portable toilet will be supplied for human waste.

A trash basket will be provided for flammable materials. Waste will be hauled by truck to the nearest sanitary landfill.

8. ANCILLARY FACILITIES

There are no ancillary facilities planned for at the present time and none foreseen in the near future.

9. WELL SITE LAYOUT

See attached Location Layout Sheet.

The B.L.M. District Manager shall be notified before any construction begins on the proposed location site and road.

9. WELL SITE LAYOUT - cont...

As mentioned in Item #6, the pits will be unlined unless it is determined by the representatives of the agencies involved that the materials are too porous and would cause contamination to the surrounding area; then the pits will be lined with a gel and any other type of material necessary to make it safe and tight.

10. PLANS FOR RESTORATION OF SURFACE

As there is some topsoil on the location site, all topsoil shall be stripped and stockpiled. (See Location Layout Sheet and Item #9). When all drilling and production activities have been completed, the location site and access road will be reshaped to the original contour and stockpiled topsoil spread over the disturbed area. Fences around pits are to be removed upon completion of drilling activities and all waste being contained in the trash basket will be hauled to the nearest sanitary landfill. The reserve pit will be completely fenced and allowed to dry before covering. When restoration activities have been completed, the location site and access ramp shall be reseeded with a seed mixture recommended by the B.L.M. District Manager when the moisture content of the soil is adequate for germination. The Lessee further covenants and agrees that all of said cleanup and restoration activities shall be done and performed in a diligent and most workmanlike manner and in strict confomity with the above mentioned Items #7 and #10.

11. OTHER INFORAMTION

The Topography of the General Area - (See Topographic Map "A").

The area is a basin that lies between the Book Cliff Mountains to the South and the Uinta Mountains to the North. The area is interlaced with numerous canyons and ridges which are extremely steep with numerous ledges formed in sandstone, conglomerates, and shale deposits.

The majority of the washes and streams in the area are non-perennial streams and flow to the Southeast and are tributaries to the Green River.

The soils of the semi-arid area are of the Uinta Formation and Duchesne River Formation (the Fulivial, Sandstone, Mudstone) from the Eocene and Quarternary Epoch (gravel surfaces) and the visible geologic structures consist of light brownish clay (OL) to sandy soils (SM-ML) with poorly graded gravels and shales with outcrops of rock (sandstone, mudstone, comglomerates, and shales).

Due to the low precipitation average, climatic conditions and the mariginal types of soils, the vegetation that is found in the area is common of the semi-arid region we are located in and in the lower elevation of the Uinta Basin. It consists of, as primary flora, areas of sagebrush, rabbitbrush, some grasses, and cacti, and large areas of bare soils devoid of any growth. In the areas that are formed along the edges of perennial streams cottonwoods, willows, tamarack, sagebrush, rabbitbrush, grasses and cacti can be found.

11. OTHER INFORMATION - cont..

The fauna of he area is sparse and consists predominantly of the mule deer, coyotes, pronghorn antelope, rabbits, and varieties of small ground squirrels and other type of rodents, and various reptiles common to the area.

The birds of the area are raptors, finches, ground sparrow, magpies, crows and jays.

The area is used by man for the primary purpose of grazing domestic livestock.

The Topography of the Immediate Area (See Topographic Map "B").

Allen Federal #32-6 location site sits on a sloping hillside Northwest of Castle Peak Draw which drains into the Green River which is located approximately 14 miles to the East of the location.

The geologic structure of the location is of the Uinta Formation and consists of light brownish-gray sandy clay (SP-CL) with some sandstone outcrops.

The ground slopes from the South through the location to the North at approximately a 2% grade., into a small non-perennial drainage which drains to the East into the above mentioned Castle Peak Draw.

The location is covered with some sagebrush and grasses.

There are no occupied dwellings or other facilities of this nature in the general area.

There are no visible archaeological, historical, or cultural sites within any reasonable proximity of the proposed location site. (See Topographic Map "B").

12. LESSEE'S OR OPERATOR'S REPRESENTATIVE

Bill Elliott DIAMOND SHAMROCK Drawer E Vernal, Utah 84078

1-801-789-5270

13. CERTIFICATION

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drill site and access route; that I am familiar with the conditions which presently exist; that the statements made in this plan are, to the best of my knowledge, true and correct; and that the work associated with the operation proposed herein will be performed by DIAMOND SHAMROCK and its contractors and subcontractors in conformity with this plan and terms and conditions under which it is approved.

Dec 29, 1980

Date

Bill Elliott

District Supervisor

[dentification	CER/EA	No.	219-81

United States Department of the Interior
Geological Survey
2000 Administration Bldg.
1745 West 1700 South
Salt Lake City, Utah 84104

NEPA CATEGORICAL EXCLUSION REVIEW

PROJECT IDENTIFICA	TION	
OperatorDiamo	nd Shamrock	•
Project Type0i	1 and Gas Well Drillin	lg
Project Location _	1949' FEL 2102' FNI	Section 6, T. 9S, R. 17E
Well No. 32-6	Allen Federal L	ease No. <u>U-020252-A</u>
Date Project Submi	tted <u>Decembe</u>	r 30,1980
FIELD INSPECTION		
Field Inspection Participants	Greg Darlington	USGS, Vernal
	Gary Slagel	BLM, Vernal
	Bill Elliot	Diamond Shamrock
	Gene Stewart	Uintah Engineering
		·
	. :	
Related Environmen	tal Documents:Ur	nit Resource Analysis, Duchesne Planning
Unit, BLM, Ver	na1	
guidelines. This	proposal would not inv	ce with the categorical exclusion revie olve any significant effects and, there the categorical exclusions.
February 3,	1981	Gregory Darlington
Date Pr	epared	Edvironmental Scientist
I concur	e/	Ewleynu
. / Da	te	District Supervisor

Typing Out

2-3-81

PROPOSED ACTION:

Diamond Shamrock proposes to drill the Allen Federal 32-6 well, a 5300 foot test for hydrocarbons in the Evacuation Creek Member and Basal Green River Formations. An 800 foot long new access road with an 18 foot wide driving surface with drainage ditches where needed is proposed. A pad 135 feet by 300 feet and a reserve pit 75 feet by 150 feet are requested for the proposed location. About 1.6 acres of new disturbance would be involved.

RECOMMENDED APPROVAL CONDITIONS:

Drilling should be approved provided the operator agrees to incorporate the following additional measures into the APD and drilling plans and adhere to them:

- 1. BLM Stipulations
- 2. Lease Stipulations
- 3. Adequate logs will be furnished as requested by the Mineral Evaluation
 Report and Mining Report for the evaluation of other potentially
 valuable resources such as oil shale.

FIELD NOTES SHEET


Date of Field Inspection: January 30, 1981
Date of Field Inspection: January 30, 1/81
Well No.: Allen Ederal 32-6
Lease No.:
Approve Location:
Approve Access Road:
Modify Location or Access Road: Recommended making pit mue
numer, regusted no wider that the 75 feet of the layout.
nerow requested no wider lash the 15 feel of the earlow
diagrem, Continued against getting put anycloser than
The state of the s
presently staked to a small draininge.
c d thanks for Cotogorical Exclusion
Evaluation of Criteria for Categorical Exclusion
1. Public Health and Safety
2. Unique Characteristics
- 11. Companyordial Items
t tile and Dicke
and the Description of the Control o
5. Establishes Precedents .
6. Cumulatively Significant
7. National Register Historic Places
8. Endangered/Threatened Species
9. Violate Federal, State, Local, or Tribal Laws
If this project is not eligible for Categorical Exclusion circle the numbers of
the above criteria requiring the preparation of an EA.
the above criteria requiring the proportion
Comments and special conditions of approval discussed at onsite: (include local
Comments and special conditions of approve
topography) Location is OK, Monnevannial drainage
1 de la fl
is to the north rear the reserve pits.
BLM led 13 point plan at time of the orisite from Hintak Engineering Copy
Official APD copy wrived Tebruary 4.
TETTOWN TILL PLUT PUR CONTROL TO THE PROPERTY OF THE PROPERTY

CATEGORICAL EXCLUSION REVIEW INFORMATION SOURCE


		Feder. Corre-	al/State A	gency	Local and private corre-		Other studies	·	Onsite	
	Criteria 516 DM 2.3.A	spondence (date)	check (date)	Meeting (date)	spondence (date)	Previous NEPA	and reports	Staff expertise	inspection (date)	Other
ι.	Public health and safety	·	v					1, 2, 3, 6	1-30-81	
	Unique charac- teristics							1, 2, 3,6	/-30	
3.	Environmentally controversial							1,2,3,6	/-30	Ç.
4.	Uncertain and unknown risks	r						1, 2, 3, 6	/-30	
5.	Establishes precedents	14	·					1,2,3,6	1-30	
6.	Cumulatively significant						•	1, 2, 3,6	1-30	
7.	National Register historic places	\$ 11			. •			1,6	/-30	
8	Endangered/							1,6	1-30	
9	. Violate Federal, State, local, tribal law							1, 2, 3,6	/-30	

CATEGORICAL EXCLUSION REVIEW COMMON REFERENCE LEGEND

- Surface Management Agency Input
- Reviews Reports, or information received from Geological Survey (Conservation Division, Geological Division, Water Resource Division, Topographic Division)
- Lease Stipulations/Terms
- 4. Application Permit to Drill
- 5. Operator Correspondence
- 6. Field Observation
- 7. Private Rehabilitation Agreement
- 8. USGS conditions of approval



South View of Allen 32-6 Diamond Shamrock



1" = 50"

DATE: January 2 1981
OPERATOR: Diamond Shamrock
WELL NO: Allen Foderal #32-6
Location: Sec. 6 T. 95 R. 17E County: Duchesne
File Prepared: Entered on N.I.D:
Card Indexed: Completion Sheet:
API Number 43-013-30559
CHECKED BY:
Petroleum Engineer: M.J. Mundy
Director: OR C-3
Administrative Aide: C-3 spacing
APPROVAL LETTER:
Bond Required: Survey Plat Required:
Order No O.K. Rule C-3
Rule C-3(c), Topographic Exception - company owns or controls acreage within a 660' radius of proposed site
Lease Designation 100 Plotted on Map 1
Approval Letter Written
Hot Line P.I.

January 9, 1981

Diamond Shamrock Drawer b Vernal, Utah 84078

Re: Well No. Allen Federal #32-6 Sec. 6, T. 9S, R. 17E Duchesne County, Utah

Insofar as this office is concerned, approval to drill the above referred to o/g is hereby granted in accordance with Rule C-3, General Rules and Regulations and Rules of Practice and Procedure.

Should you determine that it will be necessary to plug and abandon this well, you are hereby requested to immediately notify the following:

MICHAEL T. MINDER - Petroleum Engineer Office: 533-5771 Home: 876-3001

Enclosed please find Form OGC-8-X, which is to be completed whether or not water sands (Acquifers) are encountered during drilling. Your cooperation in completing this form will be appreciated.

Further, it is requested that this Division be notified within 24 hours after drilling operations commence, and that the drilling contractor and rig number be identified.

The API number assigned to this well is 43-013-30559.

Sincerely,

DIVISION OF OIL, GAS, AND MINING

Cleon B. Feight Director

/ko

cc: USGS

Form approved. Budget Bureau No. 42-R1425.

5. LEASE DESIGNATION AND SERIAL NO.

DEPARTMENT OF THE INTERIOR

	GEOLO	GICAL SURVE	Y			U-020252-A
APPLICATIO	N FOR PERMIT	TO DRILL, D	EEPE	N, OR PLUG B	ACK	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
b. TYPE OF WELL	ILL X	DEEPEN [81	PLUG BAC		7. UNIT AGREEMENT NAME Allest Fodoral 8. FARM OR LEASE NAME.
WELL X	VELL X OTHER		20	NE L ZONE	<u> _</u>	
	MAN CAM.					9. WELL NO.
DIAMOND SHA ADDRESS OF OPERATOR	MROCK Corp.			•		#32-6
Drawer F V	Jornal IItah 84	078 801-789	-52	70		10. FIELD AND POOL, OR WILDCAT
LOCATION OF WELL (F	Vernal, Utah 84 Report location clearly and	in accordance with	any S	tate requirements.*)		Field
At surface 1949' FEL 2	102' FNL Section	n 6, T9S, R1	7E,	S.L.B.& M.		11. SEC., T., R., M., OR BLE.
At proposed prod. zo			-			
same						Sec. 6, T9S, R17E, S.L.B.&
	AND DIRECTION FROM NEA		offici	•		12. COUNTY OR PARISH 13. STATE
	uthwest of Myto		10 NO	, OF ACRES IN LEASE	1 17 NO	Duchesne Utah OF ACRES ASSIGNED
	T LINE, FT. Ig. unit line, if any)	1949		640	тол	rhis well 40
OR APPLIED FOR, ON TH	DRILLING, COMPLETED, HIS LEASE, FT.	N/A		oposed depth 5300 [†]	20. ROT.	Rotary 22. APPROX. DATE WORK WILL START*
	hether DF, RT, GR, etc.)				<u>:</u>	A.S.A.P.
3.		PROPOSED CASING	ANE	CEMENTING PROGRA	м }	
SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOO	T	SETTING DEPTH		QUANTITY OF CEMENT
12½"	8 5/8"	24# K-55		250'	_Circ	rulate to surface
7 7/8"	5½'	15.5# K-55		T.D. 5300'	300	sacks
N ABOVE SPACE DESCRIB	is required and 300° if product	pressure testion is found	fe.	Drill 7 7/8" h asable set 52"	ole to	cassing of alternion militarine and frequence of the state of the stat
one. If proposal is to reventer program, if an	drill or deepen direction	ally, give pertinent	data o	n subsurface locations an	d measur	ed and frue vertical depths. Give blowout
SIGNED BUE	elatt	TITL	= _D	istrict Superin	tendar	nt 12/29/80
(This space for Fed	eral or State office use) .					The state of the s
PERMIT NO.			 F0	APPROVAL DATE E. W. GUYNN DISTRICT ENGIN	EER	FEB 19 1981
APPROVED BY (Ori CONDITIONS OF APPRO	VAL, IF ANY :	enricks TITL ONDITIONS O	.	PPROVAL ATTAC	:	DATE OF THE PARTY

NOTICE OF APPROVAL

TO OPERATOR'S COPY

FLARING OR VENTING OF GAS IS SUBJECT TO NTL 4-A **DATED 1/1/80**

extel out and of me



United States Department of the Interior

T & R U-801

VERNAL DISTRICT OFFICE 170 South 500 East Vernal, Utah 84078

January 30, 1981

Ed Guynn, District Engineer USGS, Conservation Division 2000 Administration Building 1745 West 1700 South Salt Lake City, Utah 84104

Re: Joint on site Investigation
Diamond Shamrock Corporation
T9S, R17E, Sec. 6
Allen Federal #32-6
Allen Federal #23-6

Dear Mr. Guynn:

On January 30, 1981 a joint on site inspection was made of the above referenced well site locations and proposed access roads by people representing Diamond Shamrock Corporation, USGS, and the BLM. We feel that the surface use and operating plans are adequate with the following stipulations:

- Construction and maintenance of roads, rehabilitation of disturbed areas, and construction of pipeline routes shall be in accordance with surface use standards as set forth in the booklet, "Surface Operating Standards for Oil and Gas Exploration and Development."
- 2. The maximum width of access roads will be 30 feet total disturbed area. Turnouts will not be required and traveling off the right-of-way will not be allowed.
- 3. Topsoil will be stockpiled as addressed in the applicants 13 point plan. Our office recommends the top 6-10 inches of soil materials be stockpiled.
- 4. The BLM will be notified at least 24 hours prior to any construction.
- 5. The BLM will be notified at least 24 hours prior to any rehabilitation.



- 6. A burn pit will not be constructed. There will be no burying of garbage or trash at the location. All trash must be contained and hauled to an approved disposal site.
- 7. All permanent (on site for six (6) months duration or longer) structures constructed or installed shall be painted a flat (non-reflective) earth tone color to match Pittsburgh Paints "Moccasin," number M3492. Facilities that are required to comply with O.S.H.A. (Occupational Safety and Health Act) standards are excluded.

An Archaelogical clearance has been conducted by Archaelogical - Environmental Research Corporation of the proposed drill sites and access roads. No cultural materials were located on the surface of the survey areas.


The proposed activities do not jeopardize listed, threatened or endangered flora/fauna and their habitats.

Sipeekely,

Ralph J. Heft Area Manager

Diamond Mountain Resource Area

cc: USGS, Vernal






32-6

4920' - 498

DIAMOND SHAMROCK CORPORATION





Each Horizontal Line Equal to 1000 p.s.i.

FLUIC	SAMPL	E DATA	,	Date 5-4-8	3]	Ticket Number	83631	5	Legal L Sec T	
Sampler Pressure	95		at Surface K	ind f DST open	1101 F	Halliburto Location	on VERNA	\ 1	Location - Twp Rng	. ≥
Recovery: Cu. Ft. (Gas <u>40</u> 140		F	f D.S.T. OPEN	HULE		VERINA	١	g G	ALLEN
cc. Oil cc. Wate		<u> </u>	т	ester MR [RICH	Witness	MR. F	OSTER		
cc. Mud	100			Drillina						Lease Name
	ıid cc. <u>150</u>			ontractor BRINI			#85	[C	SE	
	° /	_	°F		JIPMENT	reen River	DATA		<u>ا</u>	P
Gas/Oil Ratio	RESISTI			ormation Testec			5333' KE	3Ft.	6	
	RESISTI	COI	NTENT !	Net Productive I	2	0'		Ft.	<u> </u>	
Recovery Water	@	°F		All Depths Meas	ared FromK	elly Bushin	g		98	
Recovery Mud		°F	1 .	otal Depth		987		Ft.	1	
Recovery Mud Filts		°F		Main Hole/Casir	-	7/8"	2.37		17	
Mud Pit Sample	<u>2</u> @	_60_ ∘ _{F.} _3		Orill Collar Leng		82.34' 1.D 305' 1.D.			П	32-6 Well No.
Mud Pit Sample Fi	ltrate@	°F	ppm	Orill Pipe Length Packer Depth(s)_		912' - 4920		Ft.		N N
Mud Weight	9.1	vis	20 I	Depth Tester Va		895'		Ft.		0
TYPE Cushion	AMOUNT	Ft.	Depth Back Pres. Valve		Surface Choke]	/8" x 1" Cho	tom oke .75"			7.0
Recovered 190	Feet	of OIl cu	t mud						Field Area	Test No.
Recovered		D	wy fluid	800 nnm	chromates	as per muc	l logger	Meg. F	l°°	
Recovered	Feet	of Recove	ry Hulu	- ooo ppiii	- TH Olla CES	us per mue	· rogger	13		
Recovered	Feet	of						Tester Valve	SOUTH	
								\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	l₽	
Recovered	Feet	of							3	1
Recovered	Feet	of							MYTON	1920 Tes
		E DRODUCT	TON TECT	DATA CHEET					Z	ested
Remarks	<u> </u>	E PRODUCT	IUN IEST	DATA SHEET	•				1	Tested Interval
									-	nterval
									County	
	Gauge No. 20)5	Gauge No.	192	Gauge No.			ME	DUCHE	
TEMPERATURE		897' Ft.	Depth:	4984' _{Ft.}	Depth:	Ft.		4:00 hrs.)	1S	1
	12			12Hour Clock	- 1 1 A	Hour Clock	Tool Opened 1	7.48	SNE	
Est. °F.	Blanked Off NC)	Blanked Off	YES	Blanked Off		Opened 1	7.40	1	
4 · 1 120=	D		Pro	ssures	Pre	essures		0:34		
Actual 30°F.	Press	Office	Field	Office	Field	Office	Reported	Computed	1	E
Initial Hydrostatic	Field 2334	2341.2	2410	2378.6			Minutes	Minutes	<u> </u>	ose
lmitial	27	20.9	54	65.9					State	Own I
Flow Final	55	34.0	81	69.1			15	*	 €	er/0
Closed in	1672	1660.9	1702	1698.6	<u></u>		31		HATU	om 7
Flow Initial	55	42.1	81	80.0		 	120	*	┤ [≖]	Lease Owner/Company Name
Final_	137	107.7	135 1784	138.8 1840.4		-	240	*	1	Non
Closed in Initial	1810	1804.4	1/04	1040.4					1	6 3
Flow Final	*See attac	ched incre	mental re	ading shee	t.]	
	Jee acca	,,, <u>,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,</u>								
Closed in								*		
Closed in Final Hydrostatic	2306	2333.4	2355	2371.1					-	

Casing perfs		Bottom	choke	.75"	Surf. temp°F Ticket No836315
Gas gravity		Oil grav	ity		GOR PAGE #1
Spec. gravity	AND SIZE	Chloride	URING DEVICE !	USEDPP	m Kes
	AND SIZE	OI GAS MEAS			
Date Time a.m. p.m.	Choke Size	Surface Pressure psi	Gas Rate MCF	Liquid Rate BPD	Remarks
12:00					On location-rig pulling drill pipe.
13:30					Started to pick up tools.
15:00					Started in hole.
17:45		00 "			Set packers.
17:48		30# GAUGE			Opened tool.
17:49	1/8"	0	.528		l" blow in water.
17:50	11	0	1.06		4" "
17:51	11	0	1.39		7" "
17:55	11	0	1.83		12" "
18:00	н	0	1.83		12" "
18:03		20# GAUGE			CLosed tool for closed in pressure-blow continued throughout closed in.
18:34	11	7 1/2	z. 1.91		Opened tool with 20 oz. gauge on line.
18:39	11	9 oz.	2.05		20 oz. gauge on line.
18:44	11	10 oz.	2.18		п
18:49	11	14 oz.	2.59		п
18:54	11	15 oz.	2.69		п
18:59	11	16 oz.	2.79		11
19:00	11				Opened to 2" flare line.
19:25	п				Closed back to bubble hose-1/8" ID.
19:30	н	5 oz.	1.59		20 oz. gauge on line.
19:35	11	6 oz.	1.67		II
19:40	11	10 oz.	2.18		п
19:45	11	12 oz.	2.40		II .
19:50	11	15 oz.	2.69		П
19:55	п	16 oz.	2.79		н

Gos gravity		Oil ara	vitv		Surf. temp•F Ticket No836315 GORPAGE #2
Spec. gravity		Chlorid	SURING DEVICE U	Pr	om Res
Date Time a.m. p.m.	Choke Size	Surface Pressure psi	Gas Rate MCF	Liquid Rate BPD	Remarks
20:00	1/8"	16 oz.	2.79		20 oz. gauge on line.
20:05	н	18	2.90	,	II .
20:10	11	18	2.90		П
20:15	11	18	2.90		П
20:20	11	18	2.90		u .
20:25	П	18	2.90		п
20:30	н	18	2.90		п
20:34					Closed tool for closed in pressure.
21:00	п	16	2.79		Gas to surface.
21:10					3" flare on 2" line pipe.
00:34					Pulled tool loose.
03:45					Out of hole.
06:00					Operator released.
06:00					End of job.
			·		
	-				

DIAMOND SHAMROCK CORPORATION Lease Owner/Company Name

836315 Ticket Number PAGE #1

B.T. 205	
----------	--

B.T.___192____

B.T.____

Depth 4897'-12 Hr.

Depth 4984'-12 Hr.

Depth____

Time Minutes	$Log \frac{t + \theta}{\theta}$	PSIG Temp. Corr.	Time Minutes	$Log \frac{t+\theta}{\theta}$	PSIG Temp. Corr.	Time Defl. .000''	$Log \frac{t+\theta}{\theta}$	PSIG Temp. Corr.
First Fl	wc		First F	low				
0		20.9	0		65.9			
3		22.0	3		60.3			
6		25.9	6		61.4			
9		28.2	9		64.6			
12		25.9 28.2 31.3	12		67.2			
14.3		34.0	14.6		67.2 69.1			
Initial	CIP		Initia	CIP				
0		34.0	0		69.1			
3	-	215.7	3		259.9			
6		466.7	6		501.2			
9		753.0	9		772.0			
12		1007.2	12		1016.9			
15		1272.5	15		1285.2			
18		1421.4	18		1445.8			
21		1514.6	21		1542.4			
24		1578.0	24		1611.d			
27		1623.7	27		1660.2			
30.3		1660.9	30.3		1698.6			
Second F	low		Second	Flow				
0		42.1	0		80.0			
15		58.0	15		92.0			
.30		66.3	30		99.6			
45		72.5	45		104.9			
60		80.4	60	-	112.0			
75		87.6	75		119.5			
90		94.4	90		125.8			
105		100.1	105		132.3			
121.8		107.7	122.3		138.8			
Second C	IP		Second	CIP				
0		107.7	0		138.8			
15		825.4	15		836.0	<u> </u>		
30		1429.8	30		1448.1	1		
45		1663.1	45		1691.6			
60		1735.5	60		1766.4			
75		1761.2	75		1795.2			
90		1776.7	90		1810.5			
105		1786.4	105		1820.8			
120		1793.1	120		1826.4			
135		1796.8	135		1831.7	↓	ļ	
150		1798.6	150	1	1833.7	1	J	

Kemarks:

DIAMOND SHAMROCK CORPORATION
Lease Owner/Company Name

836315 Ticket Number PAGE #2

B.T.	205	
D	205	

B.T. <u>192</u>

B.T.____

Depth 4897'-12 Hr.

Depth 4984'-12 Hr.

Depth____

t + θ PSIG Temp. Continued 1800.8 1801.9 1803.4 1804.4 1804.4		Second 165 180 195 210 225 239.6	$\frac{t + \theta}{\theta}$ CIP cor	tinued. 1836.1 1837.5 1838.3 1839.5 1839.5			
1800.8 1801.9 1801.9 1803.4 1804.4		180		1837.5 1838.3 1839.5 1839.5			
1801.9 1801.9 1803.4 1804.4		180		1837.5 1838.3 1839.5 1839.5			
1801.9 1803.4 1804.4 1804.4		195 210 225 239.6		1838.3 1839.5 1839.5 1840.4			
1803.4 1804.4 1804.4		210 225 239.6		1839.5 1839.5 1840.4			
1804.4 1804.4		225 239.6		1839.5 1840.4			
1804.4		239.6		1840.4			
1004.4		239.0		1040.4			
					 	 	
					 		
				 	 	 	
				 	 	 	
	#				 	1	
					 	 	
	Ц.					 	
	Ш				↓		
	Ш				<u> </u>		
	Π						
	П						
	11						
	$\dagger \dagger$						
	Ħ				1		
	H				1		
	H				 		
	H			 	 		
	H				 		
	╂			 	1		
	₩			 	 	 	
	₩			 	 	 	
	₩		<u> </u>	 	 		
	₩				 -	 	
	#				 	 	
	#		ļ		 	 	
	#			 	 	 	
	#			 	_		<u> </u>
	11			 	<u> </u>	-	
	Ш			ļl.	 		
	Ш			<u> </u>	<u> </u>	<u> </u>	
	Ш				<u> </u>	ļ	<u> </u>
	П				ļ		<u> </u>
	\prod						L
	П						
	Π						
	Π						
	11						

-	O. D.	1. D.	LENGTH 4205 I	DEPTH
Drill Pipe or Tubing	4 1/2"	3.826"	4305'	
Drill Collars	6 1/2"	<u>2.375"</u> 2 1/4"	492.34	4798.84
Reversing Sub	6 1/2"_			4730.04
Water Cushion Valve				
Drill Pipe	6 1/2"	2.375"	90'	· e
Drill Collars	6"	2 1/2"	1.50' X 0	/ER
Handling Sub & Choke Assembly = Dual CIP Valve =				
Dual CIP Sampler	5"	.75"	7'	4890'
Hydro-Spring Tester	5"	.75"	5'	<u> 4895'</u>
Multiple CIP Sampler				
Extension Joint				
AP Running Case	5"	3.06"	4'	4897'
	FU	7 7511	5'	
Hydraulic Jar	5"	1.75"		
VR Safety Joint	5"	1.00"	3'	
Pressure Equalizing Crossover				
Packer Assembly	6 3/4"	1.53"	5.75'	4912'
rucker /tasembly	•			
Dr. N.	5"	1.63"	21	
Distributor				
	C 2/4H	1.53"	5.75	4920'
Packer Assembly	0 3/4			
Flush Joint Anchor				
Pressure Equalizing Tube				
Blanked-Off B.T. Running Case				
bighked-Off b. F. Kurming Case				
Drill Collars				
Anchor Pipe Safety Joint		-		
Packer Assembly				
Distributor				
Packer Assembly				
Anchor Pipe Safety Joint				
Side Wall Anchor –				
Drill Collars				
		3.80"	61 '	
Flush Joint Anchor				
Blanked-Off B.T. Running Case	5 3/4"	2.50"	4.16'	4984'

NOMENCLATURE

b	=	Approximate Radius of Investigation	Feet
b 1	=	Approximate Radius of Investigation (Net Pay Zone h ₁)	Feet
D.R	.=	Damage Ratio	
Εl	=	Elevation	Feet
GD	=	B.T. Gauge Depth (From Surface Reference)	Feet
h	=	Interval TestedF	eet
h,	=	Net Pay Thickness	eet
K	=	Permeabilityn	nd
K,	=	Permeability (From Net Pay Zone h.)	nd
m	=	Slope Extrapolated Pressure Plot (Psi²/cycle Gas)	osi/cycle
OF,	=	Maximum Indicated Flow Rate	MCF/D
OF ₂	=	Minimum Indicated Flow Rate	MCF/D
OF ₃	=	Theoretical Open Flow Potential with/Damage Removed Max	MCF/D
OF₄	=	Theoretical Open Flow Potential with/Damage Removed Min	MCF/D
P _s	=	Extrapolated Static Pressure	sig.
P F	=	Final Flow Pressure	sig.
Р.,	=	Potentiometric Surface (Fresh Water*)F	eet
Q	=	Average Adjusted Production Rate During Test	bls/day
Q,	=	Theoretical Production w/Damage Removed	bls/day
Q,	=	Measured Gas Production Rate	ACF/D
R	=	Corrected Recovery	abls
r "	=	Radius of Well Bore	eet
t	_	Flow Time	A inutes
t 。	=	Total Flow Time	Ainutes
Т	=	Temperature Rankine°	R
Z	=	Compressibility Factor	
μ		Viscosity Gas or Liquid	
_		Common Log	

^{*} Potentiometric Surface Reference to Rotary Table When Elevation Not Given, Fresh Water Corrected to $100\,^\circ$ F.



LITE RESEARCH LABORATORIES

Fort Ducheshel Litan 84026

JUH 7

(801) 722-2254

H2S MONITORING

810390

Sample Data

DIVISION OF O'L, CAS & MININO

		3	عدرإسته	Data		SIL, CAS & MINING
Diamo	ond Shamrock					
	Pu			Descript	tion	
						DST #1
	Q = U hu	. Pu =		Location	n:	
				<u> </u>		Allen Fed. 32-6
Fress., PSI	A.T.M. Ten			Temp.	_	Volume, MCF/D @ 14.7-60
		°F				(0)
itted by:	Month	Day	Hour	Year 83		
Dale Gowen - Hallibu	irton 5	44			<u></u>	
rks	• • • •	- a nash	יות זי	1./1		
Colle	ected by Boyd	C. Rich	- Hali	_lburton_		
			ANA	ALYSIS		
						
					-	HEATING VALUE
	MOLE [%]	G.P.M.	LIQUID	[%]	1	B.T.U./CU. FT. 30 IN. HG, 60°F, DRY
					- 1	CALCULATED 1925
HYDROGEN-SULFIDE						CALCULATED 1925
HELIUM						ODSTRUCTO.
CARBON-DIOXIDE	29					OBSERVED
NITROGEN	.63					
METHANE	43.39					
ETHANE	20.05					SPECIFIC GRAVITY
PROPANE	18.80	5.161		.69	·	
ISO-BUTANE	3.58	<u>1.168</u>		. 34	- 1	CALCULATED 1.152
N-BUTANE	7.02	2.207		.54		OBSERVED
ISO-PENTANE	1.88	.802		.10		ORSEKAED
N-PENTANE	2.22					
HEXANES & Higher	3.10	1.272		.26		ĺ
XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX						COPIES TO
02 + Argon	05					CO-112 10
					Į.	
					li	
		4				ANALYST:
	100.00	11.296	100	1.00	ij	ARALIO:
JATOT	100.00					
JATOT	100.00					
JAFOT	100.00					AFPROVED



CI

504

CO3

LITE RESEARCH LABORATORIES

P. O. Box 266

Fort Duchesne, Utah 84026

(801) 722-2254

\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	SAMPLE TAKEN. SAMPLE RECEIV	5-4-81 ED 5-4-81	391		
	RESULTS REPOR	TED			
SAMPLE DESCRIP	TI ON nd Shamrock	LEAS	E Allen-Fed.	FIELD NO.	WELL NO. 32-6
FIELD	COUNTY		STATE		
SAMPLE TAKEN FR					
PRODUCING FORMA	TION		TOP		
REMARKS DST #	1 Sample Chamber				
		SAMPLE	TAKEN BY Boyd	l C. Rich	
	CHE	MICAL AND I	PHYSICAL PROPER	TIFS	
SPECIFIC CRAVITY	660/60° F. 1.0211				FRS @ 77°F
SPECIFIC GRAVITI	900/00 11	p		Orim McT	LKO e
TOTAL HARDNESS	113 mg/l as C	CoCO ₃	TOTAL ALM	CALINITY 1,7	751 mg/L as CaCO ₃
		MILLIGRAMS			
CON	STITUENT	PER LITER mg/L.	PER LITER MEQ/L		REMARK\$
CALCIUM - Co + +		26.5	1.32		
MAGNESIUM - Mg ++		11.4	.94		
SODIUM - Na +		11,400	495.65		
romium (as CrO	4 ⁻²)	37.3			
BARIUM (INCL. STR	ONTIUM) - Ba + +	0.7	.01		
TOTAL IRON - Fe+	+ AND F. + + +	0.20	.01		
BICARBONATE - HC	Оз	953	15.62		
CARBONATE - CO3		113	3.78		
SULFATE - SO4		1,070.	22.28		
CHLORIDE - CL -		18,900	532,99		
TOTAL DISSOLVED	SOLIDS	27,840			
		II I EOLIIVAL	ENTS PER LITER -		
	M	ILLEQUITAL			_
	LOGARITHMIC		No a	DO STAN	DARD 300
			100 Y		
			Ce		
+	 		10		\$71111111111111111
			Mg		
 	//////// 		10		*******************************
	HIII				
<u> </u>	5 - 5 IIIIVA I I IIIIIII IIII	8 8 m 1111111111111111111111111111111111	210 210		o earrithtii
000,1	_	8 8	6, 8,10		
-			¥		
			•		
			ANALYST_		

CHECKED _____



CI

HCO₃

LITE RESEARCH LABORATORIES

P. O. Box 266

Fort Duchesne, Utah 84026

(801) 722-2254

LABORATORY	NUMBER 81	0392		
SAMPLE TAKEN SAMPLE RECEI	VED 5-4-	81 81		
•				
SAMPLE DESCRIPTION COMPANY Diamond Shamrock		- Allen-Fed	FIELD NO.	32-6
COMPANY DIAMOND SHAMLOCK	LEAS	E Affelt Ted.	· · · · · · · · · · · · · · · · · · ·	WELL NO. 32 0
FIELD COUNTY		_ STATE		
SAMPLE TAKEN FROM				
PRODUCING FORMATION		10P		
DST #1 Top of Fluid	SAMPLE	TAKEN BY BO	yd C. Rich	
Ch	EMICAL AND I	PHYSICAL PROPE	PTIFS	
SPECIFIC GRAVITY @60/60° F. 1.0026				os
SPECIFIC GRAVITY 660/60° F. 1:0020	pn	<u> </u>	·32 OHM METER	(3 6
TOTAL HARDNESS 45.5 mg/L as	CoCO 2	TOTAL A	LKALINITY 823	mg/L as CaCO3
TOTAL HARDNESS 45.5				
CONSTITUENT	MILLIGRAMS PER LITER	MILLEQUIVALENTS PER LITER		REMARKS
CONSTITUENT	mg/L.	MEQ/L		NEMAKKS
CALCIUM - Ca + +	15.5	.77		
MAGNESIUM - Mg + +	1.6	.13		·
SODIUM - Na +	875	38.04		· · · · · · · · · · · · · · · · · · ·
Chromium (as CrO4 ⁻²)	351			
BARIUM (INCL. STRONTIUM) - Ba ++	0.1	.00		
TOTAL IRON - Fe++ AND Fe+++	0.11	.00	<u> </u>	
BICARBONATE - HCO3	246	4.03_		
CARBONATE - CO3	252	8.40		
SULFATE - SO4	1,020.	21.24		
CHLORIDE - CL -	320	9.02		
TOTAL DISSOLVED SOLIDS	3,300.			
	MILLEQUIVAL	ENTS PER LITER		-
		_		2
LOGARITHMIC		No 40	2D STANDA	ARD 20 40
		100		
		10 Ca		((
		Mg		
 		10		
		F•		
000,1	00,	0°0 0°0	0	
2	- :	<u>o</u>		
		ANALYST		
		AUFAUF		
	-	CHECKET)	



CI

HCO₃

so₄

CO3

LITE RESEARCH LABORATORIES

P. O. Box 266

Fort Duchesne, Utah 84026

(801) 722-2254

LABORATORY	NUMBER	810393		-
		5-4-81		
		5-4-81		
RESULTS REPO	RTED			
SAMPLE DESCRIPTION				
COMPANY Diamond Shamrock				WELL NO32-6_
FIELD COUNTY		STATE		
SAMPLE TAKEN FROM				
PRODUCING FORMATIONREMARKS		ТОР		
DST #1 Middle Fluid	SAMPLE	TAKEN BY BOY	d C. Rich	
CUI	EMICAL AND I	DUVSICAL DRODE	DTIES	
		PHYSICAL PROPE		DS 0 77°F
SPECIFIC GRAVITY @60/60° F. 1.0028	pH	1.17 KES	1.04 OHM ME IE	K2 6
TOTAL HARDNESS 30.8 mg/L as	CaCO ₃	TOTAL	ALKALINITY 887	mg/L as $CaCO_3$
	MILLIGRAMS	MILLEQUIVALENTS	T	
CONSTITUENT	PER LITER	PER LITER	'	REMARKS
	mg/L.	MEQ/L		
CALCIUM - Ca + +	10.9	.54		
MAGNESIUM - Mg + +	0.83	.07	_	
SODIUM - Na +	1270	55.22		
Chromium (as CrO ₄ ⁻²)	351			
BARIUM (INCL. STRONTIUM) - Ba ++	0.1	.00		
TOTAL IRON - Fe++ AND Fe+++	0.09	00		
BICARBONATE - HCO3	157	2.57		
CARBONATE - CO3	37 8	12.60		
SULFATE - SO4	1,111.	23.13		
CHLORIDE - CL =	729	20.56		
	3720	20.30		
TOTAL DISSOLVED SOLIDS	3720	1		· · · · · · · · · · · · · · · · · · ·
	MILLEQUIVAL	ENTS PER LITER	?	
LOGARITHMIC		No	30 STAND	ARD 30
	<u> </u>		111111111111111111	
		Co		
		10		
╫╌╫╫╫┼┼┼╫╫┼╪┊╟╫╫┼┼┼┼╫╫╫┼┼┼		10	 	
		F		
000,1	001	0, 0,0 0,0	ŏ	<u> </u>
		-		
		ANALYS"	Γ	

CHECKED_



LITE RESEARCH LABORATORIES

P. O. Box 266

Fort Duchesne, Utah 84026

(801) 722-2254

				√*
LABORATORY N)394		•
LABORATORY F SAMPLE TAKEN	5-4-81	,		
SAMPLE TAKEN SAMPLE RECEIV	5-4-81			
KESOE IS KEI O	(160			
SAMPLE DESCRIPTION			FIELD NO.	
COMPANY Diamond Sham rock	LEAS	E Allen Federa	1	WELL NO. $\frac{32-6}{}$
FIELD COUNTY				
SAMPLE TAKEN FROM				
PRODUCING FORMATION		TOP		
REMARKS DST #1 Bottom of Fluid				
			_	
	SAMPLE	TAKEN BY Boyd C	C. Rich	
		DIVERSAL PROPER	TIFE	
- 1 0020	MICAL AND I	PHYSICAL PROPER	12	. 770E
SPECIFIC GRAVITY @60/60° F. 1.0020	рН	RES.	OHM METER	S @
			932	mo/l as Caco
TOTAL HARDNESS 25.6 mg/L as	CaCO3	TOTAL AL	KALINITY 332	mg/r as cacu ₃
	MILLIGRAMS	MILLEQUIVALENTS		
CONSTITUENT	PER LITER	PER LITER		REMARKS
CALCUM C	9.7	MEQ/L .48		
CALCIUM - Co + + MAGNESIUM - Mg + +	0.28	.02		
SODIUM - No +	1140	49.57		
Chromuim (as CrO\(\frac{7}{2}\)	395			
BARIUM (INCL. STRONTIUM) - Ba + +	0.1	.00		_
TOTAL IRON - Fe++ AND Fe+++	0.15	.01		
BICARBONATE - HCO3	123	2.02		
CARBONATE - CO3	438	14.60		
SULFATE - SO4	1,200.	24.98		
CHLORIDE - CL =	354	9.98		
TOTAL DISSOLVED SOLIDS	3,200.			
	AILLEQUIVAL	ENTS PER LITER		-
LOGARITHMIC		No a	STANDAR	RD 30
				ı®ınınıhınını '
			444411111111111111111111111111111111111	N
		Ca		<u> </u>
<u> </u>		10		\mathcal{M}
<u> </u>	 	Mg	 	
8 8 9	8,	810	0	, , , , , , , , , , , , , , , , , , ,
000,1	- 0,1	6 8 10		
-		-		
		ANALYST		

CHECKED ___

GEOLOGIC WELL REPORT

DIAMOND SHAMROCK CORPORATION

OPERATOR

ALLEN-FED. 32-6 SWNE 6, T9S-R17E, SLM, DUCHESNE COUNTY, UTAH MONUMENT BUTTE FIELD May 1981

MAY 1 9 1331

Contents

DIVISION OF OIL, CAS S MINING

<u> </u>	age
BASICS/STATISTICS/PERSONNEL	1
GEOLOGIC RATIONALE	2
GENERALIZED RESULTS	2
FORMATION TOPS	2
GEOLOGIC-OPERATIONAL LOG EXPLANATION	2
DRILLING SEQUENCE/CASING/MUD	Ś
BIT RECORD	3
DEVIATION	3
LOGS, MAINTAINED OR RUN	3
DRILLING SUMMARY CHART	4
DRILL STEM (FORMATION) TESTS	5
CORES	6
STATUS - To be completed for production	6
DISTRIBUTION - THIS REPORT	6
G. S. Campbel #832	
- Call 65	

BASICS/STATISTICS/PERSONNEL

Operator - Diamond Shamrock Corporation

Location - SWNE 6, T9S-R17E, SLM, Duchesne County, Utah Monument Butte Field

Elevations - 5337 KB 5323 GL

Spud - 23 April 1981

Finish Drilling - 5 May 1981 (13 days)

TD - 5400' in lower Green River black shale

Drilling Contractor - Brinkerhoff-Signal Rig #85, Natl 370; Pump: Triplex 6" x 7". Average rate: 6-7 bbs/minute

Company Representative - Bill Foster

Wellsite Geology - G. S. Campbell

Mud (Hydrocarbon) Logging - Underwood Company
Operators - Mike Flaniken and Carey

Drilling Mud - Milkem

Casing - 8-5/8" (24#) @ 260' KB 5-1/2" (15.5#) @ 5400' KB



GEOLOGIC RATIONALE

To in-fill drill the Douglas Creek member sands of the Tertiary Green River formation in the Monument Butte Field.

GENERALIZED RESULTS

The 4920' sand drill stem test results were sufficient to justify completion. The 5240' sand was even better.

FORMATION TOPS

Surface Uinta +5337 KB	5323 GL
Green River Fm	1500'
Horse Bench SS	2300
Gas mrkr	2975
Douglas Ck mbr	4730
Pay sands	4920
Pay sands	5235
TD Blk Sh	5400

GEOLOGIC-OPERATIONAL LOG EXPLANATION

Log attached records lithology, bit record, hole condtions, hot wire gas kicks, shows, tests, cores, deviation, chronology and all drilling events.



DRILLING SEQUENCE/CASING/MUD

12-1/4" clear water drl'd to 265', ran 260' (KB) 24# 8-5/8" csg with 190SX, clear water drl'd 7-7/8" hole to 4500', mud up, drl'd to 5400' TD. Ran 5400' of 5-1/2" casing, calculated fill up to 4000' then DV tool at 3200' to cover oil shale to 1500'.

BIT RECORD

See Drilling Summary Chart or Geologist Log.

DEVIATION


See Drilling Summary Chart or Geologist Log.

LOGS, MAINTAINED OR RUN

Geologist's litho-operational, mud loggers daily log and E. logs-DIL-SFL, SONIC-GR, FDC-CNL and CYBERLOOK.



DRILLING SUMMARY CHART



CORES

None.

STATUS

WOCT

DISTRIBUTION - THIS REPORT

Diamond Shamrock Corporation Denver Office	4 copies
Diamond Shamrock Casper Office	l copy
Diamond Shamrock Vernal Office	1 сору
USGS Salt Lake City office	1 сору
State of Utah Department of Natural Resources Division of Oil, Gas and Mining	1 copy



Diamond Shamrock Fed Allen 32-6, 6/9S/17E, Utah

DST #1 REPORT

Circumstances: Drilling Douglas Creek member of Green River fm. @ 5 min/ft with 9.1 lb, 28 vis. mud @ 4920'. Hit sand; brown, m.g., rounded grains, oil stained, vis. porosity fair, good fluorescence and streaming cut. Drilling rate dropped to 1.4 min/ft from 4920'-25' then 3 min to 30', 2.6 min to 35', 3.8 min to 40', then back to 5 min/ft. Gas units increased from 5 background to 60 at 4930' (10 feet below sand top) and started tappering off after only 3 feet, back to normal after 12 feet. Chromatograph showed Cl, C2, C3 and questionable C4 breakdown.

Interval: 4920-87 (67')

<u>Times</u>: I.O. (1745 hr. 3 May 1981) 15 min., good blo. imm. rolled bucket in 7 min. incr. thruout. ISI 30 min., F.O. 2 hours str. blo. imm. incr. thruout to 1-3/4 psi against 1/8" choke. FSI 4 hrs. Gas to surf. 20 min after F.O.

IH 2334 psi FH 2306 IF 27-55 FF 55-137 ISI 1672 FSI 1810

Recovered 190' (48 gal) mud cut oil BHT 130°

<u>Field Conclusions - Comments</u>: Effective test. Sand will produce oil and respond to frak-stimulation. Permeability only fair. Zone is sufficient to justify running casing.

Sample Disposition: Recovery fluid sent to Ute Lab, Fort Duchesne, Utah.



Form 9-330 (Rev. 5-68)			STATES			DUPLICA	.		Form a Budget	ipproved. Bureau No. 42-R855	.5.
			F THE IN		R	(See struc rever	in- on se size)	1	ESIGNAT	TION AND SERIAL N	. 0.
	C	SEOLOGIC	AL SURVEY	(,	U-0202	252-A		
WELL CO	MPI FTION	OR RECO	MPLETION	REPORT	ΔN	DIO				TTEE OR TRIBE NAI	AE
1a. TYPE OF WEL				MEI OILI	711			-	•		
1964	WEL	L X WELL	DRY	Other				7. UNIT AGI	EEMEN	T NAME	
b. TYPE OF COM	PLETION: WORK DEEP	PLUG [DIFF.			ı					
WELL X	OVER L EN	L BACK L	RESVR	Other				8. FARM OR		. 그 일 일 함았다	
	hamrock Cor	noration						Allen 9. WELL NO		eral	_
3. ADDRESS OF OPE		poracion						32-6			
5730 W. Y	ellowstone	Casper. V	Wyoming 82	601					ND POO	L, OR WILDCAT	_
4. LOCATION OF WE					remen	te)*		Monume	ent F	Butte	
At surface	,949' FEL &	2.102' F	NT.					I		OH BLOCK AND BURY	E¥
	erval reported belo	-						OR ALE			
		- C	IN NE		,			3. 25 5	-] :		
At total depth						· · · · · · · · · · · · · · · · · · ·		Sec. (S . R17E *	
			14. PERMIT NO		DATE	ISSUED		12. COUNTY PARISH	٠	18. STATE	
F		1.5	43-013-3		_/~	7-01				Utah	_
15. DATE SPUDDED			TE COMPL. (Ready	10 prod.) 18				RT, GR, ETC.)*	19. 1	ELEV. CABINGHEAD	
4-23-81 20. TOTAL DEPTH, MD	5-6-81	1 2	5-28-81	THIRD TO COLUMN	5,	324' 0		ROTARY TO	N/	CABLE TOOLS	_
			HOW M			23. INTE	LLED BY			CABLE TOOLS	
5,401 MD 24. PRODUCING INTER	WAT (n) OF METER	5,365' 19	D	MD (ND MED)			→	0 - 5410) :]	N/A *	
5.232 - 5	-254 TEAT	COMPLETION—101	P, BUTTOM, NAME (MU AND TVD)		- 1				SURVEY MADE	, 5 2 - 11
5,232' - 5 -4,912' - 4	.934 ⁷ Gree	n River	- Douglas	Creek		-			= 5 -5	Yes	
26. TYPE ELECTRIC A					- 2	 		- t	97 10	AS WELL CORED	-:N
			erlook, FDC	/CNL						No	2
28.			ING RECORD (Re		4	- 45.077\					-, 🗘
CASING SIZE	WEIGHT, LB./F			OLE SIZE	8 861 11		ENTING	RECORD		AMOUNT PULLED	
8 5/8"	24.0#	260	, <u>1</u>	2 1/4"	5	190	sxs.			N/A	
5 1/2"	14.0 & 15			7 7/8"	-	·	sxs.			N/A	
3 1/2	14.0 4 13	.5" 5,40.		, ,,,,	-		UMO.	-		<u> </u>	
					 	.			-,		
29.	I	INER RECORD)		.	30.		TUBING REC	ORD		- 2
BIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (M	(D)	SIZE	$\neg \neg$	DEPTH SET (1	(D)	PACKER SET (MD)	-
	:	· · · · ·			-	2 3/8	3"- -	5,261		N/A = = =	_
							_		_	3 3 3 3 3 5	_
1. PERFORATION REC	ORD (Interval, size	e and number)		82.	AC	ID, SHOT,	FRACT	TURE, CEMEN	T SQU	EEZE, ETC. 🗝 🖰	
5,232' - 5	,254' 2 ho	les/ft.		DEPTH IN			AM	OUNT AND KI	DOF 1	MATERIAL USED &	
4,912' - 4	,934' 2 ho	les/ft.		5,232	- 5	,254	1500	gal_HCL	, 430	000 gal Gel	
• — • · · · · · · · · · · · · · · · · ·							5500	0# 20/40	sand	1, 32000# 10	720
46 holes							sand	. # * F &		ः इ. १ ३५	_
				4,912'	- 4	,934'				., 54050 gal	-
33.* PATE FIRST PRODUCT	ION I PROPER	CTION METEOR (PRO Flowing, gas lift, p	DUCTION	00 A 4	une ne		0# 20/40			
FRUDUCT	PRODUC		r sowing, yus tijt, p	umping—8126	ana t	уре ој рит :	•p)	eht e	it-in)	s (Producing or	sand
6-5-81	HOURS TESTED	- Pumping	PROD'N. FOR	OIL—BBL.		019 300	100		oduci		
•		CHOME SIZE	TEST PERIOD	1	1.	GAS-MC	. 5 .	WATER—BB		GAS-OIL BATIO	
5-28-81 rlow. Tubing Press.	24 CASING PRESSURE	CALCULATED	OIL—BBL.	100	-MCT] 30	WATER-	16		300:1: 2 &	_

TITLE Dist. Drlg. Engr.

100

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records.

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

2 copies of geologist report

Used for fuel 35. LIST OF ATTACHMENTS

30

16

TEST WITNESSED BY

Bill Elliott

DATE 6-5-

INSTRUCTIONS

or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency,

should be listed on this form, see item 35. or Federal office for specific instructions.

Hem 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Hem 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 24 show the producing intervals, to intervals, top(s), bottom(s) and name(s) (if any) for only the interval zone (multiple completion), so state in item 24 show the producing intervals, top(s), bottom(s) and name(s) (if any) for only the interval zone (multiple as Submit a separate report (page) on this form, adequately identified, showing the additional data pertinent to such interval.

Hem 25: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Hem 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

	TOP	TRUE VERT. DEPTH										626-282 DdDg
 GEOLOGIC MARKERS	70	MEAS. DEPTH	1,500'	12,300	2,975	4,730	4,920	5,235	5,400			
 38. GEOLOG	2		Green River Form	Horse Bench SS	Gas Mrkr	Douglas Creek	Pav sands	Pay sands	TD BIK Sh		•	A*
CB, INCLUDING												93 2 ,43
NTS THERROF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES	DESCRIPTION, CONTENTS, ETC.		DST #1 - no cushion	Open 15 mins.	Close 30 mins.	Open 120 mins.	Glose 240 mins. (gas to surface in 26 mins.	IH - 2334 PSI	IF - 27 - 55	1 2 2 2 3	cover	. 25
IMARY OF POROUS ZONES: SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THERROF; DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING	BOTTOM		4,987									7.8E
 OUS ZONES: TANT ZONES OF PO TESTED, CUSHION	TOP		4,920'				2.7 H					77 AG 7 77224
 37. SUMMARY OF POROUS ZONES: SHOW ALL IMPORTANT ZONES OF DEPTH INTERVAL TESTED, CUSH	FORMATION		Douglas Creek	**************************************				2	- 100		E-1 TO	5.2 RE

DEPARTMENT OF THE INTERIOR

SUBMIT IN DUPLICA

Form approved. Budget Bureau No. 42-R355.5.

5.	LEASE	DESIGNATION	AND	SERIAL	NO	

verse side)	5.	LEASE	DESIGNATION	AND	SERIAL	

	GEO	LOGICAL SU	RVEY			U-0202.	52-A		
WELL COM	MPLETION OR	RECOMPLET	ION REP	ORT A	ND LOG*	6. IF INDIAN	, ALLOTTEE OR TRIBE NAME		
1a. TYPE OF WELI	L: OIL WELL X	GAS WELL D	RY Othe	r		7. UNIT AGRE	EEMENT NAME		
b. TYPE OF COMP				- 1,70	The state of the state of the state of	<u>.</u>			
WELL X	OVER DEEP-	PLUG DIFI	VR. Othe	7 15	Bush beat	S. FARM OR	LEASE NAME		
2. NAME OF OFERATO	o r		1,77	100.0	30	Allen	Federa l		
Diamond Sh	amrock Corpor	ation	3	HIAL	^-	9. WELL NO.			
3. ADDRESS OF OPER	ATOR			JUN		32-6			
5730 W. Ye	ellowstone Ca	sper, Wyoming	g 82601			10. FIELD AN	D POOL, OR WILDCAT		
4. LOCATION OF WEL	L (Report location clea	rly and in accordance	with any Sta	te require	nents)*	Monume	nt Butte		
At surface 1	,949' FEL & 2	,102' FNL	(OIL GAS	S & MINING	11. SEC., T., I	R., M., OR BLOCK AND SURVEY		
At top prod. inte	rval reported below		`	, un	o a minaliae				
44 4-4-1 2									
At total depth		 					, T9S, R17E		
			RMIT NO.		ATE ISSUED	12. COUNTY (PARISH		
5. DATE SPUDDED	16. DATE T.D. REACHE	143-	0/3-30				Duchesne Utah PT GB FTC)* 19. ELEV. CASINGHEAD		
i i		1	(Reday to pro		ELEVATIONS (DF, RE	B, RT, GR, ETC.)*			
4-23-81	5-6-81	5-28-81			5,324' GR		N/A		
O. TOTAL DEPTH, MD &	1	1	. IF MULTIPLE HOW MANY*	COMPL.,	23. INTERVALS	Y .	1 .		
5,401' MD	5,36	5' MD	V. 145 (145 . 14	·		0 - 5410	N/A		
5,232' - 5		ETION-TOP, BUTTOM,	NAME (MD AN	VD 1VD)*			25. WAS DIRECTIONAL SURVEY MADE		
	,934' Green	River - Dougl	as Crook				Yes		
	ND OTHER LOGS RUN		- OTCCK				27. WAS WELL CORED		
, e. C	onic, Gamma R	ay, Cyberlook	, FDC/CN	IL			No No		
S.		CASING RECO	RD (Report a	ll strings s	et in well)	······································			
CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SI	ZE	CEMENTIN	G RECORD	AMOUNT PULLED		
8 5/8"	24.0#	260 '	12 1/4	,''	190 sxs.		N/A		
5 1/2"	14.0 & 15.5#	5,401'	7 7/8	3''	355 sxs. 1s	t stage	N/A		
					340 sxs. 2n	d stage			
					D.V. Tool @	3,342' KB			
9.	LINE	R RECORD			30.	TUBING RECO	ORD		
SIZE	TOP (MD) BOTT	OM (MD) SACKS CI	MENT* SCF	REEN (MD)	SIZE	DEPTH SET (M	D) PACKER SET (MD)		

	2 3/0 3,201
31. PERFORATION RECORD (Interval, size and number)	82. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.
	DEPTH INTERVAL (MD) AMOUNT AND KIND OF MATERIAL USED
5,232' - 5,354' 2 holes/ft.	5,232' - 5,254' 1500 gal HCL, 43,000 gal Gel
4,912' - 4,934' 2 holes/ft.	55,000# 20/40 sand, 32,000#
	10/20 sand
46 holes	4 912' - 4 934' 15000 gal 15% HCL 54050 gal Ge

33.*			PRG	DUCTION	3500	0# 20/40 s	and, 32000# 10/20
DATE FIRST PRODUCTI	ON PRODUCT	ION METHOD (Flo	wing, gas lift, p	umping—size and	(ype of pump)	WELL ST	TATUS (Producing or sand
<u>6-5-81</u>		Pumpin	g				Producing
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR	OIL-BBL.	GAS-MCF.	WATER-BBL.	GAS-OIL RATIO
5-28-81	24			100	30	16	300:1
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS-MCF.	WATER-	BBL.	OIL GRAVITY-API (CORE.)
0	40	>	100	30	1	6	30
34. DISPOSITION OF G	as (Sold, used for fu	el, vented, etc.)				TEST WITNESS	ED BY
Used for f	ue1			-		Bill E	lliott
35. LIST OF ATTACHM	1ENTS						

			logist rep					<i>;</i>	
36.				/ ~ /				all available records	
	CICKED	11/10	2 10 6	. LO COUNTY	m Dist.	Drlg.	Supt.	6-15-81	

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency or a State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal

and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formand on pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be itsed on this form, see item 35.

If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instanctions.

iters 22 and 24.1 fthis well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing iterval, or interval, or interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.) Hem 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

TRUE VERT. DEPTH TOP MEAS. DEPTH 4,920 2,975 2,300' 5,235 GEOLOGIC MARKERS 1,500' 4,7301 Form SS Douglas Creek Green River Horse Bench NANE Pay sands Pay sands ID BIK Sh Gas Mrkr 38. DRILL-STEM TESTS, INCLUDING (gas to surface in 26 mins) 37. SUMMARY OF POROUS ZONES: Show all important zones of pororit and contents thereof; cored intervals; and all drill-stem t drith interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries DESCRIPTION, CONTRNTS, ETC. cut mud Close 240 Mins. Close 30 mins. Open 120 mins. - no cushion Open 15 mins. oil Recovers 190' IH - 2334 PSI FF - 55 - 137 IF - 27 - 55-1672-1810FH - 230C #1 ISIDST 4,987 BOTTOM 4,920' Douglas Creek FORMATION

July 7, 1981

Diamond Shamrock Corporation 5730 West Yellowstone Casper, Wyoming 82601

> Re: Well No. Allen Federal #32-6 Sec. 6, T. 9S, R. 17E Duchesne County, Utah

Gentlemen:

According to our records, a "Well Completion Report" filed with this office 6-15-81, from above referred to well indicates the following electric logs were run: DIL, SFL, Sonic, Gamma Ray, Cyberlook, FDC/CNL. As of tedys date this office has not received these logs: DIL, SFL, Gsmma Ray, Cyberlook, FDC/CNL.

Rule C-5, General Rules and Regulations and Rules of Practice and Procedure, requires that a well log shall be filed with the Commission together with a copy of the electric and radioactitity logs.

Your prompt attention to the above will be greatly appreciated.

Sincerely,

DIVISION OF OIL, GAS, AND MINING

Sandy Bates Clerk-Typist


/1m

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Form 9–331 Dec. 1973	Form Approved. Budget Bureau No. 42–R1424
UNITED STATES DEPARTMENT OF THE INTERIOR	5. LEASE U-020252A
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9-331-C for such proposals.) 1. oil XXX gas well other 2. NAME OF OPERATOR	7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME ALLEN FEDERAL 9. WELL NO.
DIAMOND CHEMICAL CO. (formerly DIAMOND SHAMROCK) 3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME Monument Butte Field
P.O. Drawer 'E', Vernal, Utah 84078 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 6, T9S, R17E 12. COUNTY OR PARISH 13. STATE Duchesne Utah
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinen	rectionally drilled give subsurface locations and
DIAMOND CHEMICAL COMPANY requests permission system to all wells within federal lease U-O be 1" and 2" polyethylene pipe and will be 1 gas gathering system as shown on the attache	20252A. These dry gas lines wil aid parallel to the existing wet

including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones perting DIAMOND CHEMICAL COMPANY requests permission system to all wells within federal lease Ube 1" and 2" polyethylene pipe and will be gas gathering system as shown on the attack will be 50 psig. These lines will be laid along lease and access roads wherever possible, will be cased and buried at road crossings, and will not create a surface disturbance. The laying of these lines will allow DIAMOND CHEMICAL to severely reduce the amount of downtime we are now experiencing caused by the condensation of liquids in fuel gas lines on existing locations & thus increase oil & gas production from this lease. Subsurface Safety Valve: Manu. and Type Set @ _ 18. I hereby certify that, the foregoing is true and correct TLE Production Engineer 9-12-83 SIGNED (This space for Federal or State office BY THE STATE APPROVED BY OF WEAH DIVISION OF TITLE CONDITIONS OF APPROVAL IF ANY: OIL, GAS, AND MAN

*See Instructions on Reverse Side





355 West North Temple, 3 Triad Center, Suite 350, Salt Lake City, Ut 84180-1203. ●(801-538-5340)

_	1		6
age		of	

MONTHLY OIL AND GAS PRODUCTION REPORT

Operator name	and address:
•	

DIAMOND SHAMROCK EXPL.
2001 ROSS AVE #1500
DALLAS TX
ATTN: PAT COTE

75201

JUN 0 5 1987

DIVISION OF

OIL, GAS & MINING

Report Period (Month/Year) 4 / 87

Amended Report

Well Name **Producing** Days Production Volume API Number Entity Location Zone Oper Oil (BBL) Gas (MSCF) Water (BBL) ALLEN FEDERAL #1 4301315779 01110 09S 17E 238 -0-**GRRV** 23 71 X EAST RED WASH 2-5 -0--0--0-4304720252 01112 08S 25E -0-**GRRV** ALLEN FEDERAL A-1 4301315780 01115 09S 17E -0--0--0--0-**GRRV** ALLEN FEDERAL 23-6 4301330558 01120 098 17E 30 225 1825 7 **GRRV** ALLEN FEDERAL 32-6 4301330559 01120 09S 17E 30 115 925 -0-**GRRV** XALLEN FEDERAL 41-6 4301330581 01120 098 17E 30 321 2838 -0-**GRRV** X ALLEN FEDERAL 43-6 4301330583 01120 09S 17E 30 199 1705 26 **GRRV** ALLEN FEDERAL 21-6 4301330584 01120 09S 17E 30 230 1234 -0-**GRRV** ALLEN FEDERAL 34-6 4301330586 01120 09S 17E 209 30 1577 8 **GRRV** XALLEN FEDERAL 13-6 4301330918 01120 095 17E 30 125 1047 -0-**GRRV** XALLEN FEDERAL 22-6 30 186 2692 8 4301330919 01120 09S 17E **GRRV** ALLEN FEDERAL 12-5 30 230 4301330611 01125 09S 17E **GRRV** 1186 -0-ALLEN FEDERAL 12-6 4301330582 01135 09S 17E 30 556 2595 **GRRV** 3 2467 17862 52 TOTAL

Comments (attach separate sheet if necessary)	
I have reviewed this report and certify the information to be accurate and complete.	Date6-2-87
Authorized signature	Telephone (214) 979-2822

COMPANY:	MAXUS EXPLORATION CO UT ACCOUNT II SUSPENSE DATE: 6-10-87
	DIAMOND SHAMROCK EXPLORATION CO)
	TELEPHONE CONTACT DOCUMENTATION
CONTACT N	NAME: PAT COTE (PAT PRONOUNCES HER NAME "CONTEE")
CONTACT	TELEPHONE NO .: (214) 777 - 2822
SUBJECT:	OPERATOR CHANGE - DIAMOND SHAMROCK EXPLORATION CO TO MAXUS EXPL CL
	(Use attachments if necessary)
RESULTS:	PAT SAID SHE WOULD PROVIDE: LIP OF EXPLANATION FOR 1) EFFECTIVE BATE,
	2) BONOING, 3) ENTITY REVIEW, 4) WELLS IN QUESTION, 5) ADDRESS & TEL
	FOR BOTH DRILLING AND PRODUCTION CONTACT PEOPLE,
	SHE WILL USE GOPY A SUPPLEMENTED COPY OF TAD TO IDENTIFY ALL
	WELLS, INCLUDING DAILLING AND INCECTION (Use attachments if necessary)
CONTACTED	BY: Hopin
DATE:	6-2-67

. .

••

Control of the property of the same



060810

DIVISION OF OIL, GAS & MINING

June 2, 1987

EUXAM

Utah Division of Oil, Gas & Mining Attn: Norm Stout 355 W. North Temple 3 Triad Center, Suite 350 Salt Lake City, UT 84180-1203

Dear Mr. Stout,

Regarding your request for information concerning the change of name of our company from Diamond Shamrock Exploration, to Maxus Exploration Company:

- 1. New replacement bond is being taken care of by Sherry Neally (214) 953-2858, and will be mailed to you shortly by Judy Tate (806) 378-3876.
- 2. Contact names will remain the same Kaleb Leake (307) 266-1882, Maxus Exploration Company, P.O. Box 2530, Mills, WY 82644, for drilling and permitting; Pat Cote (214) 979-2822, at the letterhead address, for production and disposition reporting.
- 3. I am enclosing a copy of our most recent production report. This is a complete list of all wells to be affected by the name change.
- 4. The name change is effective 4-28-87. All name change notices are being handled by Dick Smith in our Legal Department (214) 953-2979. He assures us that the notices will be sent out in a few days.
- 5. There are no changes in the division of interest on any of the attached wells, therefore all entity numbers will remain the same.

Thank you for your patience in this matter, and please contact me if there is any other information needed.

Sincerely,

Pat Cote

Production Clerk, Oil Revenue Maxus Exploration

(214) 979-2822

Poim 3100-5 (November 1983) (Formerly 9-331)

D STAILS DEPARTMENT OF THE INTERIOR Verse alde) BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIP.

Expires August 31, 1985 5. LEASE DESIGNATION AND SERIAL NO.

U-020252A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Budget Bureau No. 1004-0135

SUNDRY NOTICES AND REPORTS ON WELLS

(1)o not use this form for proposals to drill or to deepen or plug back to a different reservoir.

UM "APPLICATION FOR PERM	IIT—" for such proposals.)
OIL GAB OTHER	
AAXUS EXPLORATION COMPANY	OCT 15 1990
P. O. BOX 1669, VERNAL, UTAH 840 LOCATION OF WELL (Report location clearly and in account of the state of th	078 rdance with any State requirements.

1949' FEL & 2102' FNL, SW/NL

14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)
43-013-30559	532/41 GR

SEC. 6, T9S, R17E 12. COUNTY OR PARISH 13. STATE DUCHESNE

7. UNIT AGREEMENT NAME

B. FARM OR LEASE NAME ALLEN FEDERAL

10 FIRLD AND POOL, OR WILDCAT MONUMENT BUTTE

11. SEC., T., R., M., OR BLK. AND SURVEY OR ARMA

9. WBLL NO. 32-6

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOT	ICB O	FINTENTION TO:		
TEST WATER SHUT-OFF		PULL OR ALTER CASING	[]
FRACTURE TREAT	XX	MULTIPLE COMPLETE		
BHOOT OR ACIDIZA		ABANDON®		
REPAIR WELL		CHANGE PLANS		
(Athor)			1 - 1	ı

WATER SHUT-OFF REPAIRING WELL PRACTURE TRBATMENT SHOOTING OR ACIDIZING

ALTERING CARING

UTAH

(Norz: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

MAXUS EXPLORATION requests permission to perforate and fracture treat a hydrocarbon bearing zone in the Allen Federal 32-6 well as follows:

1. POOH with rods and tubing.

Perforate the new zone at 4246' - 4252' and 4283' - 4289'

3. Isolate the new zone with a bridge plug and packer.

Breakdown and frac new zone.

Return well to pumping operations.

ACCEPTED BY THE CONTROL OF UTAH DIVISIO OIL, GAS, AND M

Federal approval of this action

18. I hereby certify that the foregoing is true and correct RIGHMA 10-10-90 DATE . (This space for Federal or State office use) APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side


18. I hereby certify that the foregoing is true and correct the well to production from the signed RODNEY BREWER (This space for Federal or State office use)	kcessive water produ sted to 3000# and the original Green Riv	' - 4289'. ction, the z e cement dri er formation	The zone was per one was squeezed	rforated and d off. After ill now return
fracture treated, but due to exthe squeeze, the casing was testhe well to production from the the well to production from the signed was the foregoing is true and correct signed with the foregoing with the forego	kcessive water produsted to 3000# and the original Green Riv	' - 4289'. ction, the z e cement dri er formation	The zone was perone was squeezed lled out. We was perforations.	rforated and d off. After ill now return
fracture treated, but due to exthe squeeze, the casing was test the well to production from the	kcessive water produsted to 3000# and the original Green Riv	' - 4289'. ction, the z e cement dri er formation	The zone was perone was squeezed lled out. We was perforations.	rforated and d off. After ill now return
fracture treated, but due to exthe squeeze, the casing was testhe well to production from the	kcessive water produ sted to 3000# and the original Green Riv	' - 4289'. ction, the z	The zone was per one was squeezed	rforated and
fracture treated, but due to extend the squeeze, the casing was tes	46' - 4252' and 4283 kcessive water produ sted to 3000# and th	' - 4289'. ction, the z	The zone was per one was squeezed	rforated and
fracture treated, but due to extend the squeeze, the casing was tes	46' - 4252' and 4283 kcessive water produ sted to 3000# and th	' - 4289'. ction, the z	The zone was per one was squeezed	rforated and
fracture treated, but due to extend the squeeze, the casing was tes	46' - 4252' and 4283 kcessive water produ sted to 3000# and th	' - 4289'. ction, the z	The zone was per one was squeezed	rforated and
fracture treated, but due to extend the squeeze, the casing was tes	46' - 4252' and 4283 kcessive water produ sted to 3000# and th	' - 4289'. ction, the z	The zone was per one was squeezed	rforated and
fracture treated, but due to extend the squeeze, the casing was tes	46' - 4252' and 4283 kcessive water produ sted to 3000# and th	' - 4289'. ction, the z	The zone was per one was squeezed	rforated and
fracture treated, but due to extend the squeeze, the casing was tes	46' - 4252' and 4283 kcessive water produ sted to 3000# and th	' - 4289'. ction, the z	The zone was per one was squeezed	rforated and
fracture treated, but due to extend the squeeze, the casing was tes	46' - 4252' and 4283 kcessive water produ sted to 3000# and th	' - 4289'. ction, the z	The zone was per one was squeezed	rforated and
fracture treated, but due to extend the squeeze, the casing was tes	46' - 4252' and 4283 kcessive water produ sted to 3000# and th	' - 4289'. ction, the z	The zone was per one was squeezed	rforated and
fracture treated, but due to extend the squeeze, the casing was tes	46' - 4252' and 4283 kcessive water produ sted to 3000# and th	' - 4289'. ction, the z	The zone was per one was squeezed	rforated and
fracture treated, but due to extend the squeeze, the casing was tes	46' - 4252' and 4283 kcessive water produ sted to 3000# and th	' - 4289'. ction, the z	The zone was per one was squeezed	rforated and
fracture treated, but due to extend the squeeze, the casing was tes	46' - 4252' and 4283 kcessive water produ sted to 3000# and th	' - 4289'. ction, the z	The zone was per one was squeezed	rforated and
fracture treated, but due to extend the squeeze, the casing was tes	46' - 4252' and 4283 kcessive water produ sted to 3000# and th	' - 4289'. ction, the z	The zone was per one was squeezed	rforated and
fracture treated, but due to extend the squeeze, the casing was tes	46' - 4252' and 4283 kcessive water produ sted to 3000# and th	' - 4289'. ction, the z	The zone was per one was squeezed	rforated and
fracture treated, but due to extend the squeeze, the casing was tes	46' - 4252' and 4283 kcessive water produ sted to 3000# and th	' - 4289'. ction, the z	The zone was per one was squeezed	rforated and
fracture treated, but due to ex	46' - 4252' and 4283 Kcessive water produ	' - 4289'.	The zone was per	rforated and
32 0: The Zone exists from 424	40 - 4252' and 4283	' - 4289'	The zone was not	mfamahad1
1/-h. The gone orders form 101		•	non Bone In the	Allen redera
MAXUS EXPLORATION wishes to rep	ort the squeeze cem	enting of a	new zone in the	Allon Fodom
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clear) proposed work. If well is directionally drilled, g nent to this work.) *	ive subsurface locations and mea	give pertipent dates sured and true verti	s, including estimated date cal depths for all plarkers	e of starting any cand sones perti-
(Other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Classical Complete	ly state all postly and distally	Completion or Recom	n of multiple completion pletion Report and Log for	on Well
REPAIR WELL CHANGE PLANS			MENT PERF, INTE	
SHOOT OR ACIDIZE ABANDON*		ING OR ACIDIZING	ABANDONME	
FRACTURE TREAT MULTIPLE COMP		UBE TERATMENT	REPAIRING V	
TEST WATER SRUT-OFF PULL OR ALTER	CARING	R SHUT-OFF		
NOTICE OF INTENTION TO:	1		QUANT REPORT OF:	
16. Check Appropriate Bo	ox To Indicate Nature of N	otice. Report or	Other Data	
43-013-30559 Food 5324'	GR		DOGHEGINE	OTAM
14. PERMIT NO. 18. BLEVATION	NS (Show whether DP, RT, GR, etc.)		12DUCHESNE PARISH	UTAH
1949' FEL & 2102' FNL SW/NE			SEC. 6, T9S,	, R17E
1949' FEL & 2102' FNL SW/NE			11. SUC., T., R., M., OR I	L
At surface			MONUMENT BUT	TE FIELD
oce miso space it below.)	ecordance with any State require	ments.*	10. FIBLD AND POOL, O	R WILDCAT
P. O. BOX 1669, VERNAL, UTAH 4. LOCATION OF WELL (Report location clearly and in a			32-6	
8. ADDRESS OF OPERATOR	OIL, GAS &	. •	ALLEN FEDERA 9. WELL NO.	AL
MAXUS EXPLORATION COMPANY	DIVISION	i OF	8. FARM OR LEASE NA.	
WELL WELL OTHER 2. NAME OF OPERATOR	DEC 06	1990	9	
1. OIL GAS []	=== 0.0	1000	7. UNIT AGREEMENT N	AMB
	to deepen de la la particular sans	CALL SEALING		
(Do not use this form for proposals to drill or Use "APPLICATION FOR PI			İ	OR INIBE NAME
		WIEIM	6. IF INDIAN, ALLOTTE	TE OR TRIBE MANY
SUNDRY NOTICES AND (Do not use this form for proposals to drill or use "APPLICATION FOR PI	D REPORTS - Open THE	WIED	U-020252A 6. IF INDIAN, ALLOTTE	PE OR MEINE MANY
SUNDRY NOTICES AND (Do not use this form for proposals to drill or use "APPLICATION FOR PE	D REPORTS - OF THE	elde)		

DIVISION OF OIL, GAS AND MINING

·		5. LEASE DESIGNAT	
SUNDRY NOTICES AND REPORTS C (Do not use this form for proposals to drill or to deepen or plug ba Use "APPLICATION FOR PERMIT—" for such	ick to a different reservoir.		ACHED LIST
OIL GAS WELL OTHER		1. UNIT AGREEMENT	TNAME
2. NAME OF OPERATOR EQUITABLE RESOURCES ENERGY COMPANY		8. FARM OR LEASE I	NAME
P.O. Box 21017; Billings, MT 59104	(406)259-7860	9. WELL NO.	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requises also space 17 below.) At surface		10. FIELD AND POOL	. OR WILDCAT
At proposed prod. zone SEE ATTACHED LIST		11. SEC., T., R., M., O. SURVEY OR	
14. APT NO. 15. ELEVATIONS (Show whether DF	, RT, GR, etc.)	12 COUNTY	I3. STATE
16. Check Appropriate Box To Indicate No.	ature of Notice, Report or (Ither Data	¹
NOTICE OF INTENTION TO:	SUBS	QUENT REPORT OF:	
FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other) FULL OR ALTER CASING MULTIPLE COMPLETE ABANDON CHANGE PLANS (Other) Change of Operator X	WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other) (Note: Report result	ABANDO:	G CASING NMENT*
APPROX. DATE WORK WILL START	DATE OF COMPLETION	ompletion Report and L	og form.)
Effective November 1, 1991, the operator Exploration Company TO: EQUITABLE RESOUR P.O. Box 21017 Billings, MT 59	* Must be according this well will CES ENERGY COMPANY	npanied by a cement	verification report
Effective November 1, 1991, Equitable Res the terms and conditions of the lease for or a portion thereof under Bureau of Land Insurance Co.	operations conduc	ted on the lease 5547188 issued	sed lands by Safeco
		001 0	9 1991
		DIVISION OIL GAS	
	ttorney-in-Fact		ober 8, 1991
(This prace for Federal or State office use) APPROVED BY		DATE	



P.O. Box 21017 1601 Lewis Avenue Building Billings, Montana 59104 (406) 259-7860



OCT 0 9 1991

DIVISION OF OIL GAS & MINING

(

October 8, 1991

-- VIA FEDERAL EXPRESS --

Lisha Romero State of Utah Division of Oil, Gas & Mining 355 West North Temple Salt Lake City, UT 84180

Dear Lisha:

Enclosed are sundry notices for Change of Operator for the wells on the enclosed list. These wells are currently operated by Maxus Exploration Company and are being transferred to:

> Balcron Oil P.O. Box 21017 Billings, MT 59104

The transfer is effective November 1, 1991.

If there is any other information you need or if you have any questions, please give me a call. Shankshelp, Lishar your help,

Sincerely,

Bobbie Schuman

Coordinator of Operations,

Environmental, and Regulatory Affairs

/rs

Enclosures

James M. Pachulski, Maxus Exploration Company

Maxus Exploration Com P.O. Box 2530 Mills, Wyoming 82644 307 266-1882



DIVISION OF OIL GAS & MINING

MAXUS

October 7, 1991

State of Utah
Division of Oil & Gas
3 Triad Center, Ste. 350
Salt Lake City, Utah 84180

Re: Operator Transfer of Maxus

Exploration Company Wells

Dear Sir:

Attached is a list of wells within the State of Utah currently operated by Maxus Exploration Company. These wells are in the process of being transferred to a new operator:

Balcron Oil
P.O. Box 21017
Billings, Montana 59104
Attn: Bobbie Schuman
Coordinator of Environmental and Regulatory
Affairs (406) 259-7860

The transfer will become effective on November 1, 1991. Individual Sundry notices for each well will be forwarded to the BLM with a copy to the State of Utah by Balcron Oil in the near future. These Sundry Notices will include the bond number, effective date and a statement agreeing to be responsible under the terms and conditions of the lease.

Please contact the undersigned if there are any questions. Thank you.

Sincerely,

James M. Pachulski

Staff Regulatory Specialist

JMP:ka

cc: Balcron Oil

Maxus Energy Corporation 717 North Harwood Street Dallas, Texas 75201 214 953-2000

11/1/91

ZUXAN

TO: INTEREST OWNERS

SALES OF WELLS

MAXUS HAS SOLD ALL THEIR NORTH DAKOTA, MONTANA, UTAH, AND WYOMING (EXCEPT ALPHA FIELD in WYOMING) EFFECTIVE 11/1/91.

TO: BALCON OIL & GAS CO
P. O. BOX 21017
BILLINGS, MT 59104

PRODUCTION DEPT / JENICE FUGERE

PH: 406/259-7860

IT IS MY UNDERSTANDING THAT MAXUS WILL OPERATE THESE WELLS UNTIL NOVEMBER 1, 1991, BUT THAT IS SUBJECT TO CHANCE. I JUST WANTED TO GIVE YOU THEIR NAME AND ADDRESS.

Nancy Lawrence / 214/953-2177

Oil Accounting

NOV 2 9 1331

DIVISION OF OIL GAS & MINING



United States Department of the Interior



IN REPLY REFER TO:

BUREAU OF LAND MANAGEMENT VERNAL DISTRICT OFFICE 170 SOUTH 500 EAST VERNAL, UTAH 84078

JAN 02 1992

3162.3 UT08438

Equitable Resources Energy Company Attn: Bobbie Schuman P.O. Box 21017 Billings, Montana 59104

Re:

43-013-30559 Well No. Allen Federal 32-6

SWNE, Sec. 6, T9S, R17E

Lease U-020252-A Uintah County, Utah

Dear Ms. Schuman:

This correspondence is in regard to the self-certification statement submitted requesting a change in operator for the referenced well. After a review by this office, the change in operator request is approved. Effective immediately, Equitable Resources Energy Company is responsible for all operations performed on the referenced well. All liability will now fall under your bond, BLM Bond No. MT0576, for all operations conducted on the referenced well on the leased land.

If you have any other questions concerning this matter, please contact Ed Forsman of this office at (801) 789-1362.

Sincerely,

Howard B. Cleavinger II

Assistant District Manager for Minerals

Maxus Exploration Company cc:

JAN 0 6 1992

DIVISION OF OIL, GAS & MINING

	OR CHANGE HORKSHEET			Routing:
	I documentation received by the division recei	· · · · · · · · · · · · · · · · · · ·	able.	2- DTS 3- VLC 4- RJF
	ge of Operator (well sold) gnation of Operator	□ Designation of □ Operator Name (5- RWM 6-ADA 7-LCR
e ope	rator of the well(s) listed below h	as changed (EFFEC	CTIVE DATE:)
(new	operator) (address) (address) P. O. BOX 21017 1601 LEWIS AVENUE BUILDIN BILLINGS, MT 59104 phone (406) 259-7860 account no. N9890 (12-5)	<u>IG</u>	phone <u>(3</u> 0	RWOOD, STE 2900
11(s)	(attach additional page if needed):		•	•
ame:_ ame:_ ame:_ ame:_	**SEE ATTACHED** API:	Entity: Entity: Entity: Entity: Entity: Entity:	SecTwpRng SecTwpRng SecTwpRng SecTwpRng	Lease Type: Lease Type: Lease Type: Lease Type: Lease Type:
ERATO	OR CHANGE DOCUMENTATION		•	
į	(Rule R615-8-10) Sundry or other operator (Attach to this form). (Rec	10-10-91)		
	(Rule R615-8-10) Sundry or other le (Attach to this form). (Rec'e! 10-9-91)	,		·
<u>é</u> f3.	The Department of Commerce has been operating any wells in Utah. Is o yes, show company file number: dba 0	n contacted if th company registere <u>97441</u> . (Owned by E	e new operator above ed with the state? (Equitable Risearus Energy To	is not currently yes/no) If ompany # 1346407
<u>C</u> 4.	(For Indian and Federal Wells ONL (attach Telephone Documentation F comments section of this form. M changes should take place prior to	orm to this rep anagement review	oort). make note o of Federal and Indi	an well operator
£5.	Changes have been entered in the Oflisted above. (1-10-92)	il and Gas Inform	nation System (Wang/I	BM) for each well
<u>C</u> 6.	Cardex file has been updated for ea	ch well listed al	bove. (1-13-92)	
£7.	Well file labels have been updated	for each well lis	sted above.(1-13-92)	
<u>ef</u> 8.	Changes have been included on the for distribution to State Lands and	monthly "Operato the Tax Commiss	r, Address, and Acco ion. <i>(1-10-92</i>)	unt Changes" memo
ef 9.	A folder has been set up for the C placed there for reference during r	perator Change fouting and proce	ile, and a copy of t ssing of the original	his page has been documents.

vision of Oil, Gas and Mining PERATOR CHANGE WORKSHEET

ATOR CHANGE WORKSHEET (CONTINUED) Initia ach item when completed. Write N/A intem is not applicable.
TY REVIEH 1. (Rule R615-8-7) Entity assignments have been reviewed for all wells listed above. Were entity changes made? (yes/no) (If entity assignments were changed, attach copies of Form 6, Entity Action Form). 2. State Lands and the Tax Commission have been notified through normal procedures of entity changes.
VERIFICATION (Fee wells only) 1. (Rule R615-3-1) The new operator of any fee lease well listed above has furnished a proper bond. 2. A copy of this form has been placed in the new and former operators' bond files. 3. The former operator has requested a release of liability from their bond (yes/no) 1. Today's date 19 If yes, division response was made by letter dated 19
1. (Rule R615-2-10) The former operator/lessee of any fee lease well listed above has been notified by letter dated 19, of their responsibility to notify any person with an interest in such lease of the change of operator. Documentation of such notification has been requested.
2. Copies of documents have been sent to State Lands for changes involving State leases.
ING 1. All attachments to this form have been microfilmed. Date:
 Copies of all attachments to this form have been filed in each well file. The original of this form and the original attachments have been filed in the Operato-Change file.
1ENTS 911007 Btm/Vernal "No documentation as of yet." 911025 Btm/Vernal "Have documentation-not approved as of yet." Will notify Dibm when approved 911125 Btm/Vernal " 911231 Btm/Vernal "
920110 Ballron Bobby Schumen Reg. Transfer of Authority to Inject "Park He Bench Unit #4" and 134-35 Sundry for operator change "Partle peak St. 43-16"



355 West North Temple, 3 Triad Center, Suite 350, Salt Lake City, Ut 84180-1203. ● (801-538-5340)

Operator name and address:

_	l.	5
Page	<u> </u>	



MONTHLY OIL AND GAS PRODUCTION REPORT

ATTN NANCY LAWRENCE MAXUS EXPLORATION CO. 717 N. HARWOOD, STE DALLAS TX 75201-	Utah Account No. — N0865 Report Period (Month/Year) — 12 / 91 Amended Report — 12 / 91				
	,				
Well Name	Producing	-	Production Volume		
API Number Entity Location	Zone	Oper	Oil (BBL)	Gas (MSCF)	Water (BBL)
MONMNT BUTTE 1-34					
4301330736 00030 09S 16E 1	GRRV				
MONMNT BUTTE 1-24					
4301330701 00050 09S 16E 1	GRRV				
ALLEN FEDERAL #1					
4301315779 01110 09S 17E 6	GRRV				
ALLEN FEDERAL A-1					
4301315780 01115 09S 17E 5	GRRV				[
ALLEN FEDERAL 23-6	GIVILA				
4301330558 01120 09S 17E 6	CDDV.				
ALLEN FEDERAL 32-6	GRRV :				
	00014				
1330559 01120 09S 17E 6+	GRRV -				
ALLEN FEDERAL 41-6					
4301330581 01120 09S 17E 6	GRRV				
ALLEN FEDERAL 43-6					
4301330583 01120 095 17E 6	GRRV				
ALLEN FEDERAL 21-6					
4301330584 01120 09S 17E 6	GRRV :				
ALLEN FEDERAL 34-6					
4301330586 01120 09S 17E 6	GRRV :				
ALLEN FEDERAL 13-6					
4301330918 01120 09S 17E 6	GRRV .]		
ALLEN FEDERAL 22-6			<u> </u>		
4301330919 01120 09S 17E 6	GRRV				
ALLEN FEDERAL 12-5	unit v				
4301330611 01125 09S 17E 5	GRRV ∂				
7701770011 01127 033 172 9	Takky 0				
	т	OTAL			<u>l</u>
Comments (attach separate sheet if nece	ssary)			· · · · · · · · · · · · · · · · · · ·	
•					
have reviewed this report and certify the	information	to be	accurate and complete.	Date	
450.					
				7-1	
				Leianhona	



EQUITABLE RESOURCES ENERGY COMPANY, BALCRON OIL DIVISION

1601 Lewis Avenue P.O. Box 21017 Billings, MT 59104 (406) 259-7860 FAX: (406) 245-136\$

March 4, 1993

State of Utah Uintah County 152 East 100 North Vernal, UT 84078

Gentlemen:

Effective March 1, 1993, the name of our company has changed from Balcron Oil Company to Equitable Resources Energy Company, Balcron Oil Division.

Please make the necessary changes in your records and let me know if there is anything else we need to do in order to effect the change for the 1993 Uintah County Business License.

Sincerely,

Bobbie Schuman

Coordinator of Operations,

Environmental and Regulatory Affairs

/rs

RECEIVED

MAR 0 8 1993

DIVISION OF OIL GAS & MINING

	rof 0%1, Gas a OR CHANGE W		•				Routing:
				rding this change. item is not appli			2-DIS//8-LEC ² 3-VLC 4-RJF
		tor (well so Operator		Designation of Operator Name		1	5-RWM 6-ADA
The op	erator of th	ne well(s) li	sted below ha	s changed (EFF	ECTIVE DATE:	3-1-93)
TO (ne	w operator) (address)	BALCRON OIL PO BOX 21017	DIVISION	COFROM (forma - -		BALCRON O PO BOX 21 BILLINGS	017
			59104 259-7860 N 9890	 		phone <u>(40</u> account n	6)259-7860 o. <u>N</u> 9890
Well(s) (attach addi	tional page if	needed):				
Name:		<i>P</i>	\PI:	Entity:	SecTw	pRng	Lease Type: Lease Type: Lease Type:
Name: Name: Name:			API: API:	Entity: Entity: _ Entity:	SecTw SecTw SecTw	pRng pRng pRng	Lease Type: Lease Type: Lease Type: Lease Type:
1		OCUMENTATION				1	
lec 2.	operator (/	Attach to thi -8-10) Sundry	s form). , or other lea				red from <u>former</u> from <u>new</u> operator
٨	The Departm	this form). ment of Comme any wells in company file	erce has been	contacted if tompany register	the new opera red with the	ator above state?	is not currently (ex/no) If
<u>*</u> 4.	(attach Te comments s	elephone Doc ection of th	umentation Fo nis form. Man	rm to this r	eport). Mak w of Federa	ce note o [.] 1 and Indi	ding this change f BLM status in an well operator
<u>fec</u> 5.		ve been enter ve. <i>(3-19-93)</i>	red in the Oil	and Gas Infor	rmation Syste	em (Wang/II	BM) for each well
				h well listed			
· //				or each well 1			
<u>Jee</u> 8.	Changes ha for distril	ve been incl bution to Sta	uded on the m ate Lands and	onthly "Operat the Tax Commis	or, Address, sion. <i>(3-19-93)</i>	, and Accou)	unt Changes" memo
<u>Jec</u> 9.	A folder h placed the	as been set re for refere	up for the Op ence during ro	erator Change uting and proc	file, and a essing of th	copy of the conjugation	nis page has been documents.

DERATOR	CHANGE WORKSHEET (CONTINUED) Initral each item when completed. Write N/A item is not applicable.
HTITY	REVIEW
1.	(Rule R615-8-7) Entity assignments have been reviewed for all wells listed above. Were entity changes made? (yes/no) (If entity assignments were changed, attach copies of Form 6, Entity Action Form).
	State Lands and the Tax Commission have been notified through normal procedures of entity changes.
OND VI	ERIFICATION (Fee wells only) * 930319 Re'd bond rider e Al. 3-4-93.
1.	(Rule R615-3-1) The new operator of any fee lease well listed above has furnished a proper bond. #5578314/80,000 Beloven oil, A Division of Equitable Resources Energy Company. A copy of this form has been placed in the new and former operators' bond files.
,	
<u>√/n</u> 3.	The former operator has requested a release of liability from their bond (yes/no) Today's date 19 If yes, division response was made by letter dated 19
EASE :	INTEREST OHNER NOTIFICATION RESPONSIBILITY
17 1.	(Rule R615-2-10) The former operator/lessee of any fee lease well listed above has been notified by letter dated
A 2.	Copies of documents have been sent to State Lands for changes involving State leases .
ILMIN	G ん All attachments to this form have been microfilmed. Date: <u>Marsl 3</u> 8 19 <u>93</u> .
IĻING	
<u>ke</u> 1.	Copies of all attachments to this form have been filed in each well file.
<u> 1</u> 2 2.	The <u>original</u> of this form and the <u>original</u> attachments have been filed in the Operator Change file.
OMMEN	
13030 "	Equitable Resources Energy Company, Baleron Oil Division".

E71/34-35

Page	1	of	6
1 846		\mathbf{v}	

MONTHLY OIL AND GAS PRODUCTION REPORT

Operator name and addres	s:					
DAWN SCHINDLER BALCRON OIL PO BOX 21017 BILLINGS MT 59104	Utah Account No. N9890 Report Period (Month/Year) 1 / 93 Amended Report					
/ell Name	Producing	Days	Production Volum	e		
PI Number Entity Location	Zone	Oper	Oil (BBL)	Gas (MSCF)	Water (BBL)	
DNMNT BUTTE 1-34 301330736300030 09S 16E 1	GRRV					
DNMNT BUTTE 1-24 5013307011300050 098 16E 1	GRRV					
LEN FEDERAL #1 01315779301110 098 17E 6	GRRV					
LEN FEDERAL 23-6 301330558301120 098 17E 6	GRRV					
LEN FEDERAL 32-6 101330559 01120 098 17E 6 LEN FEDERAL 41-6	GRRV		,			
LEN FEDERAL 41-6 2133058 1701120 098 17E 6	GRRV					
LEN FEDERAL 43-6 018330583901120 098 17E 6	GRRV					
LEN FEDERAL 21-6 01330584101120 098 17E 6	GRRV					
LEN FEDERAL 34-6 01330586301120 098 17E 6	GRRV					
LEN FEDERAL 13-6 01330918501120 098 17E 6	GRRV		WIW			
LEN FEDERAL 22-6 0]330919301120 098 17E 6	GRRV	_	-WIW			
LEN FEDERAL 12-5 013306[1]:01125 098 17E 5	GRRV					
LEN FEDERAL 12-6 301330582 01135 098 17E 6	GRRV					
	т	OTAL				
mments (attach separate sheet if nec						
and and ship and addition the						
ave reviewed this report and certify the	e intormation	to be	accurate and compl	ete. Date		
t · · · · · · · · · · · · · · · · · · ·						

OPERATOR ACCT. NO. H 9890

Billings 59104

DIVISION OF

ACTION	CURRENT	NEW ENTITY NO.	AT CHARGE AS	& MINING WELL HAHE			SPUQ	T			
					00	SC	TP	OCATION DR	COUNTY	DATE	EFFECT IVE DATE
D	16788	11492	4301331195	AF 31-6	Lot 2	6	95	17 E	Duchesne		7/1/93
WELL 1 C			11,								1 1 1 1 1 3
	ے (onah	Unit								٠
ļ						•					:
D	01120	11492	4301330559	AF 32-6.	SW	1.	95	10.0			7/1/93
WELL 2 C	ONMENTS:			<i>3</i>	NE	٥	13	176	Duchesne		11/93
					•						•
					ing #						
5	01125	111100		0.5	SW RE	1	1			···	
	01120	11492	4301330586	AF 34-6	58 Æ	6	95	17E	Duchesna		1/1/93
MELL 3 CO	HHENTS:			•				<u>-</u>	<u> </u>		1 1 10
								,			
		_Y	,						<u>.</u>		
<i>(L)</i>	01120	11492	4301330581	AF 41-6	NE	6	95	17E	N. 1		7/1/03
WELL 4 CO	MHENTS:	,	·		110 = 1		101	1111	Duchesne		11/93
		•		•	•						
1)	01120	11400	4301330583	AF 43-6	NE		T				7/ /
HETT 2 COL		11/12/	42013302831	AF 43-6	SE	Le l	951	17E	Duchesne		1/1/93
3 (0)	erill);										
				•••					•		
ACTION COL	DES (See las	tructions o	n back of form)								
A -	Establish	ev entity 6	or new well (sino	la vall aslui						1 4.	11.

B - Add new well to existing entity (group or unit well)

C - Re-assign well from one existing entity to another existing entity

D - Re-assign well from one existing entity to a new entity

E - Other (explain in comments section)

MOTE: Use COMMENT section to explain why each Action Code was selected.

(3/69)

5

Signature

Phone No. 1406, 259-7860



1601 Lewis Avenue Billings, MT 59102 March 22, 1996

Utah Division of Oil, Gas and Mining 355 West North Temple Salt Lake City, UT 84180



Gentlemen:

Effective April 1, 1996, our name will change from Equitable Resources Energy Company, Balcron Oil Division to Equitable Resources Energy Company. Attached is a sundry notice reflecting that change. To simplify paperwork, I have done one sundry notice with copies for each of the wells. To this letter I have attached a list of our wells for your ease in filing the sundry notices in the well files. This should be sufficient for your purposes.

I have the listings on a spreadsheet so if it would be easier for you to have them sorted differently (for example, the Montana Board of Oil and Gas prefers them sorted by API number), please give me a call at (406) 259-7860, extension 240 and I would be glad to provide a list to your specifications.

This change affects only our company name. The physical locations of our offices and the personnel remain the same. We will be changing our well signs and ask for your patience and cooperation as this will be done as soon as possible but may take some time since we do have so many properties at which to make the change.

If you have any questions, please do not hesitate to give me a call.

Sincerely,

Bobbie Schuman Regulatory and

Environmental Specialist

/hs

Enclosures

OF UTAH DIVISION OF OIL, GAS AND MINING

			5. Lease Designation and Serial Number:
		·	See attached listing
SUNDR	Y NOTICES AND REPORT	S ON WELLS	6. If Indian, Allottee or Tribe Name:
Do not use this form for po Use AF	roposals to drill new wells, deepen existing wells, or to r PPLICATION FOR PERMIT TO DRILL OR DEEPEN form	reenter plugged and abandoned wells. for such proposals.	7. Unit Agreement Name: See attached listing
. Type of Well: OIL . GAS	S□ OTHER: See attached 1	listing	8. Well Name and Number: See attached listing
Name of Operator: Equitable Re	API Well Number: See attached listing		
Address and Telephone Number: 1601 Lewis A	10. Field and Pool, or Wildcat: See attached listing		
Location of Well	Tollac Avellacy Billings, III	<u> 59102 (406) 259-7860</u>	Jace accaence 113cmg
	ee attached listing		county: See attached list
QQ, Sec.,T.,R.,M.:	State: UTAH		
CHECK APPR	ROPRIATE BOXES TO INDICATE	E NATURE OF NOTICE, REPO	RT, OR OTHER DATA
	TICE OF INTENT (submit in Duplicate)		DUENT REPORT Driginal Form Only)
] Abandon	☐ New Construction	☐ Abandon *	☐ New Construction
Repair Casing	☐ Pull or Alter Casing	☐ Repair Casing	Pull or Alter Casing
Change of Plans	☐ Recomplete	☐ Change of Plans	☐ Reperiorate
Convert to Injection	☐ Reperforate	☐ Convert to Injection	☐ Vent or Flare
Fracture Treat or Acidize	☐ Vent or Flare	☐ Fracture Treat or Acidize	Water Shut-Off Wate
Multiple Completion	☐ Water Shut-Off	□ Other Operator name	e change
Other		_	
		Date of work completion	
proximate date work will star	rt		nd Recompletions to different reservoirs on WELL PRT AND LOG form.
		Must be accompanied by a cement verification.	allon report.
Effective Apr Effective Apr Energy Compar Physical loca (406) 259-780	ril. 1, 1996, operator will ny, Balcron Oil Division Tation of the operator remails of FAX: (406) 145-1361. fects the wells on the att	change its name from E O: Equitable Resources E ins as: 1601 Lewis Avenu This is to report the ope	quitable Resources nergy Company. e: Billings. MT 59102
			Ŷ
	c.	•	

(I

03/27/96			} '''		EQUITA	UITABLE REOURSES ENERGY COMPANY, WESTERN REGION-OPERATED WELL LIST							 	
Revised 3/20/96						JRRENT)	T	T		ST = State	101		 	
						T	1			FED. OR STATE			BLM	UNIT OF HE
WELL NAME	FIELD	QTR/QTR	SEC.	TWP.	RANGE	COUNTY	ST.	STATUS	ZONE	LEASE NO.	API NUMBER	FOOTAGES	OFFI	UNIT OR WEL
	*======================================	******		====	22222						AFT NOMBER	 	OFFI	FILE NO.
		======	====	====		========			***************					
							+			T				
A. Anderson State #1-16	Monument Butte	sw sw	16	98	17E	Duchesne	UΤ	Oil (St)	Green River	ML-3453	43-013-15582	660' FSL, 560' FWL	 	0.1
Allen Federal #1-6	Monument Butte	SE SE	6	98	17E	Duchesne	UΤ	ww	Green River	U-020252-A	43-013-15779		17	Beluga
Allen Federal #12-5	Monument Butte	SW NW	5	98	17E	Duchesne	υT	Oil	Green River	U-020252	43-013-30611	660' FSL, 660' FEL	Vernal	Jonah
Allen Federal #12-6	Monument Butte	SW NW	6	98		Duchesne	υī	Oil	Green River	U-020252-A	43-013-30511	1980' FNL, 660' FWL	Vernal	Jonah
Vien Federal #13-6	Monument Butte	NW SW	6	98	17E	Duchesne	UT	ww	Green River	 	43-013-30562	1980' FNL, 604' FWL	Vernal	Jonah
Vien Federal #21-5	Monument Butte	NE NW	5	98		Duchesne	UT	Oil	Green River	U-020252-A		2070' FSL, 578' FWL	Vernal	Jonah
Vien Federal #21-6	Monument Butte	NE NW	6	98		Duchesne	UT	Oil	Green River	U-020252-A		660' FNL, 1980' FWL	Vemai	Jonah
Vien Federal #22-6	Monument Butte	SE NW	6	98		Duchesne	UT	ww	Green River	 		660' FNL, 1980' FWL	Vernal	Jonah
Ulen Federal #23-6	Monument Butte	NE SW	6	98		Duchesne	UT	Oil	Green River	U-020252-A		2141' FNL, 1902' FWL	Vernal	Jonah
— —		NW NE	6	98		Duchesne	υT	ww		 		1980' FSL, 1980' FWL	Vernai	Jonah
		SW NE	6	98		Duchesne	υT	Oil	Green_River			660' FNL, 1980' FEL	Vernal	Jonah
		SW SE	6	98		Duchesne	UT	Oil	Green River	 	43-013-30559	1980' FNL, 1980' FEL	Vemai	Jonah
H F-1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		NE NE	6	98		Duchesne	+	Oil	Green River			662' FSL, 2075' FEL	Vemai	Jonah
lien Federal #43-6		NE SE	6	98		Duchesne	+	Oil	Green River	U-020252-A	43-013-30581	661' FNL, 655' FEL	Vernal	Jonah
		NW NW	5	98		Duchesne		Oil	Green River	1	43-013-30583	1980' FSL, 660' FEL		Jonah
4 4 1 1 1 1		SWNW	7	8S		Uintah		WIW	Green River			660' FNL, 660' FWL	Vemal	Jonah
		C/SW	12	16S		Millard			Green River		**	1920' FNL, 550' FWL		Coyote Basin
		NW NE	6	98			υī		Paleozoic	UTU-69960			Richfield	<u> </u>
		SW NW	5	8S			_	Gas	Green River	 		708' FNL, 2076' FEL	Vemai	
		NW SW	5	85					Green River			1980' FNL, 660' FWL	Vernal	Coyote Basin
-l 0		NW SW	7	85					Green River			1605' FSL, 586' FWL	Vemal	Coyote Basin
		NE NW	5	8S					Green River				Vemai	Coyote Basin
		SE NW	7			Uintah			Green River		43-047-32260	660' FNL, 1980' FWL	Vernal	Coyote Basin
		NE SW		8S 8S		Jintah			Green River		43-047-32256	1749' FNL, 1601' FWL	Vernal	Coyote Basin
		W NE	$\overline{}$						Green River			2110' FSL, 1980' FWL	Vemai	Coyote Basin
			7	88					Green River			561' FNL, 1977' FEL	Vemal	Coyote Basin
		W SE	7	8S 8S	25E L	Jintah	UΤ	Oil	Green River	U-063597-A	43-047-32257	1892' FSL, 2326' FEL	Vernal	Coyote Basin

Page 1 APR - 8 1996

Division of Oil, Gas OPERATOR CHANGE F			•	Routing:
Attach all documentat Initial each listed i	ion received by the division tem when completed. Write N/	regarding this change 'A if item is not appl	icable.	2-DENS-8-FILE 3-VLD GILLS
□ Change of Opera □ Designation of	_	□ Designation (KKX Operator:Name		5-IROW 6-FILM
The operator of t	he well(s) listed below	has changed (EFF	ECTIVE DATE: 4-1-9)6)
TO (new operator) (address)	EQUITABLE RESOURCES EN 1601 LEWIS AVE BILLINGS MT 59102-412 phone (406)259-7860 account no. N9890		(address) BALCRO 1601 I BILLIN phone	BLE RESOURCES ENERGY CON OIL DIVISION EWIS AVE IGS MT 59102-4126 (406)259-7860 t no. N 9890
Hell(s) (attach addi	tional page if needed):			
Name :	API: 23-30 API: API: API: API: API: API: API: API:	Entity: Entity: Entity: Entity:	SecIWPRngSecTWPRngSecTWPRng_ SecTWDRng	Lease Type: Lease Type: Lease Type: Lease Type:
/	-8–10) Sundry or other ttach to this form). $\mathcal{C}_{\mathcal{L}_{\mathcal{C}}}$	col 7-9-16 2 1-0 14/		
operating a	ent of Commerce has beenny wells in Utah. Is ompany file number:	company register	he new operator abo ed with the state?	ve is not currently (yes/no) If
comments se	and Federal Hells ON ephone Documentation ction of this form. Note that the place prior to	form to this re Management review	port). Make note of Federal and Ir	of BLM status in I dian well operator
20 5. Changes have	e been entered in the O	il and Gas Inform	nation System (Wang	/IBM) for each well
Lec 6. Cardex file	has been updated for eached have been updated	ach well listed a	bove. (4-11-967	
2C 7. Well file la	abels have been updated	for each well li	sted above. (4-11-96)	
408. Changes have for distribu	e been included on the Ition to State Lands and	monthly "Operato I the Tax Commiss	r, Address, and Acc ion <i>. (4-10-96</i>)	count Changes" memo
№ 9. A folder has placed there	s been set up for the (for reference during r	Operator Change fouting and proces	ile, and a copy of Ssing of the origina	this page has been

OPERATOR	CHANGE WORKSHEET (CONTINUED) Initial each item when completed. Write N/A if item is not applicable.
/	REVIEW
Le1.	(Rule R615-8-7) Entity assignments have been reviewed for all wells listed above. Were entity changes made? (yes/no) (If entity assignments were changed, attach copies of Form 6, Entity Action Form).
N/A 2.	State Lands and the Tax Commission have been notified through normal procedures of entity changes.
BOND VI	RIFICATION (Fee wells only) # 5578314 (\$80,000) Siles Ins. Co. (Bond Rider In Progress)
Lic 1.	(Rule R615-3-1) The new operator of any fee lease well listed above has furnished a proper bond.
2.	A copy of this form has been placed in the new and former operators' bond files.
MA 3.	The former operator has requested a release of liability from their bond (yes/no) Today's date 19 19 If yes, division response was made by letter dated 19
LEASE I	NTEREST OHNER NOTIFICATION RESPONSIBILITY
, 	(Rule R615-2-10) The former operator/lessee of any fee lease well listed above has been notified by letter dated 19, of their responsibility to notify any person with an interest in such lease of the change of operator. Documentation of such notification has been requested.
<u>15</u> 2.	Copies of documents have been sent to State Lands for changes involving State leases.
FILMING	
<u> </u>	All attachments to this form have been microfilmed. Date: May 20 1994.
ILING	
1.	Copies of all attachments to this form have been filed in each well file.
	The <u>original</u> of this form and the <u>original</u> attachments have been filed in the Operator Change file.
COMMENT	S
9/204/10	Blm BIA Formal approval not necessary".

WE71/34-35

STATE OF UTAH FORM 10

DIVISION OF OIL, GAS AND MINING 355 West North Temple, 3 Triad, Suite 350, Salt Lake City, UT 84180-1203

Page 3	of_11
--------	-------

MONTHLY OIL AND GAS PRODUCTION REPORT

OPERATOR NAME AND ADDRESS:			UTAH	ACCOUNT NUMBE	.R:N9890		
BALCRON OIL DIVISION EQUITABLE RESOURCES END 1601 LEWIS AVE BILLINGS MT 59102-4126		REPORT PERIOD (MONTH/YEAR): 3 / 96 AMENDED REPORT (Highlight Changes)					
Well Name	Producing	Well	Days		Production Volumes		
API Number Entity Location	Zone	Status	Oper	OIL(BBL)	GAS(MCF)	WATER(BBL)	
MONUMENT FED 22-12J 4301315796 11492 095 16E 12 MONUMENT FED 42-11J	GRRV						
4301330066 11492 095 16E 11 VALLEN FEDERAL 23-6	GRRV						
4301330558 11492 09S 17E 6	GRRV			· · · · · · · · · · · · · · · · · · ·			
4301330559 11492 095 17E 6	GRRV						
4301330581 11492 095 17E 6	GRRV						
01330582 11492 095 17E 6 LEN FEDERAL 43-6 4301330583 11492 095 17E 6	GRRV						
4301330583 11492 095 17E 6	GRRV						
4301330584 11492 09S 17E 6	GRRV			***			
VALLEN FEDERAL 34-6 4301330586 11492 095 17E 6	GRRV					•	
FEDERAL 2-1 4301330603 11492 095 16E 1	GRRV						
VALLEN FEDERAL 12-5 4301330611 11492 095 17E 5	GRRV				/	<u> </u>	
ALLEN FEDERAL 21-5 4301330612 11492 095 17E 5	GRRV					· .	
CASTLE PK FED 31-15 4301330613 11492 095 16E 15	GRRV						
			TOTALS				
XMMENTS:							
					m sa Disprilión Transprince de A	on: hogo: of hod: hidanoli	
					- Copperation	n, ngienv	
hereby certify that this report is true and complete to	the best of my	knowledge.		D	ate:	Rule releven	
lame and Signature:					Telephone Number:		
(12/93)							

1601 Lewis Avenue Billings, MT 59102 DECEIVE MAY 3 0 1997 DIV. OF OIL, GAS & MINING

Office: (406) 259-7860 FAX: (406) 245-1365
FAX: (406) 245-1361

May 27, 1997

Utah Board Of Oil, Gas, & Mining 1594 West North Temple Suite-1220 Salt Lake City, Utah 84114

In accordance with your request please find enclosed the 1997 produced water analysis for the Uinta Basin waterflood and water disposal operations which are operated by Equitable Resources Energy Company. These water analysis are for wells that are re-injecting or disposing produced water back into the Green River Formation via the following facilities:

Jonah Secondary Recovery Unit Beluga Secondary Recovery Unit Coyote Basin Secondary Recovery Unit Castle Draw (State Section-2) Pilot Waterflood Pariette Bench Water Disposal Well #4

Equitable Resources Energy Company inadvertently failed to submit a copy of these water analysis when they were sent to the EPA and BLM. If there are any questions please contact me at our Billings, Montana office at 406-259-7860.

Respectfully,

John Zellitti

District Production Engineer



2060 SOUTH 1500 EAST VERNAL, UTAH 84078

Telephone (801) 789-4327

Water Analysis Report

Jonah Unit

Customer: EREC - Western Oil Company

Field: Monument Butte Field

Address: 1601 Lewis Avenue

Lease: Allen Federal Lease

City: Billings

Location: Well No. 32-06

State: MT

Postal Code: 59104-

Sample Point: wellhead

Attention: John Zellitti

Date Sampled: 23-Jan-97

cc1: Dan Farnsworth

Date Received: 23-Jan-97

cc2: Joe Ivey

Date Reported: 08-Feb-97

cc3 :

Salesman: Lee Gardiner

Analyst: Karen Hawkins Allen

CATIONS **ANIONS** Calcium: 200 mg/l Chloride: 7,200 mg/l 34 Magnesium: mg/l Carbonate: 60 mg/l Barium: 0 mg/l Bicarbonate: 805 mg/l Strontium: mg/l Sulfate: 108 mg/l Iron: 1.0 ma/l Sodium: 4731 mg/l 7.90 **Specific Gravity:** pH (field): 1.01 grams/ml degrees F Temperature: 85 **Total Dissolved Solids:** 13,139 ppm Ionic Strength: 0.22 CO2 in Water: 1 mg/l CO2 in Gas: 0.03 mole % ohm/meters Resistivity: **H2S in Water:** 0.0 mg/l O2 in Water: 0.000 ppm Ammonia: ppm Comments:

SI calculations based on Tomson-Oddo

Calcite PTB: 166.5 Calcite (CaCO3) SI: 1.71 -2.19**Gypsum PTB:** N/A Gypsum (CaSO4) SI: Barite (BaSO4) SI: N/A Barite PTB: N/A Celestite PTB: N/A Celestite (SrSO4) SI: N/A

INLAND

Inland Resources Change of Operator		1			:		
WELL NAME	LOCATION	COUNTY	ST	FIELD NAME	API NUMBER	LEASE NO.	AGEEMENT
BALCRON FEDERAL #24-3Y	SESW 3 9S 17E	DUOLIGONIE					
BALCRON FEDERAL #44-4Y	SESE 4 9S 17E	DUCHESNE	UT	MONUMENT BUTTE (CD)		UTU75037	
BALCRON FEDERAL #14-3Y		DUCHESNE	UT	MONUMENT BUTTE (CD)		UTU65967	
LMONUMENT FEDERAL #11-11Y	SW SW 3 9S 17E	DUCHESNE	UT	MONUMENT BUTTE (CD)		UTU75037	
MONUMENT FEDERAL #11-114	NW NW 119S 17E	DUCHESNE	UT	MONUMENT BUTTE (CD)		UTU65210	
ALLEN FEDERAL #1	NW NE 5 9S 17E	DUCHESNE	UT	MONUMENT BUTTE (CD)		UTU74808	
ALLEN FEDERAL #12-5	SESE 6 9S 17E	DUCHESNE	UT	MONUMENT BUTTE (J)	43-013-15779-00	UTU020252A	UTU72086A
ALLEN FEDERAL #12-5 ALLEN FEDERAL #12-6	SWNW 5 9S 17E	DUCHESNE	UT		43-013-30611-00	UTU020252	UTU72086A
	SWNW 6 9S 17E	DUCHESNE	UT	MONUMENT BUTTE (J)	43-013-30582-00	UTU020252A	UTU72086A
ALLEN FEDERAL #13-6	NWSW 6 9S 17E	DUCHESNE	UT	MONUMENT BUTTE (J)	43-013-30918-00	UTU020252A	UTU72086A
ALLEN FEDERAL #21-5	NENW 5 9S 17E	DUCHESNE	UT	MONUMENT BUTTE (J)	43-013-30612-00	UTU020252	UTU72086A
ALLEN FEDERAL #21-6	LOT3 6 9S 17E	DUCHESNE	UT	MONUMENT BUTTE (J)	43-013-30584-00	UTU020252A	UTU72086A
ALLEN FEDERAL #22-6	SENW 6 9S 17E	DUCHESNE	UT	MONUMENT BUTTE (J)	43-013-30919-00	UTU020252A	UTU72086A
ALLEN FEDERAL #23-6	NESW 6 9S 17E	DUCHESNE	UT	MONUMENT BUTTE (J)	43-013-30558-00	UTU020252A	UTU72086A
ALLEN FEDERAL #31-6	LOT2 6 9S 17E	DUCHESNE	UT	MONUMENT BUTTE (J)	43-013-31195-00	UTU020252A	UTU72086A
ALLEN FEDERAL #32-6	SWNE 6 9S 17E	DUCHESNE	UT	MONUMENT BUTTE (J)	43-013-30559-00	UTU020252A	UTU72086A
ALLEN FEDERAL #34-6	SWSE 6 9S 17E	DUCHESNE	UT	MONUMENT BUTTE (J)	43-013-30586-00	UTU020252A	UTU72086A
ALLEN FEDERAL #41-6	NENE 6 9S 17E	DUCHESNE	UT	MONUMENT BUTTE (J)	43-013-30581-00	UTU020252A	UTU72086A
ALLEN FEDERAL #43-6	NESE 6 9S 17E	DUCHESNE	UT	MONUMENT BUTTE (J)	43-013-30583-00	UTU020252A	UTU72086A
ALLEN FEDERAL A #1	NWNW 59S 17E	DUCHESNE	UT	MONUMENT BUTTE (J)	43-013-15780-00	UTU020252	UTU72086A
680 GOV'T #1	NWSW 129S 16E	DUCHESNE	UT	MONUMENT BUTTE (J)	43-013-15111-00	UTU035521A	UTU72086A
LC&O GOV'T #2	NWSE 129S 16E	DUCHESNE	UT	MONUMENT BUTTE (J)	43-013-15112-00	UTU035521	UTU72086A
C&O GOV'T #4	NESW 129S 16E	DUCHESNE	UT	MONUMENT BUTTE (J)	43-013-30742-00	UTU035521A	UTU72086A
CASTLE PEAK FEDERAL #22-15	SENW 159S 16E	DUCHESNE	UT	MONUMENT BUTTE (J)	43-013-30634-00	UTU017985	UTU72086A
CASTLE PEAK FEDERAL #24-15	SESW 159S 16E	DUCHESNE	UT	MONUMENT BUTTE (J)	43-013-30631-00	UTU017985	UTU72086A
CASTLE PEAK FEDERAL #31-15	NWNE 159S 16E	DUCHESNE	UT	MONUMENT BUTTE (J)	43-013-30613-00	UTU017985	UTU72086A
CASTLE PEAK FEDERAL #33-15	NWSE 159S 16E	DUCHESNE	UT	MONUMENT BUTTE (J)	43-013-30632-00	UTU017985	UTU72086A
CASTLE PEAK FEDERAL #44-10	SESE 109S 16E	DUCHESNE	UT	MONUMENT BUTTE (J)	43-013-30630-00	UTU017985	UTU72086A
CASTLE PEAK FEDERAL #42-15	SENE 159S 16E	DUCHESNE	UT		43-013-30633-00	UTU017985	UTU72086A
FEDERAL #2-1	NENE 1 9S 16E	DUCHESNE	UT		43-013-30603-00	UTU33992	UTU72086A
GETTY #12-1	NWNE 129S 16E	DUCHESNE	UT		43-013-30889-00	UTU44426	UTU72086A
GETTY #7-A	NENE 7 9S 17E	DUCHESNE	UT		43-013-30926-00	UTU44426	UTU72086A
GETTY #7-C	NENW 7 9S 17E	DUCHESNE	UT		43-013-30961-00	UTU44426	UTU72086A
COATES FEDERAL #1	SESW 119S 16E	DUCHESNE	UT	the course of the course section and the course of the cou	43-013-15789-00	UTU096547	UTU72086A
GOATES FEDERAL #3	NWNW 149S 16E	DUCHESNE	UT		43-013-15791-00	UTU096547	UTU72086A
MONUMENT BUTTE #1-14	SWSW 19S 16E	DUCHESNE	UT		43-013-30703-00	UTU18399	UTU72086A
MONUMENT BUTTE #1-23	NESW 1 9S 16E	DUCHESNE	UT		43-013-30646-00	UTU18399	UTU72086A
MONUMENT BUTTE #1-24	SESW 1 9S 16E	DUCHESNE	UT		43-013-30701-00	UTU18399	UTU72086A
MONUMENT BUTTE #1-34	SWSE 1 9S 16E	DUCHESNE	UT	The state of the s	43-013-30736-00	UTU52013	UTU72086A
MONUMENT BUTTE #1-43	NESE 1 9S 16E	DUCHESNE	UT	the contract of the contract o	43-013-30734-00	UTU52013	UTU72086A

STATE OF UTAH DIVISION OF OIL, GAS AND MINING

			5. Lease Designation and Serial Number:				
			See Attached				
SUNDRY N	OTICES AND REPORTS	ON WELLS	6. If Indian, Allottee or Tribe Name:				
			n/a				
Do not use this form for proposals	to drill new wells, deepen existing wells, or to reent	er plugged and abandoned wells	7. Unit Agreement Name;				
Use APPLICAT	ION FOR PERMIT TO DRILL OR DEEPEN form for a	uch proposals.	See Attached				
1. Type of Well: OIL XX GAS	OTHER:		8. Well Name and Number:				
		PECEIVED	See Attached				
2. Name of Operator: Inland Pro	duction Company	OCT_1_3_1997	9. API Well Number: See Attached				
3. Address and Telephone Number:			10. Field and Pool, or Wildcat:				
475 - 17th	Street, Suite 1500, Den	ver, CO 80202	See Attached				
4. Location of Well							
Footages: See Attach	ed Exhibit		County:				
QQ, Sec.,T.,R.,M.:			State:				
11. CHECK ADDRODD	NATE DOVED TO BUILDING						
CHECK APPROPR	RIATE BOXES TO INDICATE N	ATURE OF NOTICE, REPORT	T, OR OTHER DATA				
	DF INTENT	SUBSEQU	ENT REPORT				
(Submit at	Duplicate)	(Submit Ork	ginal Form Only)				
Abandon	□ New Construction	☐ Abandon *	□ New Construction				
☐ Repair Casing	Pull or Alter Casing	☐ Repair Casing	☐ Pull or Alter Casing				
Change of Plans	☐ Recomplete	☐ Change of Plans	☐ Reperforate				
☐ Convert to Injection	☐ Reperforate	☐ Convert to Injection	☐ Vent or Flare				
☐ Fracture Treat or Acidize	☐ Vent or Flare	☐ Fracture Treat or Acidize	☐ Water Shut-Off				
☐ Multiple Completion	☐ Water Shut-Off	Other Change of Opera	_				
☑ Other <u>Change of Opera</u>	ntor		1001				
		Date of work completion 9-30	D-97'				
Approximate date work will start		•					
		COMPLETION OR RECOMPLETION REPORT	Recompletions to different reservoirs on WELL AND LOG form.				
		* Must be accompanied by a cement verification	Must be accompanied by a cement vertification report.				
DESCRIBE PROPOSED OR COMPLETED OPER vertical depths for all markers and zones pertins	PATIONS (Clearly state all pertinent details, and givent to this work.)	e pertinent dates. If well is directionally drilled, 9h	ve subsurface locations and measured and true				
Effective September 3 wells on the attached	0, 1997, Inland Producti list. The previous ope	on Company will take overator was:	ver operations of the				
			rces Energy Company				
		1601 Lewis Aven	3				
		Billings, MT 5	9102				
and conditions of the	0, 1997, Inland Producti leases for operations of	conducted on the leased	ole under the terms				
thereof under State o	f Utah Statewide Bond No	· 4471291.					
			OCT 1 ⁽¹ 1997)				
13. Name & Signature:	CHRIS	A. POTTER, ATTORNEY-IN-FA	CT Date: 9/30/97				

This space for State use only)

[4\94)



(406) 259-7860 Telephone (406) 245-1361 Fax

December 10, 1997

Lisha
State of Utah
Division of Oil, Gas and Mining
1594 West North Temple, Suite 1210
Box 145801
Salt Lake City, UT 84114-5801

Dear Lisha:

RE: Equitable Sale of Utah Properties

Effective September 30, 1997, Equitable Resources Energy Company sold all of its Utah properties to Inland Production Company.

Please feel free to contact me if you require additional information.

Sincerely,

Molly Conrad

Agent for Equitable Resources

Energy Company

/mc



Crazy Mountain Oil & Gas Services P.O. Box 577 Laurel, MT 59044 (406) 628-4164 (406) 628-4165

TO: Lishar St of Wan.

FROM.

Molly Conrad

Crazy Mountain Oil & Gas Services

(406) 628-4164

Pages Attached - Including Cover Sheet 2.

NOTE

Here is the letter you requested. Callief you need anything further.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT Utah State Office P.O. Box 45155

Salt Lake City, UT 84145-0155

100 14 199 H = 17 04 . 93

IN REPLY REFER TO UT-931

January 13, 1998

Inland Production Company 475 17th Street, Suite 1500 Denver, Colorado 80202

Re:

Jonah (Green River) Unit

Duchesne County, Utah

Gentlemen:

On January 13, 1998, we received an indenture dated November 17, 1997, whereby Equitable Resources Energy Company resigned as Unit Operator and Inland Production Company was designated as Successor Unit Operator for the Jonah (Green River) Unit, Duchesne County, Utah.

This indenture was executed by all required parties and the signatory parties have complied with Sections 5 and 6 of the unit agreement. The instrument is hereby approved effective January 13, 1998. In approving this designation, the Authorized Officer neither warrants nor certifies that the designated party has obtained all required approval that would entitle it to conduct operations under Jonah (Green River) Unit Agreement.

Your statewide (Utah) oil and gas bond No. 0056 will be used to cover all operations within the Jonah (Green River) Unit.

It is requested that you notify all interested parties of the change in unit operator. Copies of the approved instruments are being distributed to the appropriate federal offices, with one copy returned herewith.

Sincerely,

/s/ Robert A. Henricks

Robert A. Henricks Chief, Branch of Fluid Minerals

Enclosure

bcc: District Manager - Vernal (w/enclosure)

Division of Oil Gas & Mining / Minerals Adjudication Group U-932

File - Jonah (Green River) Unit (w/enclosure)

MMS - Data Management Division

Agr. Sec. Chron Fluid Chron

U-931:TAThompson:tt:1/13/98

Page No. 01/13/98 1

WELL STATUS REPORTS UTAH STATE OFFICE

STATUS

INSPECTION ITEM API NO. WELL QTQT SEC TWN RNG WELL LEASE NAME OPERATOR

NUMBER

** INSPECTION	ITEM UTU72086A	JONAH	(GR) SECO	ONDARY R	RECOVERY	UNIT		
UTU72086A	430131511100s1			12 9s	16E	POW	UTU035521A	EQUITABLE RESOURCES ENERG
UTU72086A	430131578000\$1	1	NWNW	5 98	17E	POW	UTU020252	EQUITABLE RESOURCES ENERG
UTU72086A	430131577900\$1		SESE	6 98	17E	WIW	UTU020252A	EQUITABLE RESOURCES ENERG
UTU72086A	430131578900s1	1	SESW	11 9s	16E	POW	UTU096547	EQUITABLE RESOURCES ENERG
UTU72086A	430131579200\$1	1	SESE	11 98	16E	POW	UTU096550	EQUITABLE RESOURCES ENERG
UTU72086A	430133070200\$1	1-13	NUSU	1 98	16E	WIW	UTU18399	EQUITABLE RESOURCES ENERG
UTU72086A	430133070300s1	1-14	SWSW	1 98	16E	POW	UTU18399	EQUITABLE RESOURCES ENERG
UTU72086A	430133064600\$1	1-23	NESW	1 98	16E	POW	UTU18399	EQUITABLE RESOURCES ENERG
UTU72086A	430133070100s1	1-24	SESW	1 9s	16E	WIW	UTU18399	EQUITABLE RESOURCES ENERG
UTU72086A	430133073500s1	1-33	NWSE	1 98	16E	WIW	UTU52013	EQUITABLE RESOURCES ENERG
UTU72086A	430133073600s1	1-34	SWSE	1 9s	16E	POW	UTU52013	EQUITABLE RESOURCES ENERG
UTU72086A	430133073400s1	1-43	NESE	1 9s	16E	POW	UTU52013	EQUITABLE RESOURCES ENERG
UTU72086A	430133136200\$1	11-6	L4	6 9s	17E	WIW	UTU020252A	EQUITABLE RESOURCES ENERG
UTU72086A	430133149200\$1	11-7J	NWNW	7 9s	17E	WIW	UTU44426	EQUITABLE RESOURCES ENERG
UTU72086A	430133088900s1	12-1	NWNE	12 9s	16E	POW	UTU44426	EQUITABLE RESOURCES ENERG
UTU72086A	430133141700\$1	12-11J	SWNW	11 9s	16E	WIW	UTU096550	EQUITABLE RESOURCES ENERG
UTU72086A	430133141000s1	12-12J	SWNW	12 9s	16E	WIW	UTU096550	EQUITABLE RESOURCES ENERG
UTU72086A	430133061100s1	12-5	SWNW	5 9s	17E	POW	UTU020252	EQUITABLE RESOURCES ENERG
UTU72086A	430133058200s1	12-6	SWNW	6 9s	17E	POW	UTU020252A	EQUITABLE RESOURCES ENERG
UTU72086A	430133149300s1	12-7J	SWNW	7 9s	17E	POW	UTU44426	EQUITABLE RESOURCES ENERG
UTU72086A	430131579000s1	13-11J	NWSW	11 9s	16E	POW	UTU096547	EQUITABLE RESOURCES ENERG
UTU72086A	430133137000s1	13-5	NUSU	5 9s	17E	WIW	UTU020252	EQUITABLE RESOURCES ENERG
UTU72086A	430133091800\$1	13-6	NUSU	6 9s	17E	WIW	UTU020252A	EQUITABLE RESOURCES ENERG
UTU72086A	430133137400s1	14-11	SWSW	11 9s	16E	WIW	UTU096547	EQUITABLE RESOURCES ENERG
UTU72086A	430133141100s1	14-12J	SWSW	12 9\$	16E	WIW	UTU035521A	EQUITABLE RESOURCES ENERG
UTU72086A	430133138500s1	14-5	SWSW	5 9s	17E	POW	UTU020252	EQUITABLE RESOURCES ENERG
UTU72086A	430131511200\$1	2	NWSE	12 9s	16E	POW	UTU035521	EQUITABLE RESOURCES ENERG
UTU72086A	430131579300\$1	2	NWNE	14 9s	16E	POW	UTU096550	EQUITABLE RESOURCES ENERG
UTU72086A	430133060300\$1	2-1	L1	1 9s	16E	POW	UTU33992	EQUITABLE RESOURCES ENERG
UTU72086A	430133140600X1	21 12J	NENW	12 9s	16E	- ABD	UTU096550	EQUITABLE RESOURCES ENERG
UTU72086A	430133142100s1	21-14J	NENW	14 9s	16E	WIW	UTU096547	EQUITABLE RESOURCES ENERG
UTU72086A	430133142200x1	21~15J -	NENW	15-93	16E-	ABD	UTU017985	EQUITABLE RESOURCES ENERG
UTU72086A	430133061200s1	21-5	NENW	5 9\$	17E	POW	UTU020252	EQUITABLE RESOURCES ENERG
UTU72086A	430133058400s1	21-6	L3	6 9s	17E	POW	UTU020252A	EQUITABLE RESOURCES ENERG
UTU72086A	4301315 79 600s2	22-12J	SENW	12 9s	16E	POW	UTU096550	EQUITABLE RESOURCES ENERG
UTU72086A	430133063400s1	22-15	SENW	15 9s	16E	POW	UTU017985	EQUITABLE RESOURCES ENERG
UTU72086A	430133138400s1	22-5	SENW	5 9\$	17E	WIW	UTU020252	EQUITABLE RESOURCES ENERG
UTU72086A	430133091900s1	22-6	SENW	6 9\$	17E	WIW	UTU020252A	EQUITABLE RESOURCES ENERG
UTU72086A	430133136900\$1	23-11	NESW	11 9s	16E	WIW	UTU096550	EQUITABLE RESOURCES ENERG
UTU72086A	430133137300s1	23-15	NESW	15 9s	16E	WIW	UTU01 79 85	EQUITABLE RESOURCES ENERG
UTU72086A	430133138300\$1	23-5	NESW	5 9\$	17E	POW	UTU020252	EQUITABLE RESOURCES ENERG
UTU72086A	430133055800\$1	23-6	NESW	6 9s	17E	POW	UTU020252A	EQUITABLE RESOURCES ENERG
UTU72086A	430133140900s1	24-12J	SESW	12 9s	16E	PO₩	UTU035521A	EQUITABLE RESOURCES ENERG
UTU72086A	430133063100s1	24-15	SESW	15 9s	16E	POW	UTU017985	EQUITABLE RESOURCES ENERG
UTU72086A	430133137500s1	24-5	SESW	5 9\$	17E	WIW	UTU020252	EQUITABLE RESOURCES ENERG
UTU72086A	430133136300s1	24-6	SESW	6 98	17E	WIW	UTU020252A	EQUITABLE RESOURCES ENERG
UTU72086A	430131579100s1	3	NWNW	14 9s	16E	POW	UTU096547	EQUITABLE RESOURCES ENERG
UTU72086A	430133061300s1	31-15	NWNE	15 9 S	16E	POW	UTU0 179 85	EQUITABLE RESOURCES ENERG


Page No. 2 01/13/98

WELL STATUS REPORTS UTAH STATE OFFICE

INSPECTION ITEM	API NO.	WELL Number	QTQT	SEC	TWN	RNG	WELL Status	LEASE NAME	OPERATOR
UTU72086A	430133141300s1	31-1J	L2	1	98	16E	POW	UTU33992	EQUITABLE RESOURCES ENERG
UTU72086A	430133119500s1	31-6	L2	6	9s	17E	WIW	UTU020252A	EQUITABLE RESOURCES ENERG
UTU72086A	430133140500s1	31-7J	NWNE	7	9S	17E	WIW	UTU44426	EQUITABLE RESOURCES ENERG
UTU72086A	430133138600\$1	32-11	SWNE	11	98	16E	WIW	UTU096550	EQUITABLE RESOURCES ENERG
UTU72086A	430133141900s1	32-12J	SWNE	12	9s	16E	WIW	UTU035521	EQUITABLE RESOURCES ENERG
UTU72086A	430133136800s1	32-15	SWNE	15	9\$	16E	WIW	UTU017985	EQUITABLE RESOURCES ENERG
UTU72086A	430133141400s1	32-1J	SWNE	1	9s	16E	POW	UTU33992	EQUITABLE RESOURCES ENERG
UTU72086A	430133055900s1	32-6	SWNE	6	9 S	17E	POW	UTU020252A	EQUITABLE RESOURCES ENERG
UTU72086A	430133145100s1	33-11J	NWSE	11	9 \$	16E	120	UTU096550	EQUITABLE RESOURCES ENERG
UTU72086A	430133063200s1	33-15	NWSE	15	9 \$	16E	POW	UTU017985	EQUITABLE RESOURCES ENERG
UTU72086A	4301 3313 6100s1	33-6	NWSE	6	9s	17E	WIW	UTU020252A	EQUITABLE RESOURCES ENERG
UTU72086A	430133141600s1	34-10J	SWSE	10	98	16E	WIW	UTU017985	EQUITABLE RESOURCES ENERG
UTU72086A	430133100300s1	34-11	SWSE	11	9s	16E	WIW	UTU096550	EQUITABLE RESOURCES ENERG
UTU72086A	430133058600s1	34-6	SWSE	6	9 S	17E	POW	UTU020252A	EQUITABLE RESOURCES ENERG
UTU72086A	430133074200s1	4	NESW	12	9s	16E	WIW	UTU035521A	EQUITABLE RESOURCES ENERG
UTU72086A	430131579500s1	4	SENW	11	9s	16E	PO₩	UTU096550	EQUITABLE RESOURCES ENERG
UTU72086A	430133148700s1	41-12J	NENE	12	9s	16E	POW	UTU44426	EQUITABLE RESOURCES ENERG
UTU72086A	430133140800s1	41-14J	NENE	14	9S	16E	WIW	UTU096550	EQUITABLE RESOURCES ENERG
UTU72086A	430133136700s1	41-15	NENE	15	9s	16E	WIW	UTU017985	EQUITABLE RESOURCES ENERG
UTU72086A	430133058100s1	41-6	NENE	6	9s	17E	POW	UTU020252A	EQUITABLE RESOURCES ENERG
UTU72086A	430133006600s1	42-11J	SENE	11	9 S	16E	POW	UTU096550	EQUITABLE RESOURCES ENERG
UTU72086A	430133148600s1	42-12J	SENE	12	9s	16E	POW	UTU035521	EQUITABLE RESOURCES ENERG
UTU72086A	430133063300s1	42-15	SENE	15	9s	16E	POW	UTU017985	EQUITABLE RESOURCES ENERG
UTU72086A	430133140400s1	42-1J	SENE	1	9s	16E	WIW	UTU40652	EQUITABLE RESOURCES ENERG
UTU72086A	430133136400s1	42-6	SENE	6	9s	17E	WIW	UTU020252A	EQUITABLE RESOURCES ENERG
UTU72086A	43013310020081	43-11J	NESE	11	9s	16E	WIW	UTU096550	EQUITABLE RESOURCES ENERG
UTU72086A	430133058300s1	43-6	NESE	6	98	17E	POW	UTU020252A	EQUITABLE RESOURCES ENERG
UTU72086A	430133063000s1	44-10	SESE	10	9s	16E	POW	UTU01 7 985	EQUITABLE RESOURCES ENERG
UTU72086A	430133141500s1	44-1J	SESE	1	9s	16E	WIW	UTU44426	EQUITABLE RESOURCES ENERG
UTU72086A	430133092600s1	7-A	NENE	7	9s	17E	POW	UTU44426	EQUITABLE RESOURCES ENERG
UTU72086A	430133096100s1	7-c	NENW	7	98	17E		UTU44426	EQUITABLE RESOURCES ENERG

JONAH (GREEN RIVER) UNIT DUCHESNE COUNTY, UTAH

EFFECTIVE: JULY 1, 1993



16E

UNIT OUTLINE (UTU72086A)

4,221.61 ACRES

SECONDARY ALLOCATION FEDERAL 100.00%

Dision of Oil, Gas and Mining

OPERATOR CHANGE WORKSHEET

Attach all documentation received by the division regarding this change. Initial each listed item when completed. Write N/A if item is not applicable.

Routing:	1/
1-11 pte	6VACE
2-04-11	7-KAS
3-DIS015	8-SI (
4-VLD	9-FILE
5_ID#	

										المحروب ا	$ \longrightarrow $	
		ange of Opera signation of O	-	old)		ignation of trator Name	-	Only	-	V		
The	ope	erator of the w	vell(s) liste	d below has	changed, e	effective: _	9-30-97	7				
TO:	(ne	ew operator)	TNLAND	PRODUCTION	COMPANY	FROM:	(old one	rator)	FOUTT	ARIE R	ESOURC	ES ENERGY
	((address)	PO BOX			_ ricoivi.	` •	address)	PO BO		<u> </u>	DD DAVIDAGE
		()	ROOSEVE		66	-	•	uuur voo)	LAURE		59044	
						•					TN O&G	SVS
			Phone: (801)722-51	03						6)628-	
				10. N5160						int no.		
WE	LL	(S) attach addition	onal page if n	eeded:		*JONAH	(GREEN	RIVER)	UNIT			
Name		**SEE ATTAC	**(IAH:	ADI: 43-	013-3056	59 Entity:		s T	,	D	Lease:	
Name				API:	<u> </u>	Entity:		s 1	. ———	R	•	
Name	: _			API:		Entity:		s T		R		
Name	_					Entity:		s T s T		R	Lease:	
Name	_					Entity:		S T		R	Lease:	
Name Name				_ API: API:						R	Lease:	
Ivanic				AFI.		Entity:		s T		<u>R</u>	Lease:	
Lec Lec Pla Lec	 2. 3. 4. 	(r649-8-10) form). (Late of BLA changes shother the content of the content of the changes of through 9 by form).	Sundry or Sundry	other legal commerce hompany reginates	document as been co stered with ELLS ON section of	ation has been tacted if the state of the state of this form.	he new of the new of t	operator a o) been con proval of	bove is If yes, stacted re	CW openote on the curs of the control of the contro	erator (A crently o company g this ch ndian v	Attach to this operating any file number: nange. Make well operator
fic fic	5. 6.	Changes hav (1-14-98) Cardex file	ve been ent ¥ ÜIC/04 has been u	ered in the C « Im Pro 1-14 pdated for ea	Dil and Ga 1-18 4 Wa 1-18 well lis	ns Informa 10/08652 / sted above.	tion Syst -14-98	t em (3270)) for ea	ch well	listed a	bove.
Lec	7.	Well file lab	els have b	een updated	for each w	ell listed al	bove.					
	8.	Changes have to Trust Land	e been inclu ds, Soverei	ided on the r gn Lands, U	nonthly "(GS, Tax C	Operator, A Commission	ddress, a n, etc. //	nd Accou	int Chan	ges" m	emo for	distribution
Lec	9.	A folder has reference du	s been set	up for the O	perator (Change file	e, and a ocuments	copy of t	his page	has b	een plac	ed there for

OPERAT	OR CHANGE WORKSHEET (continued) - Initial each item when completed. Write N/A if item is not applicable.
ENTITY	/ REVIEW
yc 1.	(r649-8-7) Entity assignments have been reviewed for all wells listed above. Were entity changes made? (yes(no)) If entity assignments were changed, attach copies of Form 6, Entity Action Form. End: 49-8-7) Entity assignments were changed, attach copies of Form 6, Entity Action Form. End: 49-8-7 If entity assignments were changed, attach copies of Form 6, Entity Action Form. End: 49-8-7 If entity assignments were changed, attach copies of Form 6, Entity Action Form. End: 49-8-7 If entity assignments were changed, attach copies of Form 6, Entity Action Form. End: 49-8-7 If entity assignments were changed, attach copies of Form 6, Entity Action Form. End: 49-8-7 If entity assignments were changed, attach copies of Form 6, Entity Action Form. End: 49-8-7 If entity assignments were changed, attach copies of Form 6, Entity Action Form. End: 49-8-7 If entity assignments were changed, attach copies of Form 6, Entity Action Form. End: 49-8-7 If entity assignments were changed, attach copies of Form 6, Entity Action Form. End: 49-8-7 If entity assignments were changed, attach copies of Form 6, Entity Action Form. End: 49-8-7 If entity assignments were changed, attach copies of Form 6, Entity Action Form. End: 49-8-7 If entity assignments were changed, attach copies of Form 6, Entity Action Form. End: 49-8-7 If entity assignments were changed, attach copies of Form 6, Entity Action Form.
BOND V	PERIFICATION - (FEE WELLS ONLY)
N/A/ 1.	(r649-3-1) The NEW operator of any fee lease well listed above has furnished a proper bond.
2.	A copy of this form has been placed in the new and former operator's bond files.
3.	The FORMER operator has requested a release of liability from their bond (yes/no), as of today's date If yes, division response was made to this request by letter dated
LEASE I	INTEREST OWNER NOTIFICATION OF RESPONSIBILITY
MA 1.	Copies of documents have been sent on to at Trust Lands for changes involving State leases, in order to remind that agency of their responsibility to review for proper bonding.
	(r649-2-10) The former operator of any fee lease wells listed above has been contacted and informed by letter dated19, of their responsibility to notify all interest owners of this change.
FILMIN	G
<u>V</u> 1.	All attachments to this form have been microfilmed . Today's date: 2.3.98
FILING	
1.	Copies of all attachments to this form have been filed in each well file.
2.	The original of this form, and the original attachments are now being filed in the Operator Change file.
COMME	ENTS
980114	Bm /54 aprv. eff. 1-13-98.

FORM 10

STATE OF UTAH

DIVISION OF OIL, GAS AND MINING
1594 West North Temple, Suite 1210, PO Box 145801, Salt Lake City, UT 84114-5801

Page 3 of 14

MONTHLY OIL AND GAS PRODUCTION REPORT

OPERATOR NAME AND ADDRESS:		UTAH ACCOUNT NUMBER:N9890						
C/O CRAZY MTN O&G SVS'S EQUITABLE RESOURCES ENI PO BOX 577 LAUREL MT 59044				ORT PERIOD (MONTH NDED REPORT (1	I/YEAR): 9 / 97 Highlight Changes)			
Well Name	Deadasia		r	, , ,				
API Number Entity Location	Producing	Well	Days		Production Volumes			
WALLEN FEDERAL 23-6	Zone	Status	Орег	OIL(BBL)	GAS(MCF)	WATER(BBL)		
4301330558 11492 09S 17E 6	GRRV			4020252A	Jonah (Ge)Unit			
VALLEN FEDERAL 32-6	unity			000000000000000000000000000000000000000				
4301330559 11492 09S 17E 6	GRRV			11				
ALLEN FEDERAL 41-6								
4301330581 11492 09S 17E 6	GRRV			4				
VALLEN FEDERAL 12-6				11				
4301330582 11492 09S 17E 6	GRRV			•				
ALLEN FEDERAL 43-6		·		ц				
4301330583 11492 095 17E 6	GRRV			'				
ALLEN FEDERAL 21-6				4				
1,301330584 11492 09S 17E 6	GRRV			"				
VALLEN FEDERAL 34-6				h		**************************************		
4301330586 11492 09S 17E 6	GRRV							
#EDERAL 2-1'				U 33992				
4301330603 11492 095 16E 1 ALLEN FEDERAL 12-5	GRRV			U 22/12				
50. # 0 12 0 12 0 12 0 12 0 12 0 12 0 12 0	CDDV	į		402052				
4301330611 11492 095 17E 5 ALLEN FEDERAL 21-5	GRRV			40200				
4301330612 11492 095 17E 5	GRRV			и		-		
CASTLE PK FED 31-15	unnv							
4301330613 11492 095 16E 15	GRRV		Ì	4017985				
CASTLE PK FED 44-10	GART							
4301330630 11492 095 16E 10	GRRV			h 017895				
CASTLE PK FED 24-15								
4301330631 11492 09S 16E 15	GRRV			"	√			
		1	OTALS					
DMMENTS:								

Telephone Number:_

(12/93)

Name and Signature:

hereby certify that this report is true and complete to the best of my knowledge.

FORM 3160-5 (June 1990)


UNITED STATES MENT OF THE INTERIOR

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

	Expires:	March	31,	1993	
7	D'		. 1.0	133	_

BUR _{WA} U OF	LAND MANAGEMENT	Expires: March 31, 1993	
SUNDRY NOTICES AN	5. Lease Designation and Serial No. U-020252-A		
Do not use this form for proposals to drill or to de Use "APPLICATION F	6. If Indian, Allottee or Tribe Name NA		
SUBMIT IN	I TRIPLICATE	7. If Unit or CA, Agreement Designation JONAH	
X Oil Gas Well Other		8. Well Name and No. ALLEN FEDERAL 32-6 9. API Well No. 43-013-30559	
2. Name of Operator INLAND PRODUCTION COMPANY 3. Address and Telephone No.	10. Field and Pool, or Exploratory Area MONUMENT BUTTE		
475 17TH STREET, SUITE 1500, DENVE 4. Location of Well (Footage, Sec., T., R., m., or Survey Description) 2102 FNL 1949 FEL SW/NE Section	on 6, T09S R17E	DUCHESNE COUNTY, UTAH	
12. CHECK APPROPRIATE BOX(S TYPE OF SUBMISSION) TO INDICATE NATURE OF NOTICE, REPO		
I TPE OF SUBMISSION	ITPE OF	ACTION	
Notice of Intent X Subsequent Report Final Abandonment Notice	Abandonment Recompletion Plugging Back Casing Repair Altering Casing X Other Site Security	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	
13. Describe Proposed or Completed Operations (Clearly state all pertinent deta ally drilled, give subsurface locations and measured and true vertical dep		sed work. If well is direction-	


Attached please find the site security diagram for the above referenced well.



Signed Si	Title	Manager, Regulatory Compliance	Date	10/28/98
(This space for Federal or State office use)				
Approved by	Title		Date	

Inland Production Company Site Facility Diagram

Allen Federal 32-6 SW/NE Sec. 6, T9S, 17E Duchesne County Sept. 17, 1998



Site Security Plan is held at the Roosevelt Office. Roosevelt Utah

Production Phase:

- 1) Valves 1, and 3 sealed closed
- 2) Valves 2 and 4 sealed open

Sales Phase:

- 1) Valves 2, 3, and 4 sealed closed
- 2) Valves 1 open

Draining Phase:

1) Valve 3 open

Pumping Unit

Well Head



Emulsion Line	
Load Line	
Water Line	
Gas Sales	

Corporations Section P.O.Box 13697 Austin, Texas 78711-3697





Office of the Secretary of State

The undersigned, as Secretary of State of Texas, does hereby certify that the attached is a true and correct copy of each document on file in this office as described below:

Newfield Production Company Filing Number: 41530400

Articles of Amendment

September 02, 2004

In testimony whereof, I have hereunto signed my name officially and caused to be impressed hereon the Seal of State at my office in Austin, Texas on September 10, 2004





Secretary of State

ARTICLES OF AMENDMENT TO THE ARTICLES OF INCORPORATION OF INLAND PRODUCTION COMPANY

In the Office of the Secretary of State of Texas

SEP 02 2004

Corporations Section

Pursuant to the provisions of Article 4.04 of the Texas Business Corporation Act (the "TBCA"), the undersigned corporation adopts the following articles of amendment to the articles of incorporation:

ARTICLE 1 - Name

The name of the corporation is Inland Production Company.

ARTICLE 2 - Amended Name

The following amendment to the Articles of Incorporation was approved by the Board of Directors and adopted by the shareholders of the corporation on August 27, 2004.

The amendment alters or changes Article One of the Articles of Incorporation to change the name of the corporation so that, as amended, Article One shall read in its entirety as follows:

"ARTICLE ONE - The name of the corporation is Newfield Production Company."

ARTICLE 3 - Effective Date of Filing

This document will become effective upon filing.

The holder of all of the shares outstanding and entitled to vote on said amendment has signed a consent in writing pursuant to Article 9.10 of the TBCA, adopting said amendment, and any written notice required has been given.

IN WITNESS WHEREOF, the undersigned corporation has executed these Articles of Amendment as of the 1st day of September, 2004.

INLAND RESOURCES INC.

Susan G. Riggs, Treasurer

			•		
UTSL-	15855	61052	73088	76561	
071572A	16535	62848	73089	76787	
065914	16539	63073B	73520A	76808	
.*	16544	63073D	74108	76813	
	17036	63073E	74805	76954	63073X
	17424	63073O	74806	76956	63098A
	18048	64917	74807	77233	68528A
UTU-	18399	64379	74808	77234	72086A
	19267	64380	74389	77235	72613A
02458	26026A	64381	74390	77337	73520X
03563	30096	64805	74391	77338	74477X
03563A	30103	64806	74392	77339	75023X
04493	31260	64917	74393	77357	76189X
05843	33992	65207	74398	77359	76331X
07978	34173	65210	74399	77365	76788X
09803	34346	65635	74400	77369	77098X
017439B	36442	65967	74404	77370	77107X
017985	36846	65969	74405	77546	77236X
017991	38411	65970	74406	77553·	77376X
017992	38428	66184	74411	77554	78560X
018073	38429	66185	74805	78022	79485X
019222	38431	66191	74806	79013 ⁻	79641X
020252	39713	67168	74826	79014	80207X
020252A	39714	67170	74827	79015	81307X
020254	40026	67208	74835	79016	,
020255	40652	67549	74868	79017	
020309D	40894	67586	74869	79831	
022684A	41377	67845	74870	79832	
027345	44210	68105	74872	79833 [,]	
034217A	44426	68548	74970	79831	
035521	44430	68618	75036	79834	
035521A	45431	69060	75037	80450	
038797	47171	69061	75038	80915	
058149	49092	69744	75039	81000	
063597A	49430	70821	75075	01000	
075174	49950	72103	75078		
096547	50376	72104	75089		
096550	50385	72105	75090		
	50376	72106	75234		
	50750	72107	75238		
10760	51081	72108	76239	•	
11385	52013	73086	76240		
13905	52018	73087	76241		
15392	58546	73807	76560		
			, 00 00		



United States Department of the Interior



BUREAU OF LAND MANAGEMENT Utah State Office P.O. Box 45155 Salt Lake City, UT 84145-0155 http://www.blm.gov

IN REPLY REFER TO: 3106 (UT-924)

September 16, 2004

Memorandum

To:

Vernal Field Office

From:

Acting Chief, Branch of Fluid Minerals

Subject:

Merger Approval

Attached is an approved copy of the name change recognized by the Utah State Office. We have updated our records to reflect the merger from Inland Production Company into Newfield Production Company on September 2, 2004.

Michael Coulthard

Acting Chief, Branch of Fluid Minerals

Enclosure

1. State of Texas Certificate of Registration

cc:

MMS, Reference Data Branch, James Sykes, PO Box 25165, Denver CO 80225 State of Utah, DOGM, Attn: Earlene Russell, PO Box 145801, SLC UT 84114

Teresa Thompson Joe Incardine Connie Seare

OPERATOR CHANGE WORKSHEET

ROUTING 1. GLH

2. CDW 3. FILE

Change of Operator (Well Sold)

Designation of Agent/Operator

X Operator Name Change

Merger

The operator of the well(s) listed below has changed, effective:						9/1/2004			٦
FROM: (Old Operator):			TO: (New O	perator):		i		1	
N5160-Inland Production Company				N2695-Newfield Production Company				ľ	
Route 3 Box 3630				Route 3 Box 3630				ŀ	
Myton, UT 84052				Myton,	UT 84052				ı
Phone: 1-(435) 646-3721				Phone: 1-(435)	646-3721				╛
CA No.			Unit:		ONAH (G	REEN RI	VER)	bracket	
WELL(S)									╛
NAME	SEC	TWN	RNG	API NO	ENTITY		WELL	WELL	١
					NO	TYPE	TYPE	STATUS	4
FEDERAL 2-1	01			4301330603		Federal	OW	Р	_
GOATES FED 1	11			4301315789		Federal	ow	P	_
MONUMENT FED 13-11J	11			4301315790		Federal	OW	S	
WALTON FED 1	11	090S	160E	4301315792	11492	Federal	OW	P	
WALTON FED 4	11	090S	160E	4301315795	11492	Federal	ow	P	╝
MONUMENT FED 42-11J	11	090S	160E	4301330066	11492	Federal	ow	P	
C&O GOVT 1	12	090S	160E	4301315111	11492	Federal	OW	P	
C&O GOVT 2	12	090S	160E	4301315112	11492	Federal	OW	P	٦
MONUMENT FED 22-12J	12	090S	160E	4301315796	11492	Federal	ow	P	٦
GOATES FED 3	14	090S	160E	4301315791	11492	Federal	OW	P	٦
WALTON FED 2	14	090S	160E	4301315793	11492	Federal	ow	P	٦
ALLEN FED A-1	05	090S	170E	4301315780	11492	Federal	WI	A	7
ALLEN FED 1-6	06	090S	170E	4301315779	11492	Federal	WI	A	٦
ALLEN FED 23-6	06	090S	170E	4301330558	11492	Federal	ow	P	٦
ALLEN FED 32-6	06	090S	170E	4301330559	11492	Federal	ow	P	٦
ALLEN FED 41-6	06	090S	170E	4301330581	11492	Federal	ow	P	٦
ALLEN FED 12-6	06	090S	170E	4301330582	11492	Federal	ow	P	٦
ALLEN FED 43-6	06	090S	170E	4301330583	11492	Federal	ow	P	٦
ALLEN FED 21-6	06	090S	170E	4301330584	11492	Federal	ow	P	٦
ALLEN FED 34-6	06	090S	170E	4301330586	11492	Federal	ow	P	
									╝

OPERATOR CHANGES DOCUMENTATION

Enter date after each listed item is completed

(R649-8-10) Sundry or legal documentation was received from the FORMER operator on: 9/15/2004
 (R649-8-10) Sundry or legal documentation was received from the NEW operator on: 9/15/2004

3. The new company was checked on the Department of Commerce, Division of Corporations Database on: 2/23/2005

4. Is the new operator registered in the State of Utah:

YES Business Number:

5. If **NO**, the operator was contacted contacted on:

755627-0143

6a. (R649-9-2)Waste Management Plan has been received on:	IN PLACE
6b. Inspections of LA PA state/fee well sites complete on:	waived
7. Federal and Indian Lease Wells: The BLM and or	r the BIA has approved the merger, name change.
or operator change for all wells listed on Federal or Indian le	
or operator change for an wear more of the control	
8. Federal and Indian Units:	
The BLM or BIA has approved the successor of unit opera	ator for wells listed on: <u>n/a</u>
9. Federal and Indian Communization Agreemen	nts ("CA"):
The BLM or BIA has approved the operator for all wells l	
10 II I Control (BIICI) T	he Division has approved UIC Form 5, Transfer of Authority to
10. Underground Injection Control ("UIC") Inject, for the enhanced/secondary recovery unit/project for	
inject, for the enhanced secondary recovery uniterroject for	the water disposal went(s) listed on.
DATA ENTRY:	2/29/2005
1. Changes entered in the Oil and Gas Database on:	2/28/2005
2. Changes have been entered on the Monthly Operator Cha	nge Spread Sheet on: 2/28/2005
3. Bond information entered in RBDMS on:	2/28/2005
4. Fee/State wells attached to bond in RBDMS on:	2/28/2005
5. Injection Projects to new operator in RBDMS on:	2/28/2005
6. Receipt of Acceptance of Drilling Procedures for APD/New	v on: waived
FEDERAL WELL(S) BOND VERIFICATION:	
Federal well(s) covered by Bond Number:	UT 0056
INDIAN WELL(S) BOND VERIFICATION:	61BSBDH2912
1. Indian well(s) covered by Bond Number:	01D3DD112312
FEE & STATE WELL(S) BOND VERIFICATIO	N:
1. (R649-3-1) The NEW operator of any fee well(s) listed cov	vered by Bond Number 61BSBDH2919
2. The FORMER operator has requested a release of liability f The Division sent response by letter on:	from their bond on:n/a* n/a
The Division sent response by letter on.	19 d
LEASE INTEREST OWNER NOTIFICATION:	
3. (R649-2-10) The FORMER operator of the fee wells has be	
of their responsibility to notify all interest owners of this cha	ange on: n/a
COMMENTS:	
*Bond rider changed operator name from Inland Production Co.	mpany to Newfield Production Company - received 2/23/05



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY REGION 8

1595 Wynkoop Street DENVER, CO 80202-1129 Phone 800-227-8917 http://www.epa.gov/region08

DEC 2 4 2008

Ref: 8P-W-GW
CERTIFIED MAIL
RETURN RECEIPT REQUESTED

Mr. Eric Sundberg Regulatory Analyst Newfield Production Company 1001 Seventeenth Street – Suite 2000 Denver, CO 80202 Accepted by the Utah Division of Oil, Gas and Mining FOR RECORD ONLY

RE: Additional Well: Jonah Unit Permit

UIC Permit No. UT20642-00000

Well ID: UT20642-08173

Allen Federal 32-6-9-17
2102' FNL & 1949' FEL
NW NE Section 6-T9S-R17E
Duchesne County, Utah
API # 43-013-30559

Corrective Action Required on 2 AOR Wells

Dear Mr. Sundberg:

The Newfield Production Company request to convert the former Green River Formation oil well Allen Federal 32-6-9-17 to an enhanced recovery injection well in the Jonah Unit Area Permit is hereby authorized by the Environmental Protection Agency (EPA) under the terms and conditions described in the Authorization For Additional Well.

The addition of the proposed injection well within the exterior boundary of the Uintah & Ouray Indian Reservation is being made under the authority of 40 CFR §144.33 (c), terms of the Jonah Unit Area Permit No. UT20642-00000, and subsequent modifications.

Please be aware that Newfield does not have authorization to begin injection operations until all <u>Prior to Commencing Injection</u> requirements have been submitted and evaluated by the EPA and written authorization to begin injection is given by the Director. Please note that the Permit limits injection to the gross interval within the Green River Formation between the depth of 3742 feet and the top of the Wasatch Formation estimated to be at 6105 feet.



Prior to receiving authorization to inject, the EPA requires that Newfield submit for review and approval: (1) a complete EPA Form No. 7520-12 (Well Rework Record) with a new schematic diagram, (2) a pore pressure calculation of the injection interval, and (3) the results of a Part I (Internal) Mechanical Integrity Test (MIT).

The initial Maximum Allowable Injection Pressure (MAIP) for the Allen Federal 32-6-9-17 is 1700 psig. UIC Area Permit UT20642-00000 allows the permittee to request a change in the MAIP based upon results of a step rate test which demonstrates that the formation breakdown pressure will not be exceeded.

The Injection interval for Allen Federal 32-6-9-17 has been modified from the Jonah Unit Area Permit (U120642-00000) due to the absence of cement through the established areal Confining Zone. Add that shale intervals with cement behind casing have been identified and injection in the Allen Federal 32-6-9-17 well is limited to below these shale intervals.

If you have any questions, please call Jason Deardorff at (303) 312-6583 or 1-(800)-227-8917 (Ext. 312-6583). Please submit the required data to Margo Smith at the letterhead address citing mail code 8P-W-GW.

Sincerely,

Eddie A. Sierra

Acting Assistant Regional Administrator Office of Partnerships and Regulatory Assistance

Encl: Authorization For Conversion of An Additional Well EPA Form No. 7520-12 (Well Rework Record)

Proposed Wellbore and P&A Wellbore Schematics for Allen Federal 32-6-9-17

cc: Letter Only

Uintah & Ouray Business Committee: Curtis Cesspooch, Chairman Ronald Groves, Councilman Irene Cuch, Vice-Chairwoman Steven Cesspooch, Councilman

Phillip Chimburas, Councilman

Frances Poowegup, Councilwoman

Daniel Picard BIA - Uintah & Ouray Indian Agency

All Enclosures:

Michelle Sabori Acting Director Land Use Department Ute Indian Tribe

Larry Love Director of Energy & Minerals Dept. Ute Indian Tribe

Elaine Willie GAP Coordinator Ute Indian Tribe

Gil Hunt Associate Director Utah Division of Oil, Gas, and Mining

Fluid Minerals Engineering Office BLM - Vernal Office

Michael Guinn District Manager Newfield Production Company Myton, Utah



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

REGION 8 1595 WYNKOOP STREET DENVER, CO 80202-1129 Phone 800-227-8917 http://www.epa.gov/region08

<u>AUTHORIZATION FOR ADDITIONAL WELL</u>

UIC Area Permit No: UT20642-00000

The Jonah Unit Final UIC Area Permit No.UT20642-00000, effective December 22, 1992, authorizes injection for the purpose of enhanced oil recovery in the Monument Butte Field. On July 21, 2008, Newfield Production Company notified the Director concerning the following additional enhanced recovery injection well:

Well Name:

EPA Well ID Number:

Location:

Allen Federal 32-6-9-17

UT 20642-08173

2102' FNL & 1949' FEL SW NE Sec. 6 T9S-R17E Duchesne County, Utah API #43-013-30559

Pursuant to 40 CFR §144.33, Area UIC Permit No. UT20642-00000 authorizes the permittee to construct and operate, convert, or plug and abandon additional enhanced recovery injection wells within the area permit. This well was determined to satisfy additional well criteria required by the permit.

This well is subject to all provisions of UIC Area Permit No. UT20633-00000, as modified and as specified in the Injection Well-Specific Requirements detailed below. This Authorization shall expire one year after the Effective Date unless the permittee has converted the well to injection or submits a written request to extend this Authorization prior to the expiration date.

This Authorization is effective upon signature.

DEC 2 4 2008 Date:

Eddie A. Sierra

*Acting Assistant Regional Administrator Office of Partnerships and Regulatory Assistance

^{*} The person holding this title is referred to as the Director throughout the permit and Authorization

INJECTION WELL-SPECIFIC REQUIREMENTS

Well Name: Allen Federal 32-6-9-17 EPA Well ID Number: UT20642-08173

<u>Prior to Commencing Injection Operations, the permittee shall submit the following information:</u>

- 1. Completed Well Rework Record (EPA Form No. 7520-12) and schematic diagram.
- 2. Pore pressure calculation of the proposed injection zone;
- 3. A successful Part I (internal) Mechanical Integrity test (MIT)

Once these records are received and approved by EPA, the Director will provide written authorization to inject for a limited period of 180 days, during which time a Radioactive Tracer Survey (RTS) is required to demonstrate no significant upward migration of injection fluids behind the casing from the injection zone. It is intended that a maximum of 180 days of injection will allow the injection zone to adequately pressurize prior to executing the RTS.

<u>Approved Injection Zone:</u> Due to the absence of cement through the previously established areal confining zone [3546 feet to 3748 feet (KB)], injection in this well is limited to an interval from the base of a shale zone (Shale "B") at 4056 feet (KB) to the top of the Wasatch Formation, which is estimated to be at a depth of 6105 feet (KB). The approved injection interval for this well is from 4056 feet to 6105 feet (KB).

<u>Maximum Allowable Injection Pressure (MAIP)</u>: The initial MAIP is <u>1700 psig</u>, based on the following calculation:

MAIP = [FG - (0.433)(SG)] * D, where FG = 0.84 psi/feet SG = 1.015 $D = \underline{4246 \text{ feet}}$ (top perforation depth KB) MAIP = $\underline{1700 \text{ psig}}$

UIC Area Permit No. UT20642-00000 provides the opportunity for the permittee to request a change of the MAIP based upon the submitted results of a Step Rate Test that demonstrates the formation breakdown pressure will not be exceeded.

Well Construction: Casing and Cementing: The well was constructed in compliance with existing regulatory controls for casing and cementing pursuant to 40 CFR §146.22(c). However, cementing records, including the cement bond log (CBL), have demonstrated the absence of cement through the established areal confining zone to prevent the migration of injection fluids behind the casing from the established injection zone. Instead of requiring the emplacement of cement behind casing through this shale interval, Newfield has agreed to limit the injection interval for the Allen Federal 32-6-9-17 well.

Well Construction: Tubing and Packer: 2-7/8" or similar size injection tubing is approved; the packer shall be set at a depth no more than 50 feet above the top perforation.

Demonstration of Mechanical Integrity:

- (1) A successful demonstration of Part I (Internal) Mechanical Integrity using a Casing-Tubing Annulus Pressure Test is required prior to injection, and no less than every five years after the last successful test.
- (2) Because cementing records have not satisfactorily demonstrated the presence of adequate cement to prevent migration of injection fluids behind the casing from the injection zone [4056 feet to 6105 feet (KB)], a RTS is required to confirm the presence of adequate cement. If the RTS is not run, or if the RTS does not confirm adequate cement, the permittee shall demonstrate Part II (External) Mechanical Integrity pursuant to 40 CFR §146.8(a)(2) using an approved test method such as temperature log, noise log or oxygen activation log, and the demonstration of Part II Mechanical Integrity shall be repeated no less than every five years after the last successful test.

<u>Demonstration of Financial Responsibility:</u> The applicant has demonstrated financial responsibility by a Financial Statement in the amount of \$59,344 that has been approved by the EPA. The Director may revise the amount required, and may require the permittee to obtain and provide updated estimates of costs for plugging the well according to the approved Plugging and Abandonment plan.

Plugging and Abandonment: The well shall be plugged in a manner that isolates the injection zone and prevents movement of fluids into or between USDWs. Tubing, packers, and any downhole apparatus shall be removed. Class A, C, G, and H cements, with additives such as accelerators and retarders that control or enhance cement properties, may be used for plugs; however, volume extending additives and gel cements are not approved for plug use. Plug placement shall be verified by tagging. Plugging gel of at least 9.2 lb/gal shall be placed between all plugs. A minimum 50 ft. surface plug shall be set inside and outside of the surface casing to seal pathways for fluid migration into the subsurface. Within sixty (60) days after plugging the owner or operator shall submit Plugging Record (EPA Form 7520-13) to the Director. The Plugging Record must be certified as accurate and complete by the person responsible for the plugging operation. At a minimum, the following plugs are required:

- PLUG NO. 1: Set a cast iron bridge plug (CIBP) no more than 50 ft above the top perforation with a minimum of 20 ft cement plug on top of the CIBP.
- PLUG NO. 2: Perforate and squeeze cement up the backside of the 5-1/2" casing across the Trona Zone and the Mahogany Bench from approximately 2906 ft to 3050 ft (KB) unless pre-existing backside cement precludes cement-squeezing this interval. Set a minimum 144-foot balanced cement plug inside the 5-1/2" casing from approximately 2906 to 3050 ft (KB).
- PLUG NO. 3: Perforate and squeeze cement up the backside of the 5-1/2" casing across the contact between the Uinta Formation and Green River Formation at 1411 ft (KB) unless pre-existing backside cement precludes cement-squeezing this interval. Set a minimum 100-foot plug inside the 5-1/2" casing from approximately 1361-1461 ft (KB).

PLUG NO. 4: Set a Class "G" cement plug within the 5-1/2" casing to 585 ft. and up the 5-1/2" x 8-5/8" casing annulus to the surface.

Cut off surface and 5-1/2" casing at least 4 ft below ground level and set P&A marker; submit Sundry Notices and all necessary data as required by the EPA and other regulatory agencies.

INJECTION WELL-SPECIFIC CONSIDERATIONS

Well Name: Allen Federal 32-6-9-17
EPA Well ID Number: UT20642-08173

<u>Underground Sources of Drinking Water (USDWs)</u>: USDWs in the Jonah Unit Area Permit generally occur within the Uinta Formation. According to "Base of Moderately Saline Ground Water in the Uinta Basin, Utah, State of Utah Technical Publication No. 92," the base of moderately saline ground water may be found at approximately 535 ft below ground surface in the Allen Federal 32-6-9-17 well.

http:NRWRT1.NR.STATE.UT.US:

There are no reservoirs, streams, domestic or agricultural water wells within a quarter (1/4) mile of the well.

Composition of Source, Formation, and Injectate Water: (Total Dissolved Solids [TDS]:

- TDS of the Douglas Creek Member of the Green River Formation Water: 17,931 mg/l.
- TDS of Jonah Facility Injection System source water: 4,278 mg/l.

The **injectate** is water from the Jonah Facility Injection System blended with produced Green River Formation Water resulting in TDS < 10,000 mg/l.

<u>Aquifer Exemption</u> is not required because the TDS of water produced from the proposed injection well is greater than 10,000 mg/l.

<u>Confining Zone(s)</u>: The established areal Confining Zone directly overlies the Garden Gulch Member of the Green River Formation and is found between 3546 ft and 3742 ft (KB) in the Allen Federal 32-6-9-17 well. However, the cement record shows no cement behind casing through this interval. To avoid the risks associated with cement-squeezing, two additional AOR-wide confining zones that have cement behind casing in the Allen Federal 32-6-9-17 well have been identified as follows:

Shale "A": 3858 feet to 3942 feet (KB) – cement inadequate according to CBL analysis Shale "B": 3972 feet to 4056 feet (KB) – cement adequate according to CBL analysis

<u>Injection Zone</u>: The Injection Zone at this well location, which has been modified from the *Authorization for Additional Well*: UIC Area Permit UT20642-00000 *Well*: Allen Federal 32-6-9-17 *EPA Well ID*: UT20642-08173

Jonah Unit Area Permit, is approximately 2,049 ft of multiple lenticular sand units interbedded with shale, marIstone and limestone from the base of Shale "B" at 4056 feet (KB) to the top of the Wasatch Formation which is estimated to be at 6105 ft (KB). The Wasatch Formation top is based on correlation to the Newfield Production Federal #1-26-8-17 (UT20702-04671) Type Log.

Well Construction: The CBL shows no cement through the established areal Confining Zone [3546 ft to 3748 ft (KB)]. However, cement is present immediately beneath this interval and continues through the Shale "A" and Shale "B" intervals with Shale "B" showing more than 18 feet of continuous 80 percent or greater cement bond index. Due to the absence of cement through the established areal Confining Zone, further demonstration that well cement is adequate to prevent significant migration of injection fluids behind casing is required.

Surface Casing: 8-5/8" casing is set at 260 ft (KB) in a 12-1/4" hole, using 190 sacks Class G cement, cemented to the surface.

Longstring Casing: 5-1/2" casing is set at 5401 ft (KB) in a 7-7/8" hole secured with 695 sacks of

cement. Total driller depth 5401 ft. Plugged back total depth is 5365 ft. EPA

calculates top of cement at 896 ft. Estimated CBL top of cement is 2550 ft.

<u>Perforations</u>: Top perforation: <u>4246 ft</u> (KB) Bottom perforation: <u>5232 ft</u> (KB)

AREA OF REVIEW (AOR) WELL REQUIREMENTS

The following eight wells that penetrate the confining zone within or proximate to a 1/4 mile radius around the Allen Federal 32-6-9-17 were evaluated to determine if any corrective action is necessary to prevent fluid movement into USDWs.

Well: Jonah Federal H-6-9-17	API: 43-013-33494	SWNE Sec. 6-T9S-R17E
Well: Jonah Federal I-6-9-17	API: 43-013-33495	NENE Sec. 6-T9S-R17E
Well: Jonah Federal J-6-9-17	API: 43-013-33496	SENE Sec. 6-T9S-R17E
Well: Jonah Federal L-6-9-17	API: 43-013-33498	NWSW Sec. 6-T9S-R17E
Well: Jonah Federal M-6-9-17	API: 43-013-33499	NESW Sec. 6-T9S-R17E
Well: Allen Federal 22-6-6-17	API: 43-013-30919	SENW Sec. 9-T9S-R17E
Well: Monument Federal 33-6-9-17	API: 43-013-31361	NWSE Sec. 6-T9S-R17E
Well: Monument Federal 42-6-9-17	API: 43-013-31364	SENE Sec. 6-T9S-R17E

Corrective Action Required on One AOR Well:

Well: Monument Federal 42-6-9-17 API: 43-013-31364 SENE Sec. 6-T9S-R17E Submitted CBL does not include the confining zone, thus preventing a determination of wellbore mechanical integrity. Newfield has the option of following the corrective action plan detailed below for this well or running and submitting a complete CBL to demonstrate that well construction is adequate. If the CBL does not show an adequate section of 80 percent cement bond index through the confining zone, corrective action will be required. TOC 990 ft

AOR Well Corrective Action Plan: The Monument Federal 42-6-9-17 well shall be monitored weekly at the surface for evidence of fluid movement out of the injection zone. In addition, Newfield developed a corrective action monitoring program, effective July 10, 2008, entitled "Procedure related to proposed Class II Enhanced Oil Recovery Injection Wells determined by the EPA to have specific Area of Review (AOR) wells with inadequate cement across the Confining Zone" and the permittee is referred to this document.

If possible fluid movement out of the Injection Zone is identified, either through the weekly monitoring, through Newfield's July 10, 2008 procedure described above, or through any other means, (for example, evidence of fluid flow or increased bradenhead annulus pressure readings, the Permittee will shut in the Allen Federal 32-6-9-17 well immediately and notify the Director. No injection into the Allen Federal 32-6-9-17 well will be permitted until the Permittee has notified the Director that the situation has been resolved, submitted Reword Records (EPA Form No.7520-12) and a schematic diagram, and received authorization from the Director to recommence injection.

Corrective Action Not Required on Seven AOR wells:

Well: Jonah Federal H-6-9-17 API: 43-013-33494 SWNE Sec. 6-T9S-R17E Shows 222 ft of 80 percent cement bond or greater from 3672-3894 ft.

Well: Jonah Federal J-6-9-17 API: 43-013-33496 SENE Sec. 6 -T9S-R17E Shows 86 ft of 80 percent cement bond or greater from 3630-3830 ft.

Well: Jonah Federal L-6-9-17 API: 43-013-33498 NWSW Sec. 6-T9S-R17E Shows 98 ft of 80 percent cement bond or greater from 3624-3722 ft.

Well: Jonah Federal M-6-9-17 API: 43-013-33499 NESW Sec. 6-T9S-R17E Shows 26 ft of 80 percent cement bond index or greater from 3745-3771 ft.

Well: Jonah Federal I-6-9-17 API: 43-013-33495 NENE Sec. 6-T9S-R17E Shows marginal cement through the established areal Confining zone, but 80 percent cement bond or greater through Shales "A" and "B"

Well: Allen Federal 22-6-6-17 API: 43-013-30919 SENW Sec. 9-T9S-R17E This is a previously permitted injection well (UT20642-03729). Submitted CBL shows marginal cement bond index throughout the confining zone. Any corrective action required for this well will be handled through the existing permit for Allen Federal 22-6-9-17.

Well: Monument Federal 33-6-9-17 API: 43-013-31361 NWSE Sec. 6-T9S-R17E This is a previously permitted injection well (UT20642-03736). Submitted CBL does not include the confining zone. Any corrective action required for this well will be handled through the existing permit for Monument Federal 33-6-9-17.

Reporting of Noncompliance:

- (a) <u>Anticipated Noncompliance</u>. The operator shall give advance notice to the Director of any planned changes in the permitted facility or activity which may result in noncompliance with permit requirements.
- (b) <u>Compliance Schedules</u>. Reports of compliance or noncompliance with, or any progress on, interim and final requirements contained in any compliance schedule of this Permit shall be submitted no later than thirty (30) days following each schedule date.
- (c) Written Notice of any noncompliance which may endanger health or the environment shall be reported to the Director within five (5) days of the time the operator becomes aware of the noncompliance. The written notice shall contain a description of the noncompliance and its cause; the period of noncompliance including dates and times; if the noncompliance has not been corrected the anticipated time it is expected to continue; and steps taken or planned to prevent or reduce recurrence of the noncompliance.

Twenty-Four Hour Noncompliance Reporting: The operator shall report to the Director any noncompliance which may endanger health or environment. Information shall be provided, either orally or by leaving a message, within twenty-four (24) hours from the time the operator becomes aware of the circumstances by telephoning 1-(800)-227-8917 and asking for the EPA Region 8 UIC Program Compliance and Enforcement Director, or by contacting the Region 8 Emergency Operations Center at

(303)-293-1788, if calling from outside EPA Region 8. The following information shall be included in the verbal report:

- (a) Any monitoring or other information which indicates that any contaminant may cause an endangerment to a USDW.
- (b) Any noncompliance with a Permit condition or malfunction of the injection system which may cause fluid migration into or between underground sources of drinking water.

Oil Spill and Chemical Release Reporting: The operator shall comply with all other reporting requirements related to oil spills and chemical releases or other potential impacts to human health or the environment by contacting the National Response Center (NRC) 1-(800)-424-8802 or 1-(202)-267-2675, or through the NRC website at http://www.nrc.uscg.mil/index.htm

<u>Other Noncompliance</u>: The operator shall report all other instances of noncompliance not otherwise reported at the time monitoring reports are submitted.

Other Information: Where the operator becomes aware that he failed to submit any relevant facts in the Permit application, or submitted incorrect information in a Permit application, or in any report to the Director, the operator shall submit such correct facts or information within two (2) weeks of the time such information became known to him.

OMB No. 2040-0042

Approval Expires 4/30/07

O EDA		Environmental Washington, DC	Protection Agence 20460	;y			
WELL REWORK RECORD							
Name and Address of Permittee Name and Address of Contractor							
			- -		alization		
Security of the security of th	State	- Same	County		Permit Number		
Locate Well and Outline Unit on Section Plat - 640 Acres				***************************************			
	Surface	Location Descr	iption	-			
N The state of the	1	4 of 1/4 of	1/4 of 1	I/4 of Section	Township Range		
					ection and drilling unit		
			tions nom near	est lines of quarter s	oction and arming and		
│	Surface	gentranskraving	(C) Line of	quarter section			
	and	ft. from (E/W)		rter section.			
	Zavana	ACTIVITY	γ	pth Before Rework	TYPE OF PERMIT		
W E	guong	rine Disposal		and a construction of the state	Individual		
├ ─ ┼─┞ ─ ┼─┠ ┵━┞─┼─┃	parame.	nhanced Recove	Total Dep	oth After Rework	Area		
	1 1	ydrocarbon Stor	1		Number of Wells		
	toward.			vork Commenced	7		
▎ ▕ ┌┽─├ ╸ ┽╼┠╌┽╼╎	Lease	Name			Well Number		
	- Cultimate	-	Date Rev	vork Completed			
s		And the second s		<u> </u>			
.,	————		EFORE REWORI	K			
Casing Cement Size Depth Sacks	Type	Perform From	To		Acid or Fracture reatment Record		

		į	Santa and the sa				
				and Changes Only)	<u></u>		
Casing Cement		Perfora . From	To		Acid or Fracture Treatment Record		
Size Depth Sacks	Type	· FIOIII					
Professional Contraction of Contract				\$			
Security of the second			***************************************				
An antique of the second of th				į.			
Security and the security of t	management of the second of th						
DESCRIBE REWORK OPERATIONS IN	N DETAIL			WIRE LINE LOGS, LI	ST EACH TYPE		
USE ADDITIONAL SHEETS IF NECES			Log Typ	oes	Logged Intervals		
	· · · · · · · · · · · · · · · · · · ·		***************************************				
Certification I certify under the penalty of law that I have personally examined and am familiar with the information submitted in this document and all attachments and that, based on my inquiry of those individuals immediately responsible for obtaining the information, I believe that the information is true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment. (Ref. 40 CFR 144.32)							
Name and Official Title (Please type or print)	Si	ignature			Date Signed		

PAPERWORK REDUCTION ACT

The public reporting and record keeping burden for this collection of information is estimated to average 4 hours per response annually. Burden means the total time, effort, or financial resource expended by persons to generate, maintain, retain, or disclose or provide information to or for a Federal Agency. This includes the time needed to review instructions; develop, acquire, install, and utilize technology and systems for the purposes of collecting, validating, and verifying information, processing and maintaining information, and disclosing and providing information; adjust the existing ways to comply with any previously applicable instructions and requirements; train personnel to be able to respond to the collection of information; search data sources; complete and review the collection of information; and, transmit or otherwise disclose the information. An agency may not conduct or sponsor, and a person is not required to respond to, a collection of information unless it displays a currently valid OMB control number. Send comments on the Agency's need for this information, the accuracy of the provided burden estimates, and any suggested methods for minimizing respondent burden, including the use of automated collection techniques to Director, Collection Strategies Division, U.S. Environmental Protection Agency (2822), 1200 Pennsylvania Ave., NW., Washington, D.C. 20460. Include the OMB control number in any correspondence. Do not send the completed forms to this address.

Spud Date: 4/23/81

Put on Projection: 5/28/81

GL: 5323' KB: 5337' SURFACE CASING

Allen Federal 32-6-9-17

Wellbore Diagram

Initial Production: 100 STBOPD. 30 MCFD, 16 STBWPD

FRAC JOB

STRING: CSG SIZE:

WEIGHT: LENGTH:

DEPTH LANDED: CEMENT DATA:

8 5/8 K-55 24 lbs 6 jts @ 260' 260'KB 12 1/4"

190 sx Class-H Cemented to surface. 05/17/81 4912'- 5254'

Top Green River

Frac w/Western on 5/17/81. 43,000 gal Apollo 40 w/32,000 lbs 10/20 mesh sd & 55,000 lbs 20/40 mesh sd, avg 34 BPM @ 2400 psig, max @ 2600 psig,ISIP @ 2000 psig, 5 min @ 1832 psig, 10 min @ 1800 psig, 15 min @ 1750 psig.

Frac w/Smith on 10/15/90. 24,086 gal 30 lbs GWX-9 w/46,000 lbs 20/40 mesh sd, & 83,000 lbs 16/30 mesh sd, Avg @ 55 BPM @ 2200 psig, max @ 2950 psig, ISIP @ 2010 psig, 15 min @ 1670 psig. Ramp 1/2 to 6 lbs.

PRODUCTION CASING

STRING:

CSG SIZE: GRADE:

WEIGHT: LENGTH: DEPTH LANDED:

D.V. TOOL: HOLE SIZE:

CEMENT DATA:

CEMENT TOP AT:

J-55 15.5# & 14# 169 jts @ 5389' 5401 1 KB

5 1/2

3342

695 sx 50-50 Poz.

2200' from well records

3546

TUBING RECORD

SIZE/GRADE/WT.: NO. OF JOINTS: TUBING ANCHOR:

2 3/8", J-55, 4.7# 168 jts. @ 5282' None

NO. OF JOINTS: 1 jt. 2 3/8" x 1' 2 3/8" x 4' SEATING NIPPLE: PERF. SUB: MUD ANCHOR: 2 3/8" x 31

TOTAL STRING LENGTH:

5297'KR SN LANDED AT:

5318

SUCKER RODS

POLISHED ROD: 1-1/2" x 16' SM

SUCKER RODS: 1-2', 1-4' x 1/4" pony rods, 98-1/4" guided rods, 96-1/4" slick rods, 15- 34" guided rods, 2- 1 1/2" weight bars.

PUMP SIZE: 2" x 1-1/2" x 16' RHAC pump w/SM plunger

STROKE LENGTH: 64"

PUMP SPEED, SPM: 6 SPM

LOGS: DIGL/SP/GR/CAL

12/20/03 03/23/07

Stuck Pump: Update tubing and rod detail. Pump Change: Updated rod and tubing detail.

2956 - Trona 2982' - Mahogany

Berch (bux 6 3000) coment through established confining

3748 GG

3546

ACID JOB

4246'- 4289' 3990 gal 3% KCl; 75 ball sealers were pumped, 7.5 BPM @ 4300 psig. Healers were pumped, 7.5 BPM @ 4300 psig.

HSIP @ 1630 psig, 15 min @ 1520 psig.

4912'- 5254' 1500 gal 15% HCl Acid, 5 BPM @

1500 psig to 8 BPM @ 1700 psig. Drop balls,

Baw ball action. Pumping @ 8 BPM @ 2000 psig, no ball off. ISIP @ 1600 psig, 5 min @ 1500

PERFORATION RECORD

4283'-4289' 4246! - 4252! 4283' - 4289' (61) 49121- 49341 (221) 2 SPF 5232'- 5254' (22') 2 SPF

4912'-4934'

5232'-5254'

4730

SN @ 5297°

~ 4246'-4252'

EOT @ \$318 Top of Fill @ 5350 PBTD @ 5365

SHOE @ 5364' TD @ 5401'

Basal Carbonale 6 5980 (est) Wasatch @ 6105 (est)

NEWFIELD

Allen Federal #32-6-9-17

2102' FNL & 1949' FEL

SW/NE Section 6-T9S-R17E

Duchesne Co, Utah

API #43-013-30559; Lease #UTU-020252A

TK 5-3-07

CT 7/18/08

Allen Federal 32-6-9-17 Spud Date: 4/23/81 Put on Projection: 5/28/81 Initial Production: 100 STBOPD, Proposed P & A GL: 5323' KB: 5337' 30 MCFD, 16 STBWPD Wellbore Diagram SURFACE CASING STRING: CSG SIZE: Circulate 87 sx Class "G" Cement down 5-1/2" casing and up GRADE: the 5-1/2" x 8-5/8" annulus Aug#4: 12'-585'(KB) WEIGHT: 24 lbs. 6 its @ 260' LENGTH: Casing Shoe @ 260' 260 KB DEPTH LANDED: 12 1/4" HOLE SIZE: 190 sx Class-H CEMENT DATA: Cemented to surface 585 Plugty: Perf casing 250' Was US 200 bose @ 535 and squeeze coment to Plug #3: Minimum of 100' plug across the contact between - 1416 surface to 2 50' below the Base of the winta formation and PRODUCTION CASING - the USDW@ STRING: 535. the Green River Formation at CSG SIZE: GRADE: 15.5# & 14# Plug from 1366 to 1466 169 jts @ 5389' 5401'KB LENGTH: DEPTH LANDED: D.V. TOOL: 7.7/8" HOLE SIZE 695 sx 50-50 Poz. CEMENT DATA: 2200' from well records 17 sx Class G Cement plug on top of CICR Plna # Z: Minimum of 200 Trona/Birds Nest 200' Plug w/0' excess plug from = 50 above 36 sx Class G Cement plug below CICR Trona @ 2907 to 250 Cement top @ 2200 from well records Perforate 2 JSPF @-22001below the base of the Spot inhibited water between cement plugs Mahagany Berch @ 3000 Plug from 2906 to 3050 Plug#1: \$50' above first port. 5' CIBP with 2 Zo' cerent on top. 100' (12 sx) Class G Cement plug on top of CIBP CIBP @ 4196 - 4246`-4252` 4283'-4289' 4912'-4934 5232'-5254' Top of Fill @ 5350 NEWFIELD PBTD @ 5365 TD @ 5401" Allen Federal #32-6-9-17 2102' FNL & 1949' FEL SW/NE Section 6-T9S-R17E Duchesne Co, Utah

API #43-013-30559; Lease #UTU-020252A



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY REGION 8

1595 Wynkoop Street DENVER, CO 80202-1129 Phone 800-227-8917 http://www.epa.gov/region08

MAY 0 4 2010

Ref: 8P-W-GW
CERTIFIED MAIL
RETURN RECEIPT REQUESTED


Mr. Eric Sundberg Regulatory Analyst Newfield Production Company 1001 Seventeenth Street – Suite 2000 Denver, CO 80202 Utah Division of Oil, Gas and Mining

RE: Underground Injection Control (UIC)
Authorization for Additional Well
EPA UIC Permit UT20642-08173
Well: Allen Federal 32-6-9-17
SWNE Sec. 6 T9S-R17E
Duchesne County, Utah
API No.: 43-013-30559

Dear Mr. Sundberg:

The Environmental Protection Agency Region 8 (EPA) received Newfield Production Company's (Newfield) April 16, 2010, letter requesting re-authorization to add the Allen Federal 32-6-9-17 well to the Jonah Area Permit after the original authorization issued by EPA on December 24, 2008, expired. Newfield is hereby authorized to convert the oil well Allen Federal 32-6-9-17 well to an enhanced recovery injection well according to the terms and conditions of the enclosed Authorization for Additional Well. The addition of this injection well, within the exterior boundary of the Uintah & Ouray Indian Reservation, is being made under the authority of 40 CFR §144.33 (c) and terms of the Jonah Area Permit UT20642-00000 and subsequent modifications.

Please be aware that Newfield does not have authorization to begin well injection until all Prior to Commencing Injection requirements are met and written authorization to inject is given by the Director. Prior to receiving authorization to inject, Newfield must submit for review and approval (1) the results of a Part I (internal) Mechanical Integrity test, (2) a pore pressure calculation of the injection interval, and (3) a completed EPA Form No. 7520-12 (Well Rework Record) with a new schematic diagram.



If you have any questions, please call Jason Deardorff at (303) 312-6583 or 1-(800)-227-8917 (Ext. 312-6583). Please submit the required data to Jason Deardorff at the letterhead address citing mail code 8P-W-GW.

Sincerely,

Stephen S. Tuber

Assistant Regional Administrator

Office of Partnerships and Regulatory Assistance

i Victoria (n. 1904) Toleron (n. 1904) A bost per i i in

Enclosures:

Authorization for Additional Well

Wellbore and P&A schematics for Allen Federal 32-6-9-17

cc Letter Only:

Uintah & Ouray Business Committee:

Curtis Cesspooch, Chairman Ronald Groves, Councilman Irene Cuch, Vice-Chairwoman Steven Cesspooch, Councilman Phillip Chimburas, Councilman Frances Poowegup, Councilwoman

Daniel Picard BIA - Uintah & Ouray Indian Agency

cc All Enclosures:

Ferron Secakuku Director, Natural Resources Ute Indian Tribe

Larry Love
Director of Energy & Minerals Dept.
Ute Indian Tribe

Gil Hunt Associate Director Utah Division of Oil, Gas, and Mining Fluid Minerals Engineering Office BLM - Vernal Office

Michael Guinn District Manager Newfield Production Company Myton, Utah



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

REGION 8 1595 WYNKOOP STREET DENVER, CO 80202-1129 Phone 800-227-8917 http://www.epa.gov/region08

AUTHORIZATION FOR ADDITIONAL WELL

UIC Area Permit No: UT20642-00000

The Jonah Unit Final UIC Area Permit No.UT20642-00000, effective December 22, 1992, authorizes injection for the purpose of enhanced oil recovery in the Monument Butte Field. On July 21, 2008, Newfield Production Company notified the Director concerning the following additional enhanced recovery injection well:

Well Name:

EPA Well ID Number:

Location:

Allen Federal 32-6-9-17

UT 20642-08173

2102' FNL & 1949' FEL SWNE Sec. 6 T9S-R17E Duchesne County, Utah API #43-013-30559

Pursuant to 40 CFR §144.33, Area UIC Permit No. UT20642-00000 authorizes the permittee to construct and operate, convert, or plug and abandon additional enhanced recovery injection wells within the area permit. This well was determined to satisfy additional well criteria required by the permit.

This well is subject to all provisions of UIC Area Permit No. UT20642-00000, as modified and as specified in the Injection Well-Specific Requirements detailed below. This Authorization shall expire one year after the Effective Date unless the permittee has converted the well to injection or submits a written request to extend this Authorization prior to the expiration date.

This Authorization is effective upon signature.

MAY 0 4 2010
Date:

Stephen S. Tuber

* Assistant Regional Administrator Office of Partnerships and Regulatory Assistance

^{*} The person holding this title is referred to as the Director throughout the permit and Authorization

INJECTION WELL-SPECIFIC REQUIREMENTS

Well Name: Allen Federal 32-6-9-17 EPA Well ID Number: UT20642-08173

Prior to Commencing Injection Operations, the permittee shall submit the following:

- 1. Completed Well Rework Record (EPA Form No. 7520-12) and schematic diagram.
- 2. Pore pressure calculation of the proposed injection zone;
- 3. A successful Part I (internal) Mechanical Integrity test

Once these records are received and approved by EPA, the Director will provide written authorization to inject for a limited period of 180 days, during which time a Radioactive Tracer Survey (RTS) is required. A successful RTS will be considered a valid confirmation that cementing records show adequate cement to prevent the upward migration of injection fluids from the injection zone at injection pressures up to the MAIP, until one of the following events occurs, at which time a subsequent RTS is required:

- a) If the submitted RTS is determined to be inconclusive or inadequate by EPA,
- b) If the MAIP of the injection well is exceeded for any reason (It is a violation to exceed the MAIP without prior EPA approval),
- c) If new injection perforations are added to the injection well, either through the creation of new perforations or the adjustment of the packer depth to inject into a set of existing perforations that were previously inactive,
- d) If the injection formation is acid-treated, hydraulically stimulated, or stimulated by any other method through the injection well, that may affect the cement integrity of the well,
- e) If the Director requests that a RTS be run for any reason.

A submitted RTS which indicates the movement of fluid behind casing from the injection zone will result in a requirement to demonstrate Part II Mechanical Integrity using an approved Part II demonstration method such as a temperature log, oxygen activation log, or noise log at a frequency no less than once every five years.

All depths cited in this authorization reference the Kelly Bushing datum unless otherwise specified.

Approved Injection Zone: Due to the absence of cement through the previously established administrative confining zone [3,546-3,748 feet (ft.)], injection in this well is limited to an interval from the base of a shale zone at 4,056 ft., to the top of the Wasatch Formation, which is estimated to be at a depth of 6,105 ft. The approved injection interval for this well is from 4,056 to 6,105 ft.

<u>Maximum Allowable Injection Pressure (MAIP)</u>: The initial MAIP is 1,700 psig, based on the following calculation:

```
MAIP = [FG - (0.433)(SG)] * D, where

FG = 0.84 \text{ psi/feet} SG = 1.015 D = 4246 \text{ feet} (top perforation depth)

MAIP = 1700 psig
```

UIC Area Permit No. UT20642-00000 provides the opportunity for the permittee to request a change of the MAIP based upon the submitted results of a step rate test that determines the fracture gradient at the injection depth at this well location.

Well Construction: Casing and Cementing: The well was constructed in compliance with existing regulatory controls for casing and cementing pursuant to 40 CFR §146.22(c). However, cementing records, including the cement bond log (CBL), show the absence of cement through the established administrative confining zone. Instead of a permit requirement to emplace cement behind casing through this shale interval, the top of the injection interval for the Allen Federal 32-6-9-17 well has lowered to the base of a shale interval, Shale "B", through which the CBL does show cement behind the longstring casing.

Well Construction: Tubing and Packer: 2-7/8" or similar size injection tubing is approved; the packer shall be set at a depth no more than 50 feet above the top perforation.

Demonstration of Mechanical Integrity:

- (1) A successful demonstration of Part I (internal) Mechanical Integrity using a Casing-Tubing Annulus Pressure Test is required prior to injection, and no less than once every five years after the last successful test.
- (2) Because cementing records have not satisfactorily demonstrated the presence of adequate cement to prevent migration of injection fluids behind the casing from the injection zone a RTS during the 180-day period of Limited Authorization to Inject is required. This RTS will supplement the cementing records, which show an insufficient interval of 80 percent cement bond index or greater through the confining zone, by demonstrating the presence or absence of adequate cement to prevent fluid movement behind the casing above the uppermost perforation. It is intended that a maximum of 180 days of injection will allow the injection zone to achieve the Maximum Allowable Injection Pressure (MAIP) for the purpose of executing the RTS. If 180 days is not sufficient to achieve the MAIP specified in the permit, an extension of the period of Limited Authorization to Inject may be requested. If the RTS is not run, or if the RTS does not confirm adequate cement, the permittee shall demonstrate Part II (External) Mechanical Integrity pursuant to 40 CFR §146.8(a)(2) using an approved test method such as temperature log, noise log or oxygen activation log, and the demonstration of Part II Mechanical Integrity shall be repeated no less than every five years after the last successful test.

Demonstration of Financial Responsibility: The applicant has demonstrated financial responsibility by a Financial Statement in the amount of \$59,344 that has been approved by the EPA. The Director may revise the amount required, and may require the permittee to obtain and provide updated estimates of costs for plugging the well according to the approved Plugging and Abandonment plan.

Plugging and Abandonment: The well shall be plugged in a manner that isolates the injection zone and prevents movement of fluids into or between USDWs. Tubing, packers, and any downhole apparatus shall be removed. Class A, C, G, and H cements, with additives such as accelerators and retarders that control or enhance cement properties, may be used for plugs; however, volume extending additives and gel cements are not approved for plug use. Plug placement shall be verified by tagging. Plugging gel of at least 9.2 lb/gal shall be placed between all plugs. A minimum 50 ft. surface plug shall be set inside and outside of the surface casing to seal pathways for fluid migration into the subsurface. Within sixty (60) days after plugging the owner or operator shall submit Plugging Record (EPA Form 7520-13) to the Director. The Plugging Record must be certified as accurate and complete by the person responsible for the plugging operation. At a minimum, the following plugs are required:

- PLUG 1: Set a cast iron bridge plug (CIBP) no more than 50 ft above the top perforation with a minimum 20-foot cement plug on top of the CIBP.
- PLUG 2: Perforate and squeeze cement up the backside of the 5-1/2" casing across the Trona Zone and the Mahogany Bench from approximately 2,906 to 3,050 ft. unless pre-existing backside cement precludes cement-squeezing this interval. Set a minimum 144-foot balanced cement plug inside the 5-1/2" casing from approximately 2,906 to 3,050 ft.
- PLUG 3: Perforate and squeeze cement up the backside of the 5-1/2" casing across the contact between the Uinta Formation and Green River Formation at 1,411 ft. unless pre-existing backside cement precludes cement-squeezing this interval. Set a minimum 100-foot plug inside the 5-1/2" casing from approximately 1,361-1,461 ft.
- PLUG 4: Set a Class "G" cement plug within the 5-1/2" casing to 585 ft. and up the 5-1/2" x 8-5/8" casing annulus to the surface.

INJECTION WELL-SPECIFIC CONSIDERATIONS

Well Name: Allen Federal 32-6-9-17 EPA Well ID Number: UT20642-08173

<u>Underground Sources of Drinking Water (USDWs)</u>: USDWs in the Jonah Unit Area Permit generally occur within the Uinta Formation. According to "Base of Moderately Saline Ground Water in the Uinta Basin, Utah, Technical Publication No. 92," the base of moderately saline ground water may be found at approximately 535 ft. below ground surface in the Allen Federal 32-6-9-17 well.

Water Resources within the Area of Review: There are no reservoirs, streams, domestic or agricultural water wells within a quarter (1/4) mile of the well according to Utah's Division of Water Rights (http://nrwrt1.state.ut.us).

Composition of Source, Formation, and Injectate Water: The Total Dissolved Solids (TDS) content of water produced from the Douglas Creek Member of the Green River Formation was determined to be 17,931 mg/l on June 18, 2008. Due to nearby injection activity for the purpose of enhanced oil recovery, this TDS value may not be representative of the original TDS content of formation waters at or near the Allen Federal 32-6-9-17 well.

The TDS content of injectate was determined to be 4,278 mg/l on January 20, 2008. The injectate is water from Newfield Production Company's Jonah injection facility and consists of culinary water from the Johnson Water District blended with produced Green River Formation water resulting in a TDS content less than 10,000 mg/l.

Aquifer Exemption: An aquifer exemption is not required because the TDS of water produced from the proposed injection well is greater than 10,000 mg/l. In addition, the freshening of aquifers in parts of the Monument Butte Field as a result of water injection for the purpose of enhanced oil recovery has been demonstrated by Newfield Production Company and it is EPA Region 8's decision to not aquifer exempt these temporary, artificially created zones of aquifer with less than 10,000 mg/l TDS. It is expected that once injection operations are halted, the aquifer will re-establish its original TDS content through the natural processes of water-rock interaction.

Confining Zone: The Administrative Confining Zone directly overlies the Garden Gulch Member of the Green River Formation and is found between 3,546 ft and 3,742 ft. in the Allen Federal 32-6-9-17 well. However, the cement record shows no cement behind casing through this interval. To avoid the risks associated with cement-squeezing, two additional Area of Review-wide confining zones that have cement behind casing in the Allen Federal 32-6-9-17 well have been identified as follows:

Shale "A": 3,858 ft. to 3,942 ft. – Insufficient cement according to CBL analysis Shale "B": 3,972 feet to 4,056 ft. – Sufficient cement according to CBL analysis

<u>Injection Zone</u>: The Injection Zone at this well location, which has been modified from the Jonah Unit Area Permit, is approximately 2,049 ft. of multiple lenticular sand units interbedded with shale, marlstone and limestone from the base of Shale "B" at 4,056 ft. to the top of the Wasatch Formation which is estimated to be at 6,105 ft. The Wasatch Formation top is based on correlation to the Newfield Production Federal #1-26-8-17 (UT20702-04671) Type Log.

Well Construction: The CBL shows no cement through the Administrative Confining Zone. However, cement is present immediately beneath this interval and continues through the Shale "A" and Shale "B" intervals described above with Shale "B" showing more than 18 feet of continuous 80 percent or greater cement bond index. However, due to the absence of cement through the established areal Confining Zone and the employment of this new confining zone, further demonstration that well cement is adequate to prevent significant migration of injection fluids behind casing is required.

Surface Casing: 8-5/8" casing is set at 260 ft (KB) in a 12-1/4" hole, using 190

sacks of Class "G" cement, cemented to the surface.

Longstring Casing: 5-1/2" casing is set at 5,401 ft in a 7-7/8" hole secured with 695

sacks of cement. Recorded total driller depth is 5,401 ft. Plugged back total depth is 5,365 ft. Top of cement per CBL is 2,550 ft.

<u>Perforations</u>: Top perforation: 4246 ft. Bottom perforation: 5232 ft.

AREA OF REVIEW (AOR) WELL REQUIREMENTS

The following eight wells that penetrate the confining zone within or proximate to a 1/4 mile radius around the Allen Federal 32-6-9-17 were evaluated to determine if any corrective action is necessary to prevent fluid movement into USDWs.

Well: Jonah Federal H-6-9-17	API: 43-013-33494	SWNE Sec. 6-T9S-R17E
Well: Jonah Federal I-6-9-17	API: 43-013-33495	NENE Sec. 6-T9S-R17E
Well: Jonah Federal J-6-9-17	API: 43-013-33496	SENE Sec. 6-T9S-R17E
Well: Jonah Federal L-6-9-17	API: 43-013-33498	NWSW Sec. 6-T9S-R17E
Well: Jonah Federal M-6-9-17	API: 43-013-33499	NESW Sec. 6-T9S-R17E
Well: Allen Federal 22-6-6-17	API: 43-013-30919	SENW Sec. 9-T9S-R17E
Well: Monument Federal 33-6-9-17	API: 43-013-31361	NWSE Sec. 6-T9S-R17E
Well: Monument Federal 42-6-9-17	API: 43-013-31364	SENE Sec. 6-T9S-R17E

Authorization for Additional Well: UIC Area Permit UT20642-00000 Well: Allen Federal 32-6-9-17 EPA Well ID: UT20642-08173

Corrective Action or Weekly Monitoring Required on One AOR Well:

Well: Monument Federal 42-6-9-17 API: 43-013-31364 SENE Sec. 6-T9S-R17E Submitted CBL does not include the confining zone, thus preventing a determination of wellbore mechanical integrity. Newfield has the option of following the corrective action plan detailed below for this well or running and submitting a complete CBL to demonstrate that well construction is adequate.

AOR Well Corrective Action Plan: The Monument Federal 42-6-9-17 well shall be monitored weekly at the surface for evidence of fluid movement out of the injection zone. In addition, Newfield developed a corrective action monitoring program, effective July 10, 2008, entitled "Procedure related to proposed Class II Enhanced Oil Recovery Injection Wells determined by the EPA to have specific Area of Review (AOR) wells with inadequate cement across the Confining Zone" and the permittee is referred to this document.

If possible fluid movement out of the Injection Zone is identified, either through the weekly monitoring, through Newfield's July 10, 2008 procedure described above, or through any other means, (for example, evidence of fluid flow or increased bradenhead annulus pressure readings, the Permittee will shut in the Allen Federal 32-6-9-17 well immediately and notify the Director. No injection into the Allen Federal 32-6-9-17 well will be permitted until the Permittee has notified the Director that the situation has been resolved, submitted Reword Records (EPA Form No.7520-12) and a schematic diagram, and received authorization from the Director to recommence injection.

Monitoring Not Required on Seven AOR wells:

Well: Jonah Federal H-6-9-17 API: 43-013-33494 SWNE Sec. 6-T9S-R17E Shows 222 ft. of 80 percent cement bond or greater from 3,672-3,894 ft.

Well: Jonah Federal J-6-9-17 API: 43-013-33496 SENE Sec. 6-T9S-R17E Shows 86 ft of 80 percent cement bond or greater from 3,630-3,830 ft.

Well: Jonah Federal L-6-9-17 API: 43-013-33498 NWSW Sec. 6-T9S-R17E Shows 98 ft of 80 percent cement bond or greater from 3,624-3,722 ft.

Well: Jonah Federal M-6-9-17 API: 43-013-33499 NESW Sec. 6-T9S-R17E Shows 26 ft of 80 percent cement bond index or greater from 3,745-3,771 ft.

Well: Jonah Federal I-6-9-17 API: 43-013-33495 NENE Sec. 6-T9S-R17E Shows marginal cement through the established areal Confining zone, but 80 percent cement bond or greater through Shales "A" and "B"

Well: Allen Federal 22-6-6-17 API: 43-013-30919 SENW Sec. 9-T9S-R17E This is a previously permitted injection well (UT20642-03729). Submitted CBL shows marginal cement bond index throughout the confining zone. Any corrective action required for this well will be handled through the existing permit for Allen Federal 22-6-9-17.

Well: Monument Federal 33-6-9-17 API: 43-013-31361 NWSE Sec. 6-T9S-R17E This is a previously permitted injection well (EPA UIC Permit UT20642-03736). The submitted CBL does not include the confining zone. UIC Permit UT20642-03736 was modified to require a regular (once every 5 years) temperature log in conjunction with this add well authorization. The first temperature log, conducted in 2008, indicated no fluid movement behind pipe and a second Permit modification was made to require a RTS instead regular temperature logging. The RTS is required to be repeated under any of the circumstances specified in the modification to UIC Permit UT20642-03736, which are equivalent to the circumstances under which the RTS required for this add well authorization must be repeated.

Reporting of Noncompliance:

- (a) Anticipated Noncompliance. The operator shall give advance notice to the Director of any planned changes in the permitted facility or activity which may result in noncompliance with permit requirements.
- (b) <u>Compliance Schedules</u>. Reports of compliance or noncompliance with, or any progress on, interim and final requirements contained in any compliance schedule of this Permit shall be submitted no later than thirty (30) days following each schedule date.
- (c) Written Notice of any noncompliance which may endanger health or the environment shall be reported to the Director within five (5) days of the time the operator becomes aware of the noncompliance. The written notice shall contain a description of the noncompliance and its cause; the period of noncompliance including dates and times; if the noncompliance has not been corrected the anticipated time it is expected to continue; and steps taken or planned to prevent or reduce recurrence of the noncompliance.

Twenty-Four Hour Noncompliance Reporting: The operator shall report to the Director any noncompliance which may endanger health or environment. Information shall be provided, either orally or by leaving a message, within twenty-four (24) hours from the time the operator becomes aware of the circumstances by telephoning 1-(800)-227-8917 and asking for the EPA Region 8 UIC Program Compliance and Enforcement Director, or by contacting the Region 8 Emergency Operations Center at (303)-293-1788. The following information shall be included in the verbal report:

- (a) Any monitoring or other information which indicates that any contaminant may cause an endangerment to a USDW.
- (b) Any noncompliance with a Permit condition or malfunction of the injection system which may cause fluid migration into or between underground sources of drinking water.

Oil Spill and Chemical Release Reporting: The operator shall comply with all other reporting requirements related to oil spills and chemical releases or other potential impacts to human health or the environment by contacting the National Response Center (NRC) 1-(800)-424-8802 or 1-(202)-267-2675, or through the NRC website at http://www.nrc.uscg.mil/index.htm

<u>Other Noncompliance</u>: The operator shall report all other instances of noncompliance not otherwise reported at the time monitoring reports are submitted.

Other Information: Where the operator becomes aware that he failed to submit any relevant facts in the Permit application, or submitted incorrect information in a Permit application, or in any report to the Director, the operator shall submit such correct facts or information within two weeks of the time such information became known to him.

Spud Date: 4/23/81

Allen Federal 32-6-9-17

Put on Projection: 5/28/81

Wellbore Diagram

Initial Production: 100 STBOPD, 30 MCFD, 16 STBWPD

GL: 5323' KB: 5337' SURFACE CASING STRING: CSG SIZE: K-55 WEIGHT: 24 lbs. 6 jts @ 260 LENGTH: DEPTH LANDED: HOLE SIZE: 12 1/4" CEMENT DATA: 190 sx Class-H Cemented to surface.

05/17/81 4912'- 5254' base of Top Green River

12/20/03

03/23/07

ACID JOB

FRAC JOB

Frac w/Western on 5/17/81. 43,000 gal Apollo 40 w/32,000 ibs 10/20 mesh sd & 55,000 lbs 20/40 mesh sd, avg 34 BPM @ 2400 psig, max @ 2600 psig ISIP @ 2000 psig, 5 min @ 1832 psig, 10 min @ 1800 psig, 15 min @ 1750 psig.

Frac w/Smith on 10/15/90. 24,086 gal 30 lbs GWX-9 w/46,000 lbs 20/40 mesh sd, & 83,000 lbs 16/30 mesh sd, Avg @ 55 BPM @ 2200 psig, max @ 2950 psig, ISIP @ 2010 psig, 15 min @ 1670 psig. Ramp 1/2 to 6 lbs.

PRODUCTION CASING

STRING: CSG SIZE: GRADE: WEIGHT:

J-55

LENGTH: DEPTH LANDED: 15.5# & 14# 169 jts @ 5389 5401 KB 33421

D.V. TOOL: HOLE SIZE: CEMENT DATA: CEMENT TOP AT:

7 7/8" 695 sx 50-50 Poz.

2200' from well records

3546

TUBING RECORD

SIZE/GRADE/WT .: 2 3/8", J-55, 4.7# NO. OF JOINTS: 168 jts. @ 5282' TUBING ANCHOR: None NO. OF JOINTS: 1 jt. SEATING NIPPLE: 2 3/8" x 1' 2 3/8" x 4' PERF. SUB: MUD ANCHOR: 2 3/8" x 31' 5318 TOTAL STRING LENGTH: SN LANDED AT: 5297'KB

SUCKER RODS

POLISHED ROD: 1-1/2" x 16' SM

SUCKER RODS: 1-2', 1-4' x ¼" pony rods, 98- ¼" guided rods, 96- ¾" slick rods, 15- 4" guided rods, 2- 1 1½" weight bars.

PUMP SIZE: 2" x 1-1/2" x 16' RHAC pump w/SM plunger

STROKE LENGTH: 64"

PUMP SPEED, SPM: 6 SPM

LOGS: DIGL/SP/GR/CAL

3748

3546

2956

Pump Change: Updated rod and tubing detail.

Stuck Pump: Update tubing and rod detail.

Bench (box 6 3000) coment through established confining

4246'- 4289' 3990 gal 3% KCl; 75 ball sealers were pumped, 7.5 BPM @ 4300 psig. ISIP @ 1630 psig, 15 min @ 1520 psig. 4912'- 5254' 1500 gal 15% HCl Acid, 5 BPM @ 1500 psig to 8 BPM @ 1700 psig. Drop balls, saw ball action. Pumping @ 8 BPM @ 2000 psig, no ball off. ISIP @ 1600 psig, 5 min @ 1500

4246'-4252'

4730

PERFORATION RECORD

42461- 42521 4283'-4289' 4283' - 4289' (61) 4 SPF 4912' - 4934' 5232'- 5254' (22') 2 SPF 4912'-4934

5232'-5254'

SN @ 5297

EOT @ 5318. Top of Fill @ 5350" PBTD @ 53651 SHOE @ 5364'

TD @ 5401'

Basal Carbonate 6 5980 (est) Wasatch 6 6105 (est)

NEWFIELD

Allen Federal #32-6-9-17

2102' FNL & 1949' FEL

SW/NE Section 6-T9S-R17E

Duchesne Co, Utah

API #43-013-30559; Lease #UTU-020252A

CT 7/18/08

Put on Projection: 5/28/81 Initial Production: 100 STBOPD, GL: 5323' KB: 5337' Proposed P & A 30 MCFD, 16 STBWPD Wellbore Diagram SURFACE CASING STRING: CSG SIZE: Circulate 87 sx Class "G" Cement down 5-1/2" casing and up WEIGHT: 24 lbs. the 5-1/2" x 8-5/8" annulus Aug#4: 12'-585'(KB) 6 its @ -260 LENGTH: Casing Shoe @ 260' DEPTH LANDED: HOLE SIZE: 12 1/4" CEMENT DATA: 190 sx Class-H Cemented to surface. 585 29th Pert casing 250' Was USDN base @ 535' and Equeeze cement to Plug #3: Minimum of 100 plug across the contact between tace, cerent inside of casing(anulus). surface to 2 50' below the Base of PRODUCTION CASING the USDW @ the vinta Formation and 535. 5 1/2". CSG SIZE: the Green River Formation at GRADE: J-55 WEIGHT: Plug from 1366 to 1466 LENGTH : 169 jts @ 5389' DEPTH LANDED: 5401 KB D.V. TOOL: 3342' HOLE SIZE: 7 7/8" CEMENT DATA: CEMENT TOP AT: 695 sx 50-50 Poz. 2200' from well records 17 sx Class G Cement plug on top of CICR Plna#Z: Minimum CICR @ 2150'---Trona/Birds Nest plug from = 50 above 36 sx Class G Cement plug below CICR 200' Plug w/0' excess Trona @ 2985 to 250 Cement top @ 2200 from well records Perforate 2 JSPF @-32001 below the base of the Spot inhibited water between cement plugs Mahayany Berch @ 3000 Plug from 2906 to 3050 Plug#1: \$50' above first por. 5' CIBP with? 100' (12 sx) Class G Cement plug on top of CTBP 70' cement on top. 4246'-4252' 4283'-4289 49121-49341 5232'-5254' Top of Fill @ 5350" NEWFIELD PBTD @ 53651 TD @ 5401 Allen Federal #32-6-9-17 2102' FNL & 1949' FEL SW/NE Section 6-T9S-R17E · Duchesne Co, Utah

Allen Federal 32-6-9-17

Spud Date: 4/23/81

API #43-013-30559; Lease #UTU-020252A



RE: Procedure related to proposed Class II Enhanced Oil Recovery Injection Wells determined by the EPA to have specific Area of Review (AOR) wells with inadequate cement across the confining zone

Effective July 10, 2008 Newfield Production Company will implement the following procedure to address concerns related to protection of Underground Sources of Drinking Water (USDW) in AOR wells where the interval of cement bond index across the confining zone behind pipe has been determined to be inadequate. The procedure is intended to meet the corrective action requirements found in the UIC Class II permit, as well as provide data that could be used to detect and prevent fluid movement out of the proposed injection zone.

- 1) Establish baseline production casing by surface casing annulus pressures prior to water injection in subject well with a calibrated gauge.
- 2) Record the baseline pressure, report findings to Newfield engineering group and keep on file so it is available upon request
- 3) Place injection well in service. Run packer integrity and radioactive tracer logs to verify wellbore integrity and determine zones taking water.
- 4) Construct a geologic cross section showing zones taking water and their geologic equivalent zones in the AOR wells.
- 5) Submit a report of the packer integrity log, radioactive tracer log, and geologic cross section to to the Newfield engineering staff for review and keep on file so it is available upon request
- 6) Weekly observations of the site will be made by Newfield during normal well operating activities. Any surface discharge of fluids will be reported immediately.
- 7) After injection well is placed in service, weekly observations of annulus pressure will be made and compared to baseline pressure and will be recorded once monthly. The recorded pressure information will be kept on file and be available upon request.
- 8) If pressure increases by more than 10% above baseline at any time in an AOR well with insufficient cement bond, Newfield will run a temperature survey log in subject well. This log, in concert with the geologic crossection, will enable the determination of water movement in the open hole by production casing annulus through a shift in geothermal gradient.
- 9) If water movement is determined in annulus, Newfield will shut in the injection well and repair the production casing by open hole annulus or leave the injection well out of service.

STATE OF UTAH

	DIVISION OF OIL, GAS AN			5. LEASE DESIGNATION AND SERIAL NUMBER: USA UTU-020252-A
SUNDRY	Y NOTICES AND REPO	ORTS ON	WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:
Do not use this form for proposals to d	rill new wells, significantly deepen existing wells tal laterals. Use APPLICATION FOR PERMIT T	below current bottom	-hole depth, reenter plugged	7. UNIT or CA AGREEMENT NAME: GMBU
1. TYPE OF WELL: OIL WELL		O DRILL IOIII IOI SI	ich proposais.	8. WELL NAME and NUMBER: ALLEN FED 32-6
2. NAME OF OPERATOR:				9. API NUMBER:
NEWFIELD PRODUCTION COM	MPANY			4301330559
3. ADDRESS OF OPERATOR:		0.40==	PHONE NUMBER	10. FIELD AND POOL, OR WILDCAT:
Route 3 Box 3630 4. LOCATION OF WELL:	CITY Myton STATE UT	ZIP 84052	435.646.3721	GREATER MB UNIT
FOOTAGES AT SURFACE: 2102 FNL	1949 FEL			COUNTY: DUCHESNE
OTR/OTR, SECTION, TOWNSHIP, RANGE	: MERIDIAN: SWNE, 6, T9S, R17E			STATE: UT
	PRIATE BOXES TO INDICAT	E NATURE	OF NOTICE, RE	PORT, OR OTHER DATA
TYPE OF SUBMISSION		TY	PE OF ACTION	
NOTICE OF INTENER	ACIDIZE	DEEPEN		REPERFORATE CURRENT FORMATION
NOTICE OF INTENT (Submit in Duplicate)	ALTER CASING	FRACTURE	TREAT	SIDETRACK TO REPAIR WELL
Approximate date work will	CASING REPAIR	NEW CONST	RUCTION	TEMPORARITLY ABANDON
	CHANGE TO PREVIOUS PLANS	OPERATOR	CHANGE	TUBING REPAIR
	CHANGE TUBING	PLUG AND		VENT OR FLAIR
X SUBSEQUENT REPORT	CHANGE WELL NAME	PLUG BACK		WATER DISPOSAL
(Submit Original Form Only)	X CHANGE WELL STATUS	=		=
Date of Work Completion:	I <u></u>	=	ON (START/STOP)	WATER SHUT-OFF
06/10/2010	COMMINGLE PRODUCING FORMATIONS X CONVERT WELL TYPE		ION OF WELL SITE	OTHER: -
, , , , , , , , , , , , , , , , , , , ,			TÉ - DIFFERENT FORMATIO	
The subject well has been New interval added: D1 4 On 06/01/2010 Jason Dea casing was pressured up t	ordorff with the EPA was contacted on the contacted on 1165 psig and charted for 30 minutes on the contacted for 30 minutes on the contacted o	to an injection	well on 06/07/10. initial MIT on the ab essure loss. The we	pove listed well. On 06/10/2010 the ell was not injecting during the test.
NAME (PLEASE PRINT) Lucy Chavez-l	Naupoto		TITLE Administrative A	Assistant
SIGNATURE Key Cl	lay Mpred		DATE06/14/2010	
his space for State use only)				

RECEIVED
JUN 2 1 2010

FORM 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM A	PPROVED
OMB No.	1004-013
Expires: In	dv 31 2010

	BUREAU OF LAND MANA	GEMENT			expires: July 31,2010
	Y NOTICES AND REPO			5. Lease Serial N	lo.
	this form for proposals to			USA UTU-020	252-A
abandoned w	ell. Use Form 3160-3 (AF	D) for such proposals	3.	6. If Indian, Allot	tee or Tribe Name.
				4	
SUBMIT IN	TRIPLICATE - Other I	nstructions on page 2		7. If Unit or CA/	Agreement, Name and/or
			·	GMBU	
1. Type of Well	Other				
Oil Well Gas Well 2. Name of Operator	Other			8. Well Name and	
NEWFIELD PRODUCTION CO	OMPANY			ALLEN FED 32	-6
3a. Address Route 3 Box 3630	Z	3b. Phone (include are	code)	9. API Well No. 4301330559	
Myton, UT 84052		435,646,3721	coucy		l, or Exploratory Area
4. Location of Well (Footage,	Sec., T., R., M., or Survey Descrip		7.12	GREATER MB	
2102 FNL 1949 FEL				11. County or Par	
SWNE Section 6 T9S R17E					
	······································			DUCHESNE, U	
12. CHECK	APPROPRIATE BOX(E	S) TO INIDICATE NA	TURE OF N	OTICE, OR OT	THER DATA
TYPE OF SUBMISSION		TYPI	E OF ACTION	J	
	☐ Acidize			10 15	
Notice of Intent	Acidize Alter Casing	Deepen Fracture Treat	=	on (Start/Resume)	Water Shut-Off
Subsequent Report	Casing Repair	New Construction	Reclama Recompl		Well Integrity
Subsequent Report	Change Plans	Plug & Abandon			OtherChange Status
Final Abandonment	Change Flans Convert to Injector	Plug Back	Water Di	rily Abandon	Change Status
Bond under which the work will be of the involved operations. If the op Final Abandonment Notices shall be inspection.) The subject well has bee New interval added: D1 on 06/01/2010 Jason De the casing was pressured.	ardorff with the EPA was ca I up to 1165 psig and chart sure was 0 psig during the	in file with BLM/BIA. Required some or recompletion in a new intervalding reclamation, have been coming oil well to an injection ontacted concerning the ed for 30 minutes with r	ubsequent reports val, a Form 3160-4 npleted, and the op n well on 06/0 e initial MIT on no pressure ke	shall be filed within 30 shall be filed once test berator has determined to 07/10. In the above listences. The well was	odays following completion ting has been completed. that the site is ready for final ed well. On 06/10/2010 as not injecting during
I hereby certify that the foregoing is correct (Printed/ Typed)	true and	Title			
Lucy Chavez-Naupoto		Administrative A	Assistant		
Signature		Date			

Title

Correct (Printed/ Typed)

Lucy Chavez-Naupoto

Administrative Assistant

Date

06/14/2010

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by.

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Title 18 USC Section 1001 and Title 43 USC Section 1212 perhatic spins for some state of the spins of the state of the spins of the subject lease which would entitle the applicant to conduct operations thereon.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious and fraudulent statements or representations as to any matter within its jurisdiction

Mechanical Integrity Test Casing or Annulus Pressure Mechanical Integrity Test U.S. Environmental Protection Agency Underground Injection Control Program


999 18th Street, Suite 500 Denver, CO 80202-2466

EPA Witness:			Date:	1 10	12010	
Test conducted by:						
Others present:						
Well Name: Allen Federal 3			Type: ER SWD	Statı	ıs: AC TA	UC
Field: Monument Butte F	ield				Channe /	
Location: 5 W/NE Sec		168) R_/7	(E) W County: \(\int_{\infty}\)	acheshe	State:_6	<u>cr.</u>
Operator: NewField			1.1. Donorous		PS	iiG
Last MIT:/	/ Maxii	num Allow	able Pressure:			10
	[X]] No			
Test after well rework?		Yes [X	i No . If Yes, rat	e:		bpd
Well injecting during test?	()	165 (>-	- 1 10 \$ 11 100, 100	· · · · · · · · · · · · · · · · · · ·		- 1
Pre-test casing/tubing annulu	ıs pressure:	0	psig			
-						
MIT DATA TABLE	Test #1		Test #2		Test	#3
TUBING	PRESSURE					-
Initial Pressure	0	psig	J	osig		psig
End of test pressure	8	psig	I	osig		psig
CASING / TUBING	ANNULUS		PRESSURE			
0 minutes	1165	psig	Ţ	osig		psig
5 minutes	1165	psig	. 1	osig		psig
10 minutes	1165	psig	J	osig		psig
15 minutes	1165	psig	J	osig		psig
20 minutes	1165	psig	1	osig		psig
25 minutes	1165	psig	1	osig		psig
30 minutes	1165	psig	1	psig		psig
minutes		psig	_ 1	psig		psig
minutes		psig]	psig		psig
RESULT	[x] Pass	[]Fail	[] Pass []Fail	[] Pass	[]Fail

[X] No Does the annulus pressure build back up after the test? [] Yes MECHANICAL INTEGRITY PRESSURE TEST

Additional comments for mechanical integrity pressure test, such as volume of fluid added to annulus and bled back at end of test, reason for failing test (casing head leak, tubing leak, other), etc.:

Signature of Witness:	
nghatare of vitalious.	



Daily Activity Report

Format For Sundry ALLEN 32-6-9-17 4/1/2010 To 8/30/2010

6/1/2010 Day: 1

Conversion

Nabors #809 on 6/1/2010 - MIRUSU. Lay down rods. TOOH w/ tbg. - Shut unit down. MIRUSU. Pump 60 bbls water down casing. Unseat pump. Flush rods w/ 30 bbls water. Soft seat pump. Test tbg to 3000 psi. Fish rods. TOOH w/ rods laying down on trailer. RU BOP's. TOOH w/ tbg. Breaking, doping (liquid "O" ring) & inspecting every pin. EOT @ 2800'. SIFN.

Daily Cost: \$0

Cumulative Cost: (\$9,827)

6/3/2010 Day: 2

Conversion

Nabors #809 on 6/3/2010 - TOOH w/ tbg. Perferate D1 sds. TIH w/ frac string. Break zone down. - Open well w/ 0 psi on casing. Continue TOOH w/ tbg breaking, doping & inspecting every pin. RU Perforators LLC WLT & pack-off tool. RIH w/ 3-1/8" Port guns w/ gauge ring (11 gram, .36"EH, 120°, 16.82"pen) & perferate D1 sds @ 4772-81' w/ 3 spf for total of 27 shots. RD WLT. PU Weatherford 5-1/2" x 2-1/2" "TS" RBP, retrieving head, 2-3/8" x 4' pup joint, "HD" pkr, SN. PU off trailer 2-7/8", 6.5#, N-80 frac string. TIH w/ tbg to set RBP 4804'. Set pkr @ 4803'. Test tools. Reset pkr @ 4756'. Break down D1 sds @ 3000 psi back to 2250 psi @ 1/4 bpm. Release pkr. SIFN. Well ready for frac.

Daily Cost: \$0

Cumulative Cost: (\$1,174)

6/4/2010 Day: 3

Conversion

Nabors #809 on 6/4/2010 - Frac well. Flow well back. LD frac string. - Set pkr. RU BJ Services. Open well w/ 46 psi on tbg. Perfs broke down @ 3806 psi back to 1571 @ 3 bpm. 1 min was 1627. 4 min was 1571. Pump 30 gals of Techni Hib. Frac w/ 12,605#'s of 20/40 sand in 177 bbls of Lightning 17 frac fluid. Treated @ ave pressure of 3713 @ ave rate of 15 bpm w/ 6 ppg of sand. ISIP was 1944 w/ .84FG. 5 min was 1789. 10 min was 1735. 15 min was 1700. Flow well back. Well flowed for 1 hour & died. Rec'd 90 bbls fluid. Release pkr. Circulate tbg clean. TIH w/ tbg to tag 30' of sand. C/O to RBP. Release RBP. TOOH w/ tbg laying down on trailer. Set RBP @ 4207' & test casing to 1500 psi. Continue TOOH w/ N-80 tbg. SIFN. 138 jts LD EOT @ 1200'.

Daily Cost: \$0

Cumulative Cost: \$24,542

6/7/2010 Day: 4

Conversion

Nabors #809 on 6/7/2010 - LD N-80 tbg. Test tbg. Test casing. RDMOSU. - Continue TOOH w/ N-80 frac string. LD tools. RU 5-1/2" x 2' Arrow Set 1 pkr w/ wire line entry guide, SN. TIH w/ tbg tightening collars. Test tbg twice on TIH w/ 3000 psi. RU sand line & fish SV. RD BOP's. Pump 65 bbls of pkr fluid. Set pkr @ 4201' w/ 15,000#'s tension w/ EOT 4208' @ & CE @ 4204'. Test casing to 1400 psi for 1/2 hour test. RDMOSU. Well ready for MIT.

Daily Cost: \$0

Cumulative Cost: \$36,057

6/11/2010 Day: 5

Conversion

Rigless on 6/11/2010 - Conversion Mit - On 6/1/2010 Jason Deardorff with the EPA was contacted concerning the Conversion MIT on the above listed well (Allen 32-6-9-17). On 6/10/2010 the csg was pressured up to 1165 psig and charted for 30 minutes with no pressure loss. The well was not injecting during the test. The tbg pressure was psig during the test. There was not an EPA representative available to witness the test. Final Report EPA# UT 20642-08173 API#43-013-30559 Finalized

Daily Cost: \$0

Cumulative Cost: \$61,377

Pertinent Files: Go to File List

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY REGION 8



1595 Wynkoop Street
DENVER, CO 80202-1129
Phone 800-227-8917
http://www.epa.gov/region08

JUL 08 2010

Ref: 8P-W-GW

CERTIFIED MAIL RETURN RECEIPT REQUESTED

Mr. Michael Guinn District Manager Newfield Production Company Route 3 – Box 3630 Myton, UT 84052 Accepted by the Utah Division of Oil, Gas and Mining

FOR RECORD ONLY

RE: Underground Injection Control (UIC)
Limited Authorization to Inject
EPA UIC Permit UT20642-08173
Well: Allen Federal 32-6-9-17
NWNE Sec. 6-T9S-R17E
Duchesne County, Utah
API No.: 43-013-30559

Dear Mr. Guinn:

The Environmental Protection Agency Region 8 (EPA) has received Newfield Production Company's (Newfield) June 14, 2010, letter with enclosures. The enclosed Part I (internal) Mechanical Integrity test, Well Rework Record (EPA Form 7520-12), schematic diagram, and calculated pore pressure were reviewed and approved by EPA, satisfactorily completing all Prior to Commencing Injection Requirements for UIC Permit UT20642-08173.

As of the date of this letter, Newfield is authorized to commence injection into the Allen Federal 32-6-9-17 well at a Maximum Allowable Injection Pressure (MAIP) of 1,700 psig for a limited period of 180 days, during which time a Radioactive Tracer Survey (RTS) is required. If Newfield seeks a higher MAIP than 1,700 psig, it may be advantageous to run a step rate test prior to conducting the RTS because a RTS conducted at the higher MAIP will be required. Newfield must receive prior authorization from the Director to inject at pressures greater than the permitted MAIP during any test.

Please remember that it is Newfield's responsibility to be aware of and to comply with all conditions of Permit UT20642-08173.

RECEIVED
JUL 1 4 2010

If you have questions regarding the above action, please call Jason Deardorff at 303-312-6583 or 1-800-227-8917, ext. 312-6583. The RTS log with interpretation should be mailed to Jason Deardorff at the letterhead address, citing mail code 8P-W-GW.

Sincerely,

Stephen S. Tuber
Assistant Regional Administrator

Office of Partnerships and Regulatory Assistance

cc: Uintah & Ouray Business Committee:

Curtis Cesspooch, Chairman Frances Poowegup, Vice-chairwoman Phillip Chimburas, Councilman Stewart Pike, Councilman Irene Cuch, Councilwoman Richard Jenks, Jr., Councilman

Daniel Picard BIA - Uintah & Ouray Indian Agency

Ferron Secakuku Director, Natural Resources Ute Indian Tribe

Manual Myore Director of Energy & Minerals Dept. Ute Indian Tribe

Brad Hill Acting Associate Director Utah Division of Oil, Gas, and Mining

Fluid Minerals Engineering Office BLM - Vernal Office

Eric Sundberg, Regulatory Analyst Newfield Production Company



STATE OF UTAH

Sta	STATE OF UTAH		•	
<u> </u>	DEPARTMENT OF NATURAL R			5. LEASE DESIGNATION AND SERIAL NUMBER:
	DIVISION OF OIL, GAS AN	ID MINING		USA UTU-020252-A
SUNDR	Y NOTICES AND REPO	ORTS ON	WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:
	drill new wells, significantly deepen existing wells b ntal laterals. Use APPLICATION FOR PERMIT TO			7. UNIT or CA AGREEMENT NAME: GMBU
TYPE OF WELL				8. WELL NAME and NUMBER:
OIL WELL	GAS WELL OTHER			ALLEN FED 32-6
2. NAME OF OPERATOR:				9. API NUMBER:
NEWFIELD PRODUCTION CO	MPANY			4301330559
3. ADDRESS OF OPERATOR:			PHONE NUMBER	10. FIELD AND POOL, OR WILDCAT:
Route 3 Box 3630	CITY Myton STATE UT	ZIP 84052	435.646.3721	GREATER MB UNIT
4. LOCATION OF WELL: FOOTAGES AT SURFACE: 2102 FNI	_ 1949 FEL			COUNTY: DUCHESNE
411				
COTR/OTR, SECTION, TOWNSHIP, RANG	E. MERIDIAN: SWNE, 6, T9S, R17E			STATE: UT
A41 477				
CHECK APPRO	PRIATE BOXES TO INDICAT	E NATURE (OF NOTICE, REPO	ORT, OR OTHER DATA
TYPE OF SUBMISSION		TY	PE OF ACTION	
	ACIDIZE	DEEPEN		REPERFORATE CURRENT FORMATION
NOTICE OF INTENT (Submit in Duplicate)	ALTER CASING	FRACTURE	REAT	SIDETRACK TO REPAIR WELL
	CASING REPAIR	NEW CONST	RUCTION	TEMPORARITLY ABANDON
Approximate date work will	CHANGE TO PREVIOUS PLANS	OPERATOR O		TUBING REPAIR
08/09/2010				VENT OR FLAIR
diam.	CHANGE TUBING	PLUG AND A		
SUBSEQUENT REPORT	CHANGE WELL NAME	PLUG BACK		WATER DISPOSAL
(Submit Original Form Only)	CHANGE WELL STATUS	PRODUCTIO	N (START/STOP)	WATER SHUT-OFF
Date of Work Completion:	COMMINGLE PRODUCING FORMATIONS	RECLAMAT	ION OF WELL SITE	OTHER: - Put on Injection
	X CONVERT WELL TYPE	RECOMPLET	TE - DIFFERENT FORMATION	
DESCRIPT PROPOSED OF	COMPLETED OPEN A TIONS. Clearly show	all martinant datail	a including dates denths a	volumes etc
	COMPLETED OPERATIONS. Clearly show		s including dates, depuis,	rotunes, etc.
The above reference well	l was put on injection at 10:00 AM on	08-09-2010.		
EPA # UT20642-08173	API # 43-013-30559			
<u>ं</u> हें				
<u>iii</u>				in the second se
TMR. - 3.	÷		Accepted by the	Ve and
a.04		Signal Signal Signal	Utah Division	OT %
		-		ONIX
		E	OR RECORD	U: 1-
n .		•	~ · ·	
operation in the second				

(This space for State use only)

NAME (PLEASE PRINT) Lucy Chavez-Naupoto

RECEIVED AUG 1 6 2010

TITLE Administrative Assistant

08/09/2010



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY REGION 8

1595 Wynkoop Street
Denver, CO 80202-1129
Phone 800-227-8917
http://www.epa.gov/region08

DEC 03 2010

Ref: 8P-W-GW

<u>CERTIFIED MAIL</u> <u>RETURN RECEIPT REQUESTED</u>

RECEIVED
DEC 2 2 2010
DIV. OF OIL, GAS & MINING

Mr. Michael Guinn District Manager Newfield Production Company Route 3-Box 3630 Myton, UT 84502

Accepted by the Utah Division of Oil, Gas and Mining

FOR RECORD ONLY

RE: Underground Injection Control (UIC)
Authorization to Continue Injection
EPA UIC Permit UT20642-08173
Well: Allen Federal 32-6-9-17
SWNE Sec. 32-T9S-R17E
Duchesne County, UT

Duchesne County, UT API No.: 43-013-30559

Dear Mr. Guinn:

The U.S. Environmental Protection Agency (EPA), Region 8, received the results of the November 10, 2010, Radioactive Tracer Survey (RTS) for the Allen Federal 32-6-9-17 well. EPA determined the test demonstrates the presence of adequate cement to prevent the upward migration of injection fluids from the injection zone at the Maximum Allowable Injection Pressure (MAIP) of 1,700 psig.

As of the date of this letter, EPA hereby authorizes continued injection into the Allen Federal 32-6-9-17 well under the terms and conditions of UIC Permit UT20642-08173.

You may apply for a higher MAIP at a later date. Your application should be accompanied by the interpreted results of a Step Rate Test (SRT) that measures the formation parting pressure and determines the fracture gradient at this depth and location. Newfield must receive prior authorization from the Director in order to inject at pressures greater than the permitted MAIP during any test. A current copy of EPA guidelines for running and interpreting SRTs will be sent upon request. Should the SRT result in approval of a higher MAIP, a subsequent RTS conducted at the higher MAIP is required.

As of this approval, responsibility for permit compliance and enforcement is transferred to EPA's UIC Technical Enforcement Program. Therefore, please direct all monitoring and compliance correspondence to Nathan Wiser at the following address, referencing the well name and UIC Permit number on all correspondence:

Mr. Nathan Wiser
U.S. EPA Region 8: 8ENF-UFO
1595 Wynkoop Street
Denver, CO 80202-1129

Or, you may reach Mr. Wiser by telephone at 303-312-6211, or 1 800-227-8927, ext. 312-6211. Please remember that it is your responsibility to be aware of and to comply with all conditions of injection well Permit UT20642-08173.

If you have questions regarding the above action, please call Emmett Schmitz at 303-312-6174 or 1-800-227-8917, ext. 312-6174.

Sincerely,

for Stephen S. Tuber

Assistant Regional Administrator

Office of Partnerships and Regulatory Assistance

cc: Uintah & Ouray Business Committee:

Frances Poowegup, Vice-Chairwoman Curtis Cesspooch, Councilman Phillip Chimburas, Councilman Stewart Pike, Councilman Irene Cuch, Councilwoman Richard Jenks, Jr., Councilman

Daniel Picard BIA - Uintah & Ouray Indian Agency

Mike Natchees Environmental Coordinator Ute Indian Tribe

Manual Myore Director of Energy & Minerals Dept. Ute Indian Tribe Brad Hill Acting Associate Director Utah Division of Oil, Gas, and Mining

Fluid Minerals Engineering Office BLM - Vernal Office

Eric Sundberg Regulatory Analyst Newfield Production Company

STATE OF UTAH

	DEPARTMENT OF NATURAL R DIVISION OF OIL, GAS AN		5, LEASE DESIGNATION AND SERIAL NUMBER: USA UTU-020252-A
SUNDR	Y NOTICES AND REPO	ORTS ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:
	Irill new wells, significantly deepen existing wells be tal laterals. Use APPLICATION FOR PERMIT TO		7. UNIT or CA AGREEMENT NAME: GMBU
TYPE OF WELL: OIL WELL	GAS WELL OTHER		8. WELL NAME and NUMBER: ALLEN FED 32-6
NAME OF OPERATOR;			9. API NUMBER:
NEWFIELD PRODUCTION CO	MPANY		4301330559
ADDRESS OF OPERATOR:		PHONE NUMBER	10. FIELD AND POOL, OR WILDCAT:
Route 3 Box 3630	CITY Myton STATE UT	ZIP 84052 435.646.3721	GREATER MB UNIT
LOCATION OF WELL: FOOTAGES AT SURFACE: 2102 FNL	. 1949 FEL		COUNTY: DUCHESNE
OTR/OTR, SECTION, TOWNSHIP, RANGI	E. MERIDIAN: SWNE, 6, T9S, R17E		STATE: UT
. CHECK APPRO	PRIATE BOXES TO INDICATI	E NATURE OF NOTICE, REF	PORT, OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF ACTION	
	ACIDIZE	DEEPEN	REPERFORATE CURRENT FORMATION
NOTICE OF INTENT (Submit in Duplicate)	ALTER CASING	FRACTURE TREAT	SIDETRACK TO REPAIR WELL
(Suomi in Dupicate)			=
Approximate date work will	CASING REPAIR	NEW CONSTRUCTION	TEMPORARITLY ABANDON
	CHANGE TO PREVIOUS PLANS	OPERATOR CHANGE	TUBING REPAIR
	CHANGE TUBING	PLUG AND ABANDON	VENT OR FLAIR
X SUBSEQUENT REPORT	CHANGE WELL NAME	PLUG BACK	WATER DISPOSAL
(Submit Original Form Only)			
Date of Work Completion:	CHANGE WELL STATUS	PRODUCTION (START/STOP)	WATER SHUT-OFF
	COMMINGLE PRODUCING FORMATIONS	RECLAMATION OF WELL SITE	OTHER: - Step Rate Test
04/25/2011	CONVERT WELL TYPE	RECOMPLETE - DIFFERENT FORMATION	1
	ucted on the subject well on April 25, d is requesting that the maximum allo		ate that the fracture gradient is 0.893 e changed from 1700 psi to 1925 psi.
	U Oil,	accepted by the tah Division of Gas and Mining	
	,	ALICOND CIVET	
NAME (PLEASE PRINT) Lucy Chavez-	-Naupoto	TITLE Water Services T	`echnician
GNATURE ()	Contract of the second	DATE 05/31/2011	


This space for State use only)

RECEIVED
JUN 1 4 2011


Step Rate Test (SRT) Analysis

en jarren 1942an. Errora

	Operator:	Newfield Pro	pauction Co	ompany	
	Well:	Federal 7-7-	9-18		
	Permit #:	UT21099-074	413		
Enter t	he following data :				
	Specific Grav	vity (sg) of injectate =	1.015	g/ cc	•
	Depth to t	op perforation (D) = $\overline{}$	5116	 feet	5110
Top of permitted injection zon	e depth (blank=use top perfora.	tion to calculate fg) =		 feet	
Estimated I	Formation Parting Pressure (Pf) from SRT chart =	1430	psi psi	
j	Instantaneous Shut In Pressure	(ISIP) from SRT =	1569	psi	1430
Bottom Hole Parting	g Pressure (Pbhp) from downho	le pressure recorder =		psi	no downhol
	w	here: fg = Phhp / D (Note: this formula w	ses the downhole recorded botto	m hole parting pressure if available) = 1569
	Calculated Ftactu		0.719 ses the downhole recorded botto	psi/ft. m hole parting pressure if available) = 1569
$D = depth \ used = 5116$	Phh	used = 3678			
Calculated	l Rottom Hole Parting P.	recente (Phhn) =	3678	. .:	2670 456
Calculated	Bottom Hole Parting Pl		3678	psi *D)	3678.456
Calculated	to calculate Bottom Hole Parting Pressu	ure (Pbhp) = Formation Fracture Pressure (/	3678.456
Calculated	•	ure (Pbhp) = Formation Fracture Pressure (/	3678.456
	to calculate Bottom Hole Parting Pressi (Uses lesser of ISIP or Pfp) Value	re (Pbbp) = Formation Fracture Pressure (s	ISIP or Pfp) + (0.433 * SG	*D)	367 8 .456
Calculated Part Two - Calculate	to calculate Bottom Hole Parting Pressi (Uses lesser of ISIP or Pfp) Value	re (Pbbp) = Formation Fracture Pressure (s	ISIP or Pfp) + (0.433 * SG	*D)	3678.456
	to calculate Bottom Hole Parting Pressi (Uses lesser of ISIP or Pfp) Value	re (Pbbp) = Formation Fracture Pressure (s	ISIP or P(p) + (0.433 * SG n Pressure	*D)	3678.456
	to calculate Bottom Hole Parting Pressu (Uses lesser of ISIP or Pfp) Value on of Maximum Al	re (Pbbp) = Formation Fracture Pressure (s : used = 1430 lowable Injectio	ISIP or Pfp) + (0.433 * SG	*D)	3678.456
Part Two - Calculati	to calculate Bottom Hole Parting Pressu (Uses lesser of ISIP or Pfp) Value on of Maximum Al	re (Pbbp) = Formation Fracture Pressure (in used = 1430 lowable Injection	ISIP or P(p) + (0.433 * SG n Pressure	(MAIP)	3678.456
<u> Part Two - Calculati</u> aximum Allowable Injed	to calculate Bottom Hole Parting Press. (Uses lesser of ISIP or Pfp) Value ion of Maximum Al	re (Pbbp) = Formation Fracture Pressure (in used = 1430 lowable Injection	nsp or Pfp) + (0.433 * SG <u>n Pressure</u> 1425	(MAIP)	367 8 .456



			Steh	Nate(upu)	r ressure(psi)
Start Pressure:	939	psi	1	50	1027
Instantaneous Shut In Pressure (ISIP):	1569	psi	2	100	1182
Top Perforation:	5116	feet	3	150	1339
Fracture pressure (Pfp):	1430	psi	4	200	1454
FG:	0.719	psi/ft	5	250	1535
	,		6	300	1594



Report Name: Report Date: File Name:

PrTemp1000 Data Table
May 16, 2011 01:54:04 PM MDT
C:\Program Files\PTC® Instruments 2.00\Federal 7-7-9-18 SRT (5-11-2011).csv
Federal 7-7-9-18 SRT (5-11-2011)
PrTemp1000 - Temperature and Pressure Recorder

Device: REV2C (64K) M75866 PrTemp Hardware Revision: Serial Number: Device ID:


Title:

May 11, 2011 05:59:59 AM MDT May 11, 2011 12:30:00 PM MDT 2 Seconds Data Start Date: Data End Date:

Reading Rate: 1 to 79 of 79 Readings: Last Calibration Date: Apr 12, 2011 Apr 12, 2012 Next Calibration Date:

Rea	ding	Date and Time (MDT)	Absolute Pressure	Annotation	
	1	May 11, 2011 05:59:59 AM	944.000 PSIA		
	2	May 11, 2011 06:04:59 AM	942.600 PSIA		
	3	May 11, 2011 06:09:59 AM May 11, 2011 06:14:59 AM	940.400 ⊅PSIA 940.000 PSIA		
	4 5	May 11, 2011 06:14:59 AM May 11, 2011 06:19:59 AM	939.400 PSIA	•	
	6	May 11, 2011 06:24:59 AM	939.000 PSIA		
	7	May 11, 2011 06:30:00 AM	939.000 PSIA		
	8	May 11, 2011 06:34:59 AM	948.400 PSIA		
	9	May 11, 2011 06:40:00 AM	956.400 PSIA		
	10 11	May 11, 2011 06:44:59 AM May 11, 2011 06:49:59 AM	964.400 PSIA 968.400 PSIA		
	12	May 11, 2011 00:49:59 AM May 11, 2011 06:54:59 AM	973.600 PSIA		
	13	May 11, 2011 06:59:59 AM	980.800 PSIA		and the second second second second
	14	May 11, 2011 07:04:58 AM	988.000 PSIA		
	15	May 11, 2011 07:09:59 AM	994.800 PSIA		
	16	May 11, 2011 07:15:00 AM	1001.600 PSIA		
	17	May 11, 2011 07:19:59 AM	1008.400 PSIA 1016.000 PSIA		
	18 19	May 11, 2011 07:25:00 AM May 11, 2011 07:29:59 AM	1016.000 PSIA 1026.600 PSIA		
	20	May 11, 2011 07:34:59 AM	1056.400 PSIA		
	21	May 11, 2011 07:39:59 AM	1084.800 PSIA		
	22	May 11, 2011 07:44:59 AM	1100.800 PSIA		
2	23	May 11, 2011 07:49:59 AM	1113.800 PSIA		A second
å.	24	May 11, 2011 07:54:59 AM	1125.600 PSIA	* .	
3	25 26	May 11, 2011 08:00:00 AM May 11, 2011 08:04:59 AM	1136.200 PSIA 1145.600 PSIA		
Ť	26 27	May 11, 2011 08:04:39 AM	1153.600 PSIA	•	
	28	May 11, 2011 08:14:59 AM	1161.400 PSIA		
	29	May 11, 2011 08:19:59 AM	1169.600 PSIA		
	30	May 11, 2011 08:24:58 AM	1177.000 PSIA		
	31	May 11, 2011 08:29:59 AM	1182.200 PSIA		
	32	May 11, 2011 08:34:59 AM	1203.000 PSIA 1221.400 PSIA		
	33 34	May 11, 2011 08:39:59 AM May 11, 2011 08:45:00 AM	1240.200 PSIA		
	35	May 11, 2011 08:49:58 AM	1256.000 PSIA		
	36	May 11, 2011 08:55:00 AM	1269.400 PSIA		
	37	May 11, 2011 08:59:58 AM	1279.000 PSIA		
	38	May 11, 2011 09:04:58 AM	1292.000 PSIA		
	39 40	May 11, 2011 09:09:59 AM May 11, 2011 09:14:59 AM	1301.200 PSIA 1309.400 PSIA		
	41	May 11, 2011 09:14:39 AM	1318.600 PSIA		
	42	May 11, 2011 09:24:58 AM	1329.800 PSIA		
	43	May 11, 2011 09:30:00 AM	1339.400 PSIA		
	44	May 11, 2011 09:34:59 AM	1358.400 PSIA		
	45	May 11, 2011 09:40:00 AM	1371.800 PSIA		
	46 47	May 11, 2011 09:44:59 AM May 11, 2011 09:49:59 AM	1382.800 PSIA 1393.800 PSIA		
	47 48	May 11, 2011 09:54:59 AM	1402.200 PSIA		
	49	May 11, 2011 09:59:59 AM	1412.000 PSIA		
	50	May 11, 2011 10:04:59 AM	1421.000 PSIA		
	51	May 11, 2011 10:09:59 AM	1427.600 PSIA		
	52	May 11, 2011 10:15:00 AM	1435.600 PSIA		
	53	May 11, 2011 10:19:59 AM	1441.200 PSIA		
	54 55	May 11, 2011 10:24:59 AM May 11, 2011 10:29:59 AM	1447.800 PSIA 1453.600 PSIA		
	56	May 11, 2011 10:34:59 AM	1468.200 PSIA		
	57	May 11, 2011 10:39:59 AM	1475.800 PSIA		
	58	May 11, 2011 10:44:59 AM	1481.200 PSIA		
	59 60	May 11, 2011 10:49:59 AM	1492.000 PSIA		
	60	May 11, 2011 10:54:59 AM	1496.800 PSIA		

May 11, 2011 11:00:00 AM	1504.600 PSIA
May 11, 2011 11:04:59 AM	1512.800 PSIA
May 11, 2011 11:10:00 AM	1517.000 PSIA
May 11, 2011 11:14:59 AM	1520.000 PSIA
May 11, 2011 11:19:59 AM	1525.800 PSIA
May 11, 2011 11:24:59 AM	1530.400 PSIA
May 11, 2011 11:29:59 AM	1535.200 PSIA
May 11, 2011 11:34:59 AM	1548.200 PSIA
May 11, 2011 11:39:59 AM	1553.600 PSIA
May 11, 2011 11:45:00 AM	1559.400 PSIA
May 11, 2011 11:49:59 AM	1565.400 PSIA
May 11, 2011 11:55:00 AM	1570.600 PSIA
May 11, 2011 11:59:58 AM	1578.000 PSIA
May 11, 2011 12:04:59 PM	1577.800 PSIA
May 11, 2011 12:09:58 PM	1583.600 PSIA
May 11, 2011 12:14:59 PM	1586.000 PSIA
May 11, 2011 12:19:59 PM	1588.200 PSIA
May 11, 2011 12:24:59 PM	1591.600 PSIA
May 11, 2011 12:30:00 PM	1594.400 PSIA
•	
	May 11, 2011 11:04:59 AM May 11, 2011 11:10:00 AM May 11, 2011 11:14:59 AM May 11, 2011 11:19:59 AM May 11, 2011 11:29:59 AM May 11, 2011 11:29:59 AM May 11, 2011 11:29:59 AM May 11, 2011 11:39:59 AM May 11, 2011 11:39:59 AM May 11, 2011 11:45:00 AM May 11, 2011 11:45:00 AM May 11, 2011 11:55:00 AM May 11, 2011 11:59:58 AM May 11, 2011 12:04:59 PM May 11, 2011 12:09:58 PM May 11, 2011 12:19:59 PM May 11, 2011 12:19:59 PM May 11, 2011 12:19:59 PM May 11, 2011 12:24:59 PM May 11, 2011 12:24:59 PM



Report Name:

Report Date:

File Name: Title:

Device ID:

Device: Hardware Revision: Serial Number:

Data Start Date: Data End Date: Reading Rate: Readings:

Last Calibration Date: Next Calibration Date: PrTemp1000 Data Table

May 16, 2011 01:53:55 PM MDT
C:\PTogram Files\PTC® Instruments 2.00\Federal 7-7-9-18 ISIP (5-11-2011).csv
Federal 7-7-9-18 ISIP (5-11-2011)
PrTemp1000 - Temperature and Pressure Recorder

REV2C (64K) M75866 PrTemp

May 11, 2011 12:30:19 PM MDT May 11, 2011 01:00:19 PM MDT

2 Seconds 1 to 31 of 31 Apr 12, 2011 Apr 12, 2012

<u>Reading</u>	Date and Time (MDT)	Absolute Pressure	<u>Annotation</u>
1	May 11, 2011 12:30:19 PM	1594.000 PSIA	
2	May 11, 2011 12:31:19 PM	1598.600 PSIA	
3	May 11, 2011 12:32:18 PM	1569.200 PSIA	
4	May 11, 2011 12:33:19 PM	1563.800 PSIA	
5	May 11, 2011 12:34:19 PM	1557.800 PSIA	
6	May 11, 2011 12:35:18 PM	1553.000 PSIA	
7	May 11, 2011 12:36:19 PM	1548.200 PSIA	
8	May 11, 2011 12:37:19 PM	1543.600 PSIA	
9	May 11, 2011 12:38:19 PM	1539.800 PSIA	
10	May 11, 2011 12:39:18 PM	1536.200 PSIA	
11	May 11, 2011 12:40:19 PM	1532.800 PSIA	
12	May 11, 2011 12:41:19 PM	1529.600 PSIA	
13	May 11, 2011 12:42:18 PM	1527.000 PSIA	
14	May 11, 2011 12:43:19 PM	1524.600 PSIA	
15	May 11, 2011 12:44:19 PM	1521.800 PSIA	
16	May 11, 2011 12:45:18 PM	1519.000 PSIA	
17	May 11, 2011 12:46:19 PM	1516.600 PSIA	
18	May 11, 2011 12:47:19 PM	1514.400 PSIA	
19	May 11, 2011 12:48:18 PM	1511.800 PSIA	
20	May 11, 2011 12:49:19 PM	1509.400 PSIA	
21	May 11, 2011 12:50:19 PM	1507.000 PSIA	
22	May 11, 2011 12:51:18 PM	1505.200 PSIA	
23	May 11, 2011 12:52:18 PM	1503.200 PSIA	
24	May 11, 2011 12:53:19 PM	1500.800 PSIA	
25	May 11, 2011 12:54:19 PM	1499.000 PSIA	
26	May 11, 2011 12:55:18 PM	1497.400 PSIA	
27	May 11, 2011 12:56:19 PM	1495.400 PSIA	
28	May 11, 2011 12:57:19 PM	1493.600 PSIA	
29	May 11, 2011 12:58:18 PM	1492.000 PSIA	
30	May 11, 2011 12:59:19 PM	1490.200 PSIA	
31	May 11, 2011 01:00:19 PM	1488.400 PSIA	

Federal 7-7-9-18 Rate Sheet (5-11-11)

	Control of the Contro						
Step # 1	Time:	6:35	6:40	6:45	6:50	6:55	7:00
200p	Rate:	50.6	50.6	50.5	50.5	50.5	50.5
		7.05	7.40	7.45	7.00	7.05	7,20
	Time:	7:05	7:10	7:15	7:20 50.4	7:25 50.3	7:30 50.3
•	Rate:	50.4	50.4	50.4	50.4	50.5	
	Time:	7:35	7:40	7:45	7:50	7:55	8:00
Step # 2	Rate:	100.3	100.3	100.3	100.3	100.2	100.2
	Time:	8:05	8:10	8:15	8:20	8:25	8:30
	Rate:	100.2	100.2	100.2	100.1	100.1	100.1
ż							
Stop # 2	Time:	8:35	8:40	8:45	8:50	8:55	9:00
Step # 3	Rate:	150.4	150.4	150.4	150.4	150.3	150.3
	Time:	9:05	9:10	9:15	9:20	9:25	9:30
	Rate:	150.3	150.2	150.2	150.2	150.1	150.1
	[0.25	0.40	0:45	9:50	9:55	10:00
Step # 4	Time:	9:35 200.5	9:40	9:45 200.5	200.4	200.3	200.3
	Rate:	200.5	200.3	200.5			
	Time:	10:05	10:10	10:15	10:20	10:25	10:30
	Rate:	200.3	200.3	200.2	200.2	200.2	200.1
				·		10.000	
a. "r	Time:	10:35	10:40	10:45	10:50	10:55	11.00
Step # 5	Rate:	250.4	250.4	250.3	250.2	250.2	250.2
	Time:	11:05	11:10	11:15	11:20	11:25	11:30
	Rate:	250.2	250.1	250.1	250.1	250	250
			44.40	44.45	44.50	44.55	40.00
Step # 6	Time:	11:35	11:40	11:45	11:50	11:55	12:00 300.4
	Rate:	300.6	300.6	300.6	300.5	300.5	300.4
	Time:	12:05	12:10	12:15	12:20	12:25	12:30
	Rate:	300.4	300.4	300.4	300.3	300.3	300.3
					,		

Sundry Number: 63238 API Well Number: 43013305590000

	STATE OF UTAH		FORM 9
	DEPARTMENT OF NATURAL RESOURCE DIVISION OF OIL, GAS, AND MIN		5.LEASE DESIGNATION AND SERIAL NUMBER: UTU-020252A
SUNDF	RY NOTICES AND REPORTS (ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:
	oposals to drill new wells, significantly d reenter plugged wells, or to drill horizon n for such proposals.		7.UNIT or CA AGREEMENT NAME: GMBU (GRRV)
1. TYPE OF WELL Water Injection Well			8. WELL NAME and NUMBER: ALLEN FED 32-6
2. NAME OF OPERATOR: NEWFIELD PRODUCTION CO	OMPANY		9. API NUMBER: 43013305590000
3. ADDRESS OF OPERATOR: Rt 3 Box 3630 , Myton, UT		PHONE NUMBER: Ext	9. FIELD and POOL or WILDCAT: MONUMENT BUTTE
4. LOCATION OF WELL FOOTAGES AT SURFACE: 2102 FNL 1949 FEL			COUNTY: DUCHESNE
QTR/QTR, SECTION, TOWNSI Qtr/Qtr: SWNE Section: (HIP, RANGE, MERIDIAN: 06 Township: 09.0S Range: 17.0E Meridi	an: S	STATE: UTAH
11. CHEC	K APPROPRIATE BOXES TO INDICAT	E NATURE OF NOTICE, REPOR	RT, OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF ACTION	
	ACIDIZE	ALTER CASING	CASING REPAIR
NOTICE OF INTENT Approximate date work will start:	CHANGE TO PREVIOUS PLANS	CHANGE TUBING	CHANGE WELL NAME
	CHANGE WELL STATUS	COMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE
SUBSEQUENT REPORT Date of Work Completion:	DEEPEN	FRACTURE TREAT	☐ NEW CONSTRUCTION
5/11/2015	OPERATOR CHANGE	PLUG AND ABANDON	PLUG BACK
SPUD REPORT	PRODUCTION START OR RESUME	RECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION
Date of Spud:	REPERFORATE CURRENT FORMATION	SIDETRACK TO REPAIR WELL	TEMPORARY ABANDON
	TUBING REPAIR	VENT OR FLARE	WATER DISPOSAL
DRILLING REPORT Report Date:	WATER SHUTOFF	SI TA STATUS EXTENSION	APD EXTENSION
		✓ OTHER	OTHER: 5 YR MIT
	WILDCAT WELL DETERMINATION	OTHER	·
5 YR MIT perform casing was pressur no pressure loss pressure was 1	COMPLETED OPERATIONS. Clearly show a med on the above listed well red up to 1214 psig and charts. The well was injecting duri 572 psig during the test. The vailable to witness the test. E	On 05/11/2015 the sed for 30 minutes with ag the test. The tbg re was not an EPA PA #UT22197-08173	Accepted by the Utah Division of Oil, Gas and Mining FOR RECORD ONLY May 12, 2015
Lucy Chavez-Naupoto	435 646-4874	Water Services Technician	
SIGNATURE N/A		DATE 5/12/2015	

Sundry Number: 63238 API Well Number: 43013305590000

Mechanical Integrity Test


Casing or Annulus Pressure Mechanical Integrity Test U.S. Environmental Protection Agency Underground Injection Control Program 999 18th Street, Suite 500 Denver, CO 80202-2466

EPA Witness:	Date: 5 / 11 / 15							
Test conducted by:	1715 WOLL	-PCS	***************************************		***************************************			
Others present:								
						-08/73		
Well Name: Allen Fe Field: TMBU Location: 5 WAKE Sec Operator: NFX Last MIT: /	: 6 T 9 N	18 R_17		Duches	as: AC TA	UC		
Is this a regularly scheduled Initial test for permit? Test after well rework? Well injecting during test? Pre-test casing/tubing annulu		Yes [X Yes [X Yes [] No If Yes, r		38 Q	bpd		
MIT DATA TABLE	Test #1		Test #2		Tes	st #3		
TUBING	PRESSURE							
Initial Pressure	1572	psig	· · · · · · · · · · · · · · · · · · ·	psig	4-112)	psig		
End of test pressure	1572	psig		psig	400	psig		
CASING / TUBING	ANNULUS	***************************************	PRESSURE					
0 minutes	1215	psig	٠	psig		psig		
5 minutes	1215	psig		psig		psig		
10 minutes	1215	psig		psig		psig		
15 minutes	1215	psig		psig		psig		
20 minutes	1215	psig		psig		psig		
25 minutes	1214	psig		psig		psig		
30 minutes	1214	psig	1	psig		psig		
minutes		psig		psig		psig		
minutes		psig		psig		psig		
RESULT .	[X] Pass	Fail	Pass]Fail	Pass]Fail		
Does the annulus pressure bu MECH	ild back up after t ANICAL II	he test ?	[] Yes [RITY PRE	∖j № SSURI	E TEST			

Additional comments for mechanical integrity pressure test, such as volume of fluid added to annulu
and bled back at end of test, reason for failing test (casing head leak, tubing leak, other), etc.:

Signature of Witness:

Sundry Number: 63238 API Well Number: 43013305590000




NEWFIELD

Schematic

Well Name: Allen 32-6-9-17

Surface Legal Location 06-9S-17E	43013	Well RC 305590000 500150962	Lease	State/Province Utah	Field Name GMBU CTB5	County Duchesne
Spud Date Rig Release Date On Production 5/28/1981	original KB Elevation (ft) 5,337	Ground Elevation (ft) 5,323	Total Depth All (T	(ftKB)	PBTD (All) (ftKB) Original Hole -	5,365.0

Most Recent Job Secondary Job Type Primary Job Type Job Start Date Job End Date 5/11/2015



NEWFIELD

www.newfield.com

Newfield Wellbore Diagram Data Allen 32-6-9-17

					API/UWI 43013305590000		Lease	
County State/Province					Basin		Field Name	
Ouchesne		Utah					GMBU CTB5	
Vell Start Date 4/23/1981	1,1 = 11			Final Rig Release Date		On Production Date 5/28	/1981	
riginal KB Elevation (ft) Ground Elevation		Total Depth (ft	KB)		Total Depth All (TVD) (ftKB)	γ	PBTD (All) (ftKB)	
5,337	5,323	<u> </u>		5,401.0	1		Original Hole - 5,36	5.0
asing Strings Csg Des		Rún D)ate	OD.(in)	ID (in)	Wt/Len (lb/ft)	Grade	Set Depth (ftKB)
urface		4/24/1981		8 5/8	8.097	24.00		2
Production		5/7/1981		5 1/2	5.012	14.00	J-55	5,4
ement			100		Van Comment			
tring: Surface, 260ftKB 4/24/1	981		indian					
ementing Company			<u></u>	Nº3	Top Depth (ftKB)	Bottom Depth (ftKB)	Full Return?	Vol Cement Ret (bbl)
					14.0			Fater led Tay (BUD)
Fluid Description				Fluid Type Lead	Amount (sacks) 190	Class H	Estimated Top (ftKB)	
tring: Production, 5,401ftKB	5/7/198 ⁻	1	7.7		<u> </u>			And the second of the second o
ementing Company					Top Depth (flKB)	Bottom Depth (ftKB)	Full Return?	Voi Cement Ret (bbi)
uid Description					2,200.0 Fluid Type	5,401.0 Amount (sacks)	Class	Estimated Top (ftKB)
					Lead		50/50 POZ	3,80
tring: Production, 5,401ftKB 1	12/1/19	30						
ementing Company					Top Depth (ftKB) 4,245.5	Bottom Depth (ftKB) 4,289.5	Full Return?	Vol Cement Ret (bbi)
uid Description					Fluid Type	Amount (sacks)	Class	Estimated Top (ftKB)
75 SKS CLASS G W 2% CaCl				Lead		G	4,24	
ubing Strings ubing Description					Run Date		Set Depth (ftKB)	
ubing						2010	Sar Debrii (IIVB)	4,20
item Des	Jts	OD (in)	ID (in)	Wt (lb/ft)	Grade	Len (ft)	Top (ftKB)	8tm (ftKB)
ubing	133	2 3/8	1.995	4.70	J-55	4,185.90	14.0	4,19
ump Seating Nipple	1	2 3/8	1.995			1.10	4,199.9	4,20
acker	1	4.95	1.995			2.50	4,201.0	4,20
/ireline Guide	1	2 3/8	1.995			5.00	4,203.5	4,20
od Strings od Description					Run Date	· · · · · · · · · · · · · · · · · · ·	Set Depth (ftKB)	
a bosarpion					Nun Date		Sar Dopor (rand)	
item Des	Jts	OD (i	in)	VVt (lb/ft)	Grade	Len (ft)	Top (ftKB)	Blm (ftKB)
		<u> </u>						
ther in Hole			1.1.					
	. D	es			Top (ftKB)	Btm (ftKB)	Run Date	Pull Date
					5,350	5,365	12/20/2003	J
erforation intervals Stage# Zone		Top (ft	KB)	Btm (ftKB)	Shot Dens (shots/ft)	Phasing (*)	Nom Hole Dia (in)	Date
3			4,246	4,252		90		10/14/1990
3			4,283	4,289	4	90	İ	10/14/1990
4 D1, Original Hole			4,772	4,781	3	120	0.360	6/3/2010
2			4,912	4,934	2	180		5/21/1981
1		! L	5,232	5,254	2	180		5/16/1981
timulations & Treatments								
Stage# ISIP (psi		Frac Gradie	nt (psi/ft)	Max Rate (bbl/min)	Max PSI (psi)	Total Clean Vol (bbl)	Total Siurry Vol (bbi)	Vol Recov (bbl)
	2,000	İ	}		2,600			
	2040				0.050			1
	2,010 1,741		ادور	17.0	2,950			
			0.84	17.0	4,843			<u> </u>
Towns of	1,741							
					Total Ade	d Amount		
roppant Total Prop Vol F Stage# (lb)					rotarAu			
roppant Total Prop Vol F		Proppant E			70tal Au			
Proppant Stage# Total Prop Vol I (lb)		Proppant B	Bulk Sand	67000 lb	(Ola) Au			
Proppant Stage# Total Prop Vol F (lb)			Bulk Sand Bulk Sand	67000 lb 129000 lb	Total Au			

Page 1/1

Report Printed: 5/12/2015